

Safety Data Sheet

Copyright, 2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 19-2499-2
 Version Number:
 9.08

 Issue Date:
 09/01/23
 Supercedes Date:
 08/29/23

SECTION 1: Identification

1.1. Product identifier

3M Fire Barrier Watertight Sealant 3000 WT

Product Identification Numbers

98-0400-5503-4, 98-0400-5504-2, 98-0400-5553-9 7000006386, 7100006306, 7000059413

1.2. Recommended use and restrictions on use

Recommended use

Caulk, Fire barrier caulking.

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Industrial Adhesives and Tapes Division **ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2A.

Skin Sensitizer: Category 1. Reproductive Toxicity: Category 2. Carcinogenicity: Category 1B.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms





Hazard Statements

Causes serious eye irritation.
May cause an allergic skin reaction.
Suspected of damaging fertility or the unborn child.
May cause cancer.

Causes damage to organs through prolonged or repeated exposure: kidney/urinary tract |

May cause damage to organs through prolonged or repeated exposure: blood or blood-forming organs | respiratory system |

Precautionary Statements

General:

Keep out of reach of children.

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Supplemental Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Melamine	108-78-1	30 - 40 Trade Secret *
Siloxanes and Silicones, Di-Me, Hydroxy-Terminated	70131-67-8	15 - 40 Trade Secret *

Page 2 of 14

Graphite	7782-42-5	10 - 25 Trade Secret *
Poly (Dimethylsiloxane)	63148-62-9	10 - 25 Trade Secret *
Methyl Tris(2-Butylideneaminooxy)Silane	22984-54-9	3 - 5 Trade Secret *
Silica	7631-86-9	<= 3 Trade Secret *
(3-Aminopropyl)Triethoxysilane	919-30-2	< 1 Trade Secret *
Me Et Ketoxime	96-29-7	<= 1 Trade Secret *
3-Iodo-2-Propynyl Butylcarbamate	55406-53-6	< 0.1 Trade Secret *
Octamethylcyclotetrasiloxane	556-67-2	< 0.1 Trade Secret *

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Formaldehyde	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Oxides of Nitrogen	During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Melamine	108-78-1	AIHA	TWA(inhalable particulates):3 mg/m3	
Octamethylcyclotetrasiloxane	556-67-2	AIHA	TWA:10 ppm	
DUST, INERT OR NUISANCE	7631-86-9	OSHA	TWA(as total dust):15 mg/m3;TWA(as total dust):50 millions of particles/cu. ft.(15 mg/m3);TWA(respirable fraction):5 mg/m3;TWA(respirable fraction):15 millions of particles/cu. ft.(5 mg/m3)	
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	7631-86-9	ACGIH	TWA(inhalable particulates):10 mg/m3	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	7631-86-9	ACGIH	TWA(respirable particles):3 mg/m3	
Graphite	7782-42-5	ACGIH	TWA(respirable fraction):2 mg/m3	

Page 4 of 14

Graphite	7782-42-5	OSHA	TWA:15 millions of	
			particles/cu. ft.	
Me Et Ketoxime	96-29-7	AIHA	TWA:36 mg/m3(10 ppm)	Dermal Sensitizer

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide ventilated enclosure for curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Solid
Color Black, Gray

Flammable Limits(UEL)

Specific Physical Form: Paste
Odor Silicone

Odor threshold No Data Available рH Not Applicable **Melting point** Not Applicable **Boiling Point** No Data Available Flash Point No flash point **Evaporation rate** No Data Available Not Classified Flammability (solid, gas) Flammable Limits(LEL) No Data Available

Vapor PressureNilVapor DensityNil

Specific Gravity 1.25 [Ref Std:WATER=1]

Solubility in Water Nil

Solubility- non-water

Partition coefficient: n-octanol/ water

Autoignition temperature

Decomposition temperature

Viscosity

No Data Available

Volatile Organic Compounds <=5.3 % weight [*Test Method*:tested per EPA method 24]

No Data Available

Percent volatile No Data Available

VOC Less H2O & Exempt Solvents <=65 g/l [Test Method:tested per EPA method 24]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Not determined

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Hematopoietic Effects: Signs/symptoms may include generalized weakness, fatigue and alterations in numbers of circulating blood cells.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Melamine	108-78-1	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Melamine	Dermal	Rabbit	LD50 > 1,000 mg/kg
Melamine	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.19 mg/l
Melamine	Ingestion	Rat	LD50 3,161 mg/kg
Siloxanes and Silicones, Di-Me, Hydroxy-Terminated	Dermal	Rabbit	LD50 > 16,000 mg/kg
Siloxanes and Silicones, Di-Me, Hydroxy-Terminated	Ingestion	Rat	LD50 > 64,000 mg/kg
Graphite	Dermal		LD50 estimated to be > 5,000 mg/kg
Poly (Dimethylsiloxane)	Dermal	Rabbit	LD50 > 19,400 mg/kg
Graphite	Ingestion	Rat	LD50 > 2,000 mg/kg
Poly (Dimethylsiloxane)	Ingestion	Rat	LD50 > 17,000 mg/kg
Methyl Tris(2-Butylideneaminooxy)Silane	Dermal	Rat	LD50 > 2,000 mg/kg
Methyl Tris(2-Butylideneaminooxy)Silane	Ingestion	Rat	LD50 2,260 mg/kg
Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Me Et Ketoxime	Dermal	official classifica tion	LD50 1,100 mg/kg
Me Et Ketoxime	Ingestion	official classifica tion	LD50 100 mg/kg
Me Et Ketoxime	Inhalation- Vapor	Rat	LC50 estimated to be 20 - 50 mg/l
(3-Aminopropyl)Triethoxysilane	Dermal	Rabbit	LD50 4,290 mg/kg
(3-Aminopropyl)Triethoxysilane	Ingestion	Rat	LD50 1,570 mg/kg
Octamethylcyclotetrasiloxane	Dermal	Rat	LD50 > 2,400 mg/kg
Octamethylcyclotetrasiloxane	Inhalation- Dust/Mist (4 hours)	Rat	LC50 36 mg/l
Octamethylcyclotetrasiloxane	Ingestion	Rat	LD50 > 5,000 mg/kg
3-Iodo-2-Propynyl Butylcarbamate	Dermal	Rabbit	LD50 > 2,000 mg/kg
3-Iodo-2-Propynyl Butylcarbamate	Inhalation- Dust/Mist	Rat	LC50 0.67 mg/l
	(4 hours)		

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Melamine	Rabbit	No significant irritation
Graphite	Rabbit	No significant irritation
Poly (Dimethylsiloxane)	Rabbit	No significant irritation
Methyl Tris(2-Butylideneaminooxy)Silane	Rabbit	No significant irritation
Silica	Rabbit	No significant irritation
Me Et Ketoxime	Rabbit	Irritant
(3-Aminopropyl)Triethoxysilane	Rabbit	Corrosive
Octamethylcyclotetrasiloxane	Rabbit	Minimal irritation
3-Iodo-2-Propynyl Butylcarbamate	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Melamine	Rabbit	No significant irritation

Page 8 of 14

Graphite	Rabbit	No significant irritation
Poly (Dimethylsiloxane)	Rabbit	No significant irritation
Methyl Tris(2-Butylideneaminooxy)Silane	Rabbit	Moderate irritant
Silica	Rabbit	No significant irritation
Me Et Ketoxime	Rabbit	Corrosive
(3-Aminopropyl)Triethoxysilane	Rabbit	Corrosive
Octamethylcyclotetrasiloxane	Rabbit	No significant irritation
3-Iodo-2-Propynyl Butylcarbamate	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
Melamine	Guinea	Not classified
	pig	
Methyl Tris(2-Butylideneaminooxy)Silane	Guinea	Sensitizing
	pig	
Silica	Human	Not classified
	and	
	animal	
Me Et Ketoxime	Guinea	Sensitizing
	pig	
(3-Aminopropyl)Triethoxysilane	Guinea	Sensitizing
	pig	
Octamethylcyclotetrasiloxane	Human	Not classified
	and	
	animal	
3-Iodo-2-Propynyl Butylcarbamate	Multiple	Sensitizing
	animal	
	species	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Melamine	In Vitro	Not mutagenic
Melamine	In vivo	Not mutagenic
Siloxanes and Silicones, Di-Me, Hydroxy-Terminated	In Vitro	Not mutagenic
Graphite	In Vitro	Some positive data exist, but the data are not sufficient for classification
Methyl Tris(2-Butylideneaminooxy)Silane	In Vitro	Not mutagenic
Silica	In Vitro	Not mutagenic
Me Et Ketoxime	In Vitro	Not mutagenic
Me Et Ketoxime	In vivo	Not mutagenic
Octamethylcyclotetrasiloxane	In Vitro	Some positive data exist, but the data are not sufficient for classification
3-Iodo-2-Propynyl Butylcarbamate	In Vitro	Not mutagenic
3-Iodo-2-Propynyl Butylcarbamate	In vivo	Not mutagenic

Carcinogenicity

euremogeniery			
Name	Route	Species	Value
Melamine	Ingestion	Multiple animal species	Carcinogenic
Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Me Et Ketoxime	Inhalation	Multiple animal species	Carcinogenic
3-Iodo-2-Propynyl Butylcarbamate	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Page 9 of 14 Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Melamine	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,227 mg/kg/day	2 generation
Melamine	Ingestion	Not classified for development	Rat	NOAEL 1,060 mg/kg/day	during organogenesi s
Melamine	Ingestion	Toxic to male reproduction	Rat	NOAEL 89 mg/kg/day	2 generation
Methyl Tris(2-Butylideneaminooxy)Silane	Ingestion	Not classified for female reproduction	Rat	NOAEL 250 mg/kg/day	premating into lactation
Methyl Tris(2-Butylideneaminooxy)Silane	Ingestion	Not classified for male reproduction	Rat	NOAEL 250 mg/kg/day	28 days
Methyl Tris(2-Butylideneaminooxy)Silane	Ingestion	Not classified for development	Rat	NOAEL 250 mg/kg/day	premating into lactation
Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s
Me Et Ketoxime	Ingestion	Not classified for female reproduction	Rat	NOAEL 200 mg/kg/day	2 generation
Me Et Ketoxime	Ingestion	Not classified for male reproduction	Rat	NOAEL 200 mg/kg/day	2 generation
Me Et Ketoxime	Ingestion	Not classified for development	Rat	NOAEL 600 mg/kg/day	during organogenesi s
Octamethylcyclotetrasiloxane	Inhalation	Not classified for male reproduction	Rat	NOAEL 8.5 mg/l	2 generation
Octamethylcyclotetrasiloxane	Ingestion	Toxic to female reproduction	Rabbit	NOAEL 50 mg/kg/day	during organogenesi s
Octamethylcyclotetrasiloxane	Inhalation	Toxic to female reproduction	Rat	NOAEL 3.6 mg/l	2 generation
3-Iodo-2-Propynyl Butylcarbamate	Ingestion	Not classified for female reproduction	Rat	NOAEL 37.5 mg/kg/day	2 generation
3-Iodo-2-Propynyl Butylcarbamate	Ingestion	Not classified for male reproduction	Rat	NOAEL 37.5 mg/kg/day	2 generation
3-Iodo-2-Propynyl Butylcarbamate	Ingestion	Not classified for development	Rat	NOAEL 50 mg/kg/day	during organogenesi s

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Methyl Tris(2- Butylideneaminooxy)Silan e	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Me Et Ketoxime	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Me Et Ketoxime	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL 100 mg/kg	
3-Iodo-2-Propynyl Butylcarbamate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not Available	

Specific Target Organ Toxicity - repeated exposure

14

		1.1		7	Y 0 1 F7	Duration
Melamine	Ingestion	kidney and/or bladder	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 44.6 mg/kg/day	90 days
Melamine	Ingestion	heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system respiratory system	Not classified	Rat	NOAEL 1,400 mg/kg/day	90 days
Graphite	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Methyl Tris(2- Butylideneaminooxy)Silan e	Ingestion	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 10 mg/kg/day	28 days
Methyl Tris(2- Butylideneaminooxy)Silan e	Ingestion	endocrine system liver nervous system kidney and/or bladder	Not classified	Rat	NOAEL 250 mg/kg/day	28 days
Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Me Et Ketoxime	Inhalation	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 0.36 mg/l	28 days
Me Et Ketoxime	Inhalation	respiratory system	May cause damage to organs though prolonged or repeated exposure	Mouse	NOAEL 0.01 mg/l	90 days
Me Et Ketoxime	Inhalation	liver	Not classified	Rat	NOAEL 1.44 mg/l	28 days
Me Et Ketoxime	Ingestion	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 25 mg/kg/day	90 days
Me Et Ketoxime	Ingestion	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 100 mg/kg/day	90 days
Me Et Ketoxime	Ingestion	nervous system	Not classified	Rat	NOAEL 400 mg/kg/day	90 days
Me Et Ketoxime	Ingestion	liver kidney and/or bladder heart endocrine system bone, teeth, nails, and/or hair immune system	Not classified	Rat	NOAEL 335 mg/kg/day	90 days
Octamethylcyclotetrasiloxa ne	Dermal	hematopoietic system	Not classified	Rabbit	NOAEL 960 mg/kg/day	3 weeks
Octamethylcyclotetrasiloxa ne	Inhalation	liver	Not classified	Rat	NOAEL 8.5 mg/l	13 weeks
Octamethylcyclotetrasiloxa ne	Inhalation	endocrine system immune system kidney and/or bladder	Not classified	Rat	NOAEL 8.5 mg/l	2 generation
Octamethylcyclotetrasiloxa ne	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 8.5 mg/l	13 weeks
Octamethylcyclotetrasiloxa ne	Ingestion	liver	Not classified	Rat	NOAEL 1,600 mg/kg/day	2 weeks
3-Iodo-2-Propynyl Butylcarbamate	Dermal	skin heart hematopoietic system liver eyes kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 500 mg/kg/day	90 days
3-Iodo-2-Propynyl Butylcarbamate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.00116 mg/l	90 days

Page 11 **of** 14

3-Iodo-2-Propynyl	Inhalation	heart skin	Not classified	Rat	NOAEL	90 days
Butylcarbamate		endocrine system gastrointestinal tract			0.00625 mg/l	
		bone, teeth, nails,				
		and/or hair				
		hematopoietic system liver				
		immune system				
		muscles nervous				
		system eyes				
		kidney and/or				
		bladder vascular				
		system				
3-Iodo-2-Propynyl	Ingestion	liver hematopoietic	Not classified	Rat	NOAEL 125	90 days
Butylcarbamate		system eyes			mg/kg/day	

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical	Hazards
----------	---------

Not applicable

Health Hazards

Carcinogenicity

Reproductive toxicity

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: *3 Flammability: 1 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards

in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

 Document Group:
 19-2499-2
 Version Number:
 9.08

 Issue Date:
 09/01/23
 Supercedes Date:
 08/29/23

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com