

### NOTES:

- 1. IT IS NECESSARY TO ENSURE MINIMUM DIMENSIONS SHOWN ARE SUITABLE FOR EXISTING GROUND CONDITIONS. ENGINEERING ADVICE MAY BE REQUIRED.
- 2. MINIMUM CONCRETE STRENGTH OF 4,000 PSI IS RECOMMENDED. CONCRETE SHOULD BE VIBRATED TO ELIMINATE AIR POCKETS.
- 3. EXPANSION AND CONTRACTION CONTROL JOINTS AND REINFORCEMENT ARE RECOMMENDED TO PROTECT CHANNEL AND CONCRETE SURROUND. *ENGINEERING ADVICE MAY BE REQUIRED*. .
- 4. REFER TO ACO'S LATEST INSTALLATION INSTRUCTIONS FOR FURTHER DETAILS.

### SPECIFICATION CLAUSE

## **SPORT 2000**

### **GENERAL**

THE SURFACE DRAINAGE SYSTEM SHALL BE POLYMER CONCRETE SYSTEM 2000 CHANNEL SYSTEM AS MANUFACTURED BY ACO POLYMER PRODUCTS, INC.

### **MATERIALS**

CHANNELS SHALL BE MANUFACTURED FROM POLYESTER RESIN POLYMER CONCRETE. MINIMUM PROPERTIES OF POLYMER CONCRETE WILL BE AS FOLLOWS:

COMPRESSIVE STRENGTH: 14,000 PSI FLEXURAL STRENGTH: 4,000 PSI TENSILE STRENGTH: 1,500 PSI WATER ABSORPTION: 0.07% FROST PROOF YES DILUTE ACID AND ALKALI RESISTANT YES B117 SALT SPRAY TEST COMPLIANT YES

THE SYSTEM SHALL BE 4" (100mm) NOMINAL INTERNAL WIDTH WITH A 6.1" (155mm) OVERALL WIDTH. THE EVEN TOP CHANNEL SHALL BE 9.8" (249mm) IN OVERALL DEPTH. 10.3" (261mm) FOR UN-EVEN TOP. THE MINIMUM SLOT DIMENSION SHALL BE 0.625" (15mm). ALL CHANNELS SHALL BE INTERLOCKING WITH A MALE/FEMALE JOINT.

THE COMPLETE DRAINAGE SYSTEM SHALL BE BY ACO POLYMER PRODUCTS, INC. ANY DEVIATION OR PARTIAL SYSTEM DESIGN AND/OR IMPROPER INSTALLATION WILL VOID ANY AND ALL WARRANTIES PROVIDED BY ACO POLYMER PRODUCTS, INC.

THE SYSTEM SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS AND RECOMMENDATIONS.

REFER TO ARCHITECT'S PLANS FOR TRENCH AND CATCH BASIN LOCATION.

# S2000-FCGN A C O DATE: 12/02/13

# **SYSTEM 2000:**

Full/Partial Concrete, Grass & Non-Porous Synthetic Surface

**INSTALLATION DRAWING - ACO SPORT** 

 ACO Polymer Products, Inc.

 825 W. Beechcraft St
 P.O. Box 245
 4211 P

825 W. Beechcraft St Casa Grande, AZ 85122 Tel: 520-421-9988 Fax: 520-421-9899 P.O. Box 245 Chardon, OH 44024 Tel: 440-285-7000 Fax: 440-285-8517 4211 Pleasant Rd. Fort Mill, SC 29708 Tel: 800-543-4764 Fax: 803-802-1063

Arizona Tel: 888-490-9552 e-mail: sales@acousa.com

Ohio Tel: 800-543-4764

www.acousa.com

South Carolina Tel: 800-622-2377