Product Features

- Certified to EN 1433 Load Class C- 56,000 lbs 968 psi
- Supplied with a quantity of two (1/2 -13 x 13/4") socket head bolts to lock down grate
- Manufactured from 0.197" (5mm) thick stainless steel bars
- Suitable for use with F660 catch basin



Specifications

General

The surface drainage system shall be ACO Drain F660 catch basin stainless steel bar grate with bolt locking as manufactured by ACO, Inc. or similar approved.

Materials

The covers shall be manufactured from stainless steel and have *minimum* properties as follows:

- Independently certified to meet Load Class C to EN 1433 - 56,000 lbs - 968 psi
- Intake area of 267 sq. in. (1,722.5 cm²) per 24" grate

The overall width of 14.75" (375mm) and overall length of 24" (610mm) for part number 97443. Slots measure 3.3" (84mm) by 1.0" (25mm) and 3.0" (76mm) by 1.0" (25mm).


Installation

The trench drain* or catch basin* system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.


* delete as appropriate



ACO DRAIN F660 Stainless steel bar grate







Description	Part No.	Length inches <i>(mm)</i>	Width inches <i>(mm)</i>	Weight Ibs.
F660 Stainless steel bar grate	97442	24.00 (610)	14.75" (375)	35.2
Replacement stainless steel socket head bolts (Qty 2)	93897		-	0.4



Northeast Sales Office 9470 Pinecone Drive Mentor, OH 44060 Tel: (440) 639-7230 Toll free: (800) 543-4764 Fax: (440) 639-7235 West Sales Office 825 W. Beechcraft St. Casa Grande, AZ 85122 Tel: (520) 421-9988 Toll Free: (888) 490-9552 Fax: (520) 421-9899 **Southeast Sales Office** 4211 Pleasant Road Fort Mill, SC 29708 Toll free: (800) 543-4764 Fax: (803) 802-1063



Electronic Contact: info@ACODrain.us www.ACODrain.us



© April 2018, ACO, Inc. This information is believed to be accurate but it is not guaranteed to be so. We cannot assume liability for results that buyer obtains with our product since conditions of use are beyond the control of the company. It is the customer's responsibility to evaluate suitability and safety of product for his own use. ACO, Inc. reserves the right to change the product and specifications without notice.

April 2018