F880 Galvanized steel bar grate



Product Features

- Certified to EN 1433 Load Class C- 56,000 lbs 739 psi
- Supplied with ½ -13 x 1¾" socket head bolts to lock down grate
- Manufactured from 0.236" (6mm) thick galvanized steel bars
- Suitable for use with F880 catch basin



Specifications

General

The surface drainage system shall be ACO Drain F880 catch basin complete with galvanized steel bar grate with bolt locking as manufactured by ACO, Inc. or similar approved.

Materials

The covers shall be manufactured from galvanized steel and have **minimum** properties as follows:

- Independently certified to meet Load Class C to EN 1433 - 56,000 lbs - 739 psi
- Intake area of 456 sq. in. (2941.9 cm²) per grate

The overall width of 26.75" (680mm) and overall length of 24" (610mm). Slots measure 3.6" (91mm) by 1.0" (25mm).

Installation

The trench drain* or catch basin* system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

* delete as appropriate






F880 Galvanized steel bar grate



Plan view



Side elevation

ACO Specification Information





Description	Part No.	Length inches <i>(mm)</i>	Width inches (mm)	Weight lbs.
F880 Galvanized steel bar grate Replacement galvanized steel socket head bolts (Qty 4)	97452 93895	24.00 (610)	26.75 (680)	63.8 0.4

ACO, Inc. **Northeast Sales Office** 9470 Pinecone Drive

Mentor, OH 44060 Tel: (440) 639-7230 Toll free: (800) 543-4764 Fax: (440) 639-7235

West Sales Office

825 W. Beechcraft St. Casa Grande, AZ 85122 Tel: (520) 421-9988 Toll Free: (888) 490-9552 Fax: (520) 421-9899

Southeast Sales Office

4211 Pleasant Road Fort Mill, SC 29708 Toll free: (800) 543-4764 Fax: (803) 802-1063



Electronic Contact: info@ACODrain.us www.ACODrain.us



© April 2018, ACO, Inc. This information is believed to be accurate but it is not guaranteed to be so. We cannot assume liability for results that buyer obtains with our product since conditions of use are beyond the control of the company. It is the customer's responsibility to evaluate suitability and safety of product for his own use. ACO, Inc. reserves the right to change the product and specifications without notice.