# FlowDrain - FG200 Ductile Iron Slotted Grate














Side Front





## **Product Features**

- Certified to EN 1433 Load Class E 134,885 lbs 2,321 psi
- Bolted locking system
- Suitable for use with FG200 channels
- Manufactured from ductile iron to ASTM A 536 Grade 80-55-06
- E-coated for improved resistance against corrosion

Parts	Part No.	Length in (mm)	Width in (mm)	Weight Ibs
FG200 Ductile Iron Slotted Grate	93896	18.00 (457)	10.00 (254)	28.7
Replacement Stainless Steel Hex Head Bolts (Qty 2)	93892	-	-	0.2

# **Specifications**

#### General

The surface drainage system shall be ACO Drain FG200 channels complete with ACO FG200 ductile iron slotted grate with boltlocking as manufactured by ACO, Inc. or similar approved.

#### Materials

The covers shall be manufactured from ductile iron and have minimum properties as follows:

- Independently certified to meet Load Class E to EN 1433 - 134,885 lbs - 2,321 psi.
- Ductile iron to ASTM 536 Grade 80-55-06.
- Intake area of 58.7 in² (378.7 cm²) per 18" of grate.

The overall width of 10.00" (254 mm) and overall length of 18.00" (457 mm). Slots measure 7.87" (200 mm) by 0.61" (15 mm).

#### Grates

Grate is slotted ductile iron. Ductile iron ASTM 536 - Grade 80-55-06. After removal of the grates there shall be uninterrupted access to the trench to aid maintenence.

### Installation

The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.



EN 1433 Load Class E 134,885 lbs - 2,321 psi



200,000 lb Proof Load

# ACO, Inc.

West Sales Office 825 W. Beechcraft Street Casa Grande, AZ 85122 Tel: (520) 421-9988 Toll-Free: (888) 490-9552 Fax: (520) 421-9899 Northeast Sales Office 9470 Pinecone Drive Mentor, OH 44060 Tel: (440) 639-7230 Toll-Free: (800) 543-4764 Fax: (440) 639-7235 Southeast Sales Office 4211 Pleasant Road Fort Mill, SC 29708 Toll-Free: (800) 543-4764 Fax: (803) 802-1063 info@acousa.com www.acousa.com

© February 2021 ACO, Inc.

All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions of use are suitable. ACO, Inc. reserves the right to change products and specifications without notice.



