

ARVB

VALVE BOXES Recessed

Application

- Provides easy access to all types of valves and controls that need to be concealed in the wall, but protected by a fully enclosed box

Product Features

- The depth of the valve box can be modified to meet all the valve and control requirements
- When required, vision panels, louvers, engrave plates can be supplied, along with special holes for pipes or conduits

ARVB Valve Box Specifications:

Material: Stainless Steel or Steel: 16 gauge door, frame, box

Door: 16 gauge, flush to frame — rounded safety corners

Frame: 16 gauge, one piece outer flange welded to box

Box: 16 gauge, fully enclosed, completely attached to frame.

When required box can be made with open back.

Hinge: Continuous, concealed

Latch: Cylinder lock & key, Also available: Slotted Screwdriver Cam Latch, spanner head cam latch, flush paddle handle, thumb turn latch.

Finish: Stainless Steel: Type 304 - #4 satin polish. Steel: 5 stage iron phosphate preparation with prime coat of White alkyd baked enamel

ARVB STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Opening	Weight per Door	
Inches	mm		lbs.	kg.
8 x 8 x 4	203 x 203 x 102	1	5	2.3
8 x 8 x 6	203 x 203 x 152	1	7	3.2
8 x 8 x 8	203 x 203 x 203	1	9	4.1
12 x 12 x 4	305 x 305 x 102	1	9	4.1
12 x 12 x 6	305 x 305 x 152	1	12	5.5
12 x 12 x 8	305 x 305 x 203	1	14	6.4

Wall opening is W + 3/8" (9 mm)

For detailed specifications see submittal sheet

