

FB-5060-DW

FIRE RATED UNINSULATED

- for Drywall walls

Application

- For drywall walls applications.
- Designed to maintain continuity in a 2 hour fire rated wall, when temperature rise is not a factor

Product Features

- Concealed hinge
- Self-closing
- Self-Latching
- Drywall taping bead
- Inside latch release
- Available with a removable door panel

FB-5060-DW Access Door Specifications:

Material: Steel or Stainless Steel

Door: 16 gauge

Mounting Frame: 16 gauge. Flush to frame with reinforced edges, drywall taping bead flange

Hinge: Concealed

Fire Rating (Walls): UL — 1-1/2 hour "B" label. ULC — 2 hour "B" label. (optional) Max size 36 x 48

Standard Latch: Universal self-latching bolt, operated by either a knurled knob or flush key. When master keying is required, doors can be prepared for rim or mortise cylinder locks.

Finish: Steel: 5 stage iron phosphate preparation with prime coat of White alkyd baked-on enamel

Stainless Steel: Type 304 - #4 satin polish optional

FB-5060-DW STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Latches	Weight per Door	
Inches	mm		lbs.	kg.
8 X 8	203 X 203	1	5.5	2.5
10 X 10	254 X 254	1	6.7	2.9
12 X 12	305 X 305	1	8.3	3.8
14 X 14	355 X 355	1	9.5	4.3
16 X 16	406 X 406	1	11.5	5.2
18 X 18	457 X 457	1	14.3	6.5
22 X 30	559 X 759	1	32.5	14.5
22 X 36	559 X 914	2	28	12.7
24 X 24	610 X 610	1	20.3	9.2
24 X 36	610 X 914	2	28.5	12.9
24 X 48	610 X 1219	2	34	15.4
30 X 30	762 X 762	2	28.5	12.9
36 X 36	914 X 914	2	38	17.2
36 X 48	914 X 1220	2	47.5	21.5

Wall opening is W + 3/8" (9 mm)

For detailed specifications see submittal sheet

