

FW-5050-UP

Fire Rated Insulated Upswing Door for Ceilings

Ceiling Position

Application

- An insulated, fire rated access door for inward opening in ceilings

Product Features

- For fire rated ceilings, this door has been approved by Warnock Hersey International for 3 hours (max. size to 24" x 36")
- Insulated Door Panel
- Self-Closing
- Self-Latching
- Inside Latch Release

FW-5050-UP Access Door Specifications:

Material: Steel or Stainless Steel

Door: 16 gauge, Flush to frame with reinforced edges filled with 2" thick fire insulation

Mounting Frame: 16 gauge mounting frame, with trim 1" wide

Hinge: Concealed with coil spring for dampening

Fire Rating: For walls: UL — 1-1/2 hour "B" label. ULC — 2 hour "B" label. Max size: 24 x 36. For Ceilings: Warnock Hersey International 3 hour rated in a non-combustible ceiling. 1 hour rated in a combustibile ceiling. Max size: 24x 36

Standard Latch: L Handle - operable from both sides

Finish: Steel: 5 stage iron phosphate preparation with prime coat of white baked-on enamel. Stainless Steel: Type 304 - #4 satin polish

FW-5050-UP STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Latches	Weight per Door	
Inches	mm		lbs.	kg.
22 X 36	559 X 914	2	35	15.9
22 X 30	559 X 762	2	34	15.4
24 X 24	610 X 610	1	28	12.7
24 X 36	610 X 914	2	38	18.1

Wall or ceiling opening is W + 1/2" (12 mm)
For detailed specifications see submittal sheet

