

# MS-7000

## SECURITY DOORS for Medium Security

### Application

- For use in medium security jails, prisons, psychiatric institutions, etc.
- Medium duty security access door

### Product Features

- 12 Gauge door and frame
- A one piece trim flange and continuous concealed hinge
- Door panel features rounded safety corners

### MS-7000 Access Door Specifications:

**Material:** Steel or Stainless Steel

**Door / Mounting Frame:** 12 gauge door and mounting frame

Flush to frame with rounded corners and reinforced panel

One piece outer flange welded to mounting frame

**Hinge:** Continuous, concealed

**Standard Latch:** Tamper resistant allen head cam latch with security pin

**Optional Latches/Locks:** Spanner head cam latch, cylinder lock & key. When master keying is required, doors can be prepared for rim or mortise cylinder locks

**Finish:** 5 stage iron phosphate preparation with prime coat of White alkyd baking enamel. Stainless Steel: Type 304 #4 satin polish.

### MS-7000 STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Weight per Door	
inches	mm	lbs.	kg.
12 x 12	305 x 305	14	6.4
16 x 16	406 x 406	20	9.1
18 x 18	457 x 457	26	11.8
24 x 24	610 x 610	34	15.4
24 x 36	610 x 914	55	25
36 x 36	914 x 914	80	36.4

Wall or ceiling opening is W + 3/8" (9 mm)  
For detailed specifications see submittal sheet

