

# PA-3000

## FLUSH NON-RATED - Plastic Access Door

### Application

- Easy access to walls and ceilings
- Economical and attractive

### Product Features

- High impact styrene plastic with U.V. stabilizers
- Hinged with a removable feature

### PA-3000 Access Door Specifications:

**Door / Door Frame:** 1/8" high impact styrene plastic with U.V. stabilizers

Flush to frame — rounded safety corners, one piece outside flange with 3/4" deep mounting frame

**Standard Latch:** Snap latches allow door to fit tightly within frame

**Door Hinge:** Concealed

**Finish:** White, with textured exposed surfaces



### PA-3000 STANDARD SIZES

Nominal Door Size W&H		Weight per Door	
inches	mm	lbs.	kg.
4 X 6	102 X 152	.5	.25
6 X 9	152 X 229	.5	.25
8 X 8	203 X 203	.5	.25
12 X 12	305 X 305	.5	.25
14 X 14	356 X 356	.75	.33
14 X 29	356 X 737	4	1.87
18 X 18	457 X 457	2.25	1
22 X 22*	559 X 559	4	1.87
24 x 24*	610 x 610	4.75	2.15

Wall or ceiling opening is  $W + 3/8"$  (9 mm)  
For detailed specifications see submittal sheet

\*22 x 22 and 24 x 24 sizes are designed for wall installation only.



PA-3000 View of door back

