

FLARED END SECTION SPECIFICATION

Scope

This specification describes 12- through 36-inch (300 to 900mm) Flared End Sections for use in culvert and drainage outlet applications.

Requirements

The Flared End Section shall be high density polyethylene meeting ASTM D3350 minimum cell classification 213320C; contact manufacturer for additional cell classification information. When provided, the metal threaded fastening rod shall be stainless steel.

Installation

Installation shall be in accordance with ADS installation instructions and with those issued by state or local authorities. Contact your local ADS representative or visit www.adspipe.com for the latest installation instructions.

Build America, Buy America (BABA)

The ADS Flared End Section complies with the requirements in the Build America, Buy America (BABA) Act.

	PIPE DIAMETER, in (mm)			
Diameter	12	15	18	24
in (mm)	(300)	(375)	(450)	(600)
A	6.5	6.5	7.5	7.5
in (mm)	(165)	(165)	(191)	(191)
B (max)	10.0	10.0	15.0	18.0
in (mm)	(254)	(254)	(381)	(475)
H	6.5	6.5	6.5	6.5
in (mm)	(165)	(165)	(165)	(165)
L	25.0	25.0	32.0	36.0
in (mm)	(635)	(635)	(813)	(914)
W	29.0	29.0	35.0	45.0
in (mm)	(737)	(737)	(889)	(1143)

*Product detail may differ slightly from actual product appearance

