

# TRIBUILT® #30 Asphalt Felt – ASTM D 4869

**PRODUCT DESCRIPTION:**

TRIBUILT® #30 – ASTM D 4869 is a widely accepted underlayment product that is manufactured from organic felt and is saturated with asphalt. Line markings are placed on the top surface at 2", 8 ½", 11 5/16", and 17" from each side of the sheet.

**PRODUCT USE:**

TRIBUILT® #30 – ASTM D 4869 underlayment is applied over the roofing deck before installation of asphalt shingles. This product is highly recommended as an underlayment for architectural shingles and is not recommended for 20 year 3 tab shingles.

**TECHNICAL DATA:**

**ASTM D 4869 Type II**

Width of roll	36"
Roof coverage per roll	216 sq ft
Mass of saturated felt roll	13 lbs. / 100 ft. sq.
Mass of asphalt saturant	6.0 lbs. / 100 ft. sq.
Mass of desaturated felt	5.0 lbs. / 100 ft. sq.
Saturation by weight (min)	100%
Saturation efficiency (min) by weight	75%
Breaking strength at 77F (min)	
Machine direction	30 lbf/in
Cross direction	15 lbf/in
Pass 4 hour liquid transmission water test	YES
Pliability at 77F when bend 90 degrees	½" radius

**PACKAGING:**

Pallet size	42" x 42"
Rolls per pallet	25 - 2 square rolls
Pallets per truck	32