



TRI-BUILT

"Weather or Not"

OUR POPULAR PRIMER AND CEMENT IN HANDY SIZES



**WET SURFACE
ROOF CEMENT**
10.3 oz tube

- Wet or Dry Surface
- Easy & Fast Repairs of Splits, Seams, Cracks in Bonded Gravel, Mineral Cap, Smooth Surface, Composition Shingle, Metal



**QUICK DRY
ASPHALT PRIMER**
17 oz aerosol

- Promotes Superior Adhesion of Roofing Materials to: Concrete & Cement Decks Metal Flashings & Gypsum Masonry Thermal Insulation Weathered Roofing



**PREMIUM
SBS/APP ROOF CEMENT**
10.3 oz tube

- Compatible to SBS & APP Modified Base & Cap Sheets
- Repairs Seams & Flashings Problem Areas Prone to Movement
- Enhanced Adhesion
- Excellent Elongation



WET SURFACE ROOF CEMENT

18643000

COMPLIANCE: EXCEEDS ASTM D 4586, TYPE 1, ASTM D 6511, ASTM D 3409, ASBESTOS FREE. California products meet Los Angeles County A.P.C.D. (Rule #102).

DESCRIPTION: TRI-BUILT™ WET SURFACE ROOF CEMENT is a flexible, all-weather cement especially adapted for wet surfaces in adverse or colder weather conditions. TRI-BUILT™ WET SURFACE ROOF CEMENT is designed and formulated for the professional contractor and is manufactured with select asphalt, solvent and fibers to provide a long lasting, durable patching compound. TRI-BUILT™ WET SURFACE ROOF CEMENT can be used to patch splits, cracks and seams in bonded gravel, mineral surfaced cap sheet and smooth surface asphalt roofs as well as composition shingle roofs. It will seal areas

around chimneys, vent pipes, gravel guards, down spouts or cracks in concrete. TRI-BUILT™ WET SURFACE ROOF CEMENT is also an excellent utility mastic for use below grade in heavy duty foundation water-proofing and damp-proofing.

PREPARATION: All surfaces must be clean, have proper drainage and be free of surface rust and any other foreign matter. DO NOT HEAT OR THIN.

FOR BEST RESULTS: Apply when surface temperatures are between 40° and 120° F. In colder weather, product should be stored in heated room (65° to 80° F.) at least 24 hours prior to application. Product formulated to be used year round. After a minimum of 45 days cure time, apply TRI-BUILT™ Aluminum Roof Coating. This will greatly extend the life of the cement.

APPLICATION: Protective clothing and eyewear should be used during application of these products. Apply with a caulking gun, and if needed, smooth with a putty knife. Work material to an even consistency over and into the area to be repaired. Apply 1/8" to 1/4" thick, two or three inches beyond the problem area. It is highly recommended to reinforce the repair with a strip of reinforcing fabric. Embed fabric into the cement and cover with a second layer of cement. Form a feathered edge with cement where chimneys, vent pipes, and other projections meet the roof line.

PRECAUTIONS: When transporting this product, ensure that plug is tight and tube is secure and upright. Do not allow tube to tumble as this may cause leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 110°F. For exterior use only. Products should be applied in accordance with NRCA guidelines. Do not reuse empty containers. Do not use in drinking water or food systems.

CLEAN-UP: Clean tools with paint thinner or mineral spirits.

DANGER! HARMFUL OR FATAL IF SWALLOWED. CAUTION! KEEP OUT OF REACH OF CHILDREN.

For exterior use only. Contains petroleum based products. Keep away from heat, sparks and open flame. Use only with adequate ventilation. Eye, skin and respiratory irritant. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid contact with skin and breathing vapor. If swallowed, do not induce vomiting. Call physician immediately. Seal container when not in use. Do not use in drinking water or food systems.

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

VOC/VOS - 250 g/l max. (2.1 lbs./gal.)

PETROLEUM ASPHALT	C.A.S.# 8052-42-4
MINERAL SPIRITS	C.A.S.# 8052-41-3
CELLULOSE FIBER	C.A.S.# 9004-34-6
INORGANIC FILLER	C.A.S.# 1317-65-3

Product is Asbestos Free.

TRI-BUILT Roofing Products ("TRI-BUILT") warrants to the original end user purchaser ("OEP") that for a one year period, this product will be free of defects in materials under normal use when installed according to label instructions. Call TRI-BUILT for additional conditions and limitations at 800-516-1485



QUICK DRY ASPHALT PRIMER

18642000

COMPLIANCE: EXCEEDS ASTM D 41 ASBESTOS FREE

DESCRIPTION: TRI-BUILT QUICK DRY ASPHALT PRIMER is an aerosol spray primer formulated with a high penetrating solvent and high melt asphalt. It is designed to dry fast and promote superior adhesion of roofing materials. Use to prime newly laid concrete or cement decks, metal flashings, gypsum, masonry thermal insulation, weathered roofing prior to applying built-up roofing, self adhered roofing membranes, roof cements and coatings.

APPLICATION: Shake well before using. Apply to clean, dry surface.

Coverage is approximately 35 sq. ft. per can. After using product, clear out spray tip in the following manner: Turn can upside down and point into refuse can. Push spray head for 3 seconds to clear passage of asphalt primer. If valve becomes clogged, remove from can and clean in paint thinner.

CLEAN-UP: Paint thinner.

DANGER! EXTREMELY FLAMMABLE. DO NOT PUNCTURE, INCINERATE OR BURN CAN, EVEN WHEN EMPTY. CONTENTS UNDER PRESSURE. HARMFUL OR FATAL IF SWALLOWED. EYE, SKIN AND RESPIRATORY IRRITANT. USE WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN.

Contains Petroleum Distillate. Keep away from heat, sparks and open flame. If swallowed DO NOT induce vomiting. Call physician immediately. In case of: Eye contact - flush with plenty of warm water. Skin contact - wash thoroughly with soap and water. Irregular or stopped breathing - administer oxygen, give artificial respiration. Get medical attention (immediately). Avoid prolonged breathing of vapor or spray mist. (NIOSH/MSHA TC 23C or equivalent).

MIR 1.20 max.

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

PETROLEUM ASPHALT	C.A.S.# 8052-42-4
MINERAL SPIRITS	C.A.S.# 8052-41-3

Product is asbestos free.

TRI-BUILT Roofing Products ("TRI-BUILT") warrants to the original end user purchaser ("OEP") that for a one year period, this product will be free of defects in materials under normal use when installed according to label instructions. Call TRI-BUILT for additional conditions and limitations at 800-516-1485



PREMIUM SBS/APP ROOF CEMENT

18642500

COMPLIANCE: EXCEEDS ASTM D6511, ASTM D3409, ASTM D4586, TYPE I. ASBESTOS FREE California products meet Los Angeles County A.P.C.D. (Rule #102).

DESCRIPTION: TRI-BUILT™ SBS/APP Premium Roof Cement is a professional grade, polymer modified flashing cement specially formulated for use with modified bitumen membranes, base sheets and ply sheets. It is manufactured using select asphalt, rubber, solvent and fibers. It provides excellent elongation and recovery properties plus enhanced adhesive properties and durability. It is ideal for seams, flashings and repairs on SBS modified membranes. TRI-BUILT™ SBS/APP Premium Roof Cement is also excellent for repairs on conventional built up roofing membranes where movement is expected to occur.

NOTE: This product is formulated for repairs and seams on SBS & APP Asphalt Modified Roll Roofing Sheets. DO NOT use on TPO, EPDM, PVC or other single ply membranes.

PREPARATION: All surfaces must have proper drainage and be clean, and free of surface rust and any other foreign matter. Excessive particulate surfacing materials on modified membranes must be removed (sweeping with a stiff broom is recommended) prior to application. On reroofing applications, all deck and existing membrane repairs should be made first. Severely weathered BUR membranes may require a pre-application of TRI-BUILT™ Quick Dry Asphalt Primer Metal surfaces must have all rust and scale removed. DO NOT HEAT OR THIN.

FOR BEST RESULTS: Apply on clear sunny day when surface temperatures are between 50° and 120° F. In colder weather product should be stored in heated room (65° to 80° F.) at least 24 hours prior to application. After a minimum of 45 days cure time, apply a TRI-BUILT™ Aluminum Roof Coating. This will greatly extend the life of the cement.

APPLICATION: Protective clothing and eyewear should be used during application of this product. Apply with caulk gun. Use a putty knife to work material to an even consistency over and into the area to be repaired. Apply 1/8" to 1/4" thick, two to three inches beyond the problem area. For cracks or holes 1/4" to 3/4" wide, press a strip of reinforcing fabric into the cement and cover with an additional layer of flashing cement. Form a cant with the cement around chimneys and other roof projections.

PRECAUTIONS: When transporting this product, ensure that plug is tight and tube is secure and upright. Do not allow tube to tumble as this may cause leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 110°F. For exterior use only. Products should be applied in accordance with NRCA guidelines. Do not reuse empty containers. Do not use in drinking water or food systems.

CLEAN-UP: Clean tools with paint thinner or mineral spirits.

CAUTION – COMBUSTIBLE MIXTURE. DANGER! Use with adequate ventilation. KEEP OUT OF REACH OF CHILDREN.

Contains Petroleum Distillate. Keep away from heat, sparks and open flame. If swallowed DO NOT induce vomiting. Call physician immediately. In case of: Eye contact - flush with plenty of warm water; Skin contact - wash thoroughly with soap and water; Irregular or stopped breathing - administer oxygen, give artificial respiration and get medical attention immediately. Avoid prolonged breathing of vapor or spray mist. (NIOSH/MSHA TC 23C or equivalent). Do not use in drinking water or food systems. Seal container when not in use.

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

VOC/VOS = 250 g/l max. (2.1 lbs./gal.)

PETROLEUM ASPHALT	C.A.S.# 8052-42-4
MINERAL SPIRITS	C.A.S.# 8052-41-3
CELLULOSE FIBER	C.A.S.# 9004-34-6
INORGANIC FILLER	C.A.S.# 1317-65-3
POLYMER	C.A.S.# Mixture

Product is Asbestos Free.

TRI-BUILT Roofing Products ("TRI-BUILT") warrants to the original end user purchaser ("OEP") that for a one year period, this product will be free of defects in materials under normal use when installed according to label instructions. Call TRI-BUILT for additional conditions and limitations at 800-516-1485



TRI-BUILT

"Weather or Not"

TRI-BUILT™ Roofing Products
15 East Union Avenue, P.O. Box 511
East Rutherford, New Jersey 07073.

FL-1049