

ROOF X TENDER® 900 White Premium Thermoplastic SB Cool Roof Coating

SECTION 1: PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME:	ROOF X TENDER® 900	DISTRIBUTED BY:	Beacon Sales Acquisition, Inc.
PRODUCT NUMBER:	RX-9005	ADDRESS:	505 Huntmar Park Drive, Suite 300 Herndon, VA 20170
CATEGORY:	White Liquid	PHONE:	571-323-3939
PRODUCT USE:	White Elastomeric Roof Coating	INTERNET:	www.becn.com
MANUFACTURER:	APOC		
ADDRESS:	4161 E. 7th Avenue Tampa, FL 33605		
PHONE:	813-248-2101		
EMERGENCY PHONE:	CHEMTREC: 1-800-424-9300 Outside USA and Canada: +703-527-3887		
EFFECTIVE DATE:	4/18/2018		

Section 2 - Hazards Identification

Emergency Overview

WARNING

Flammable Liquid and Vapor. Contains Combustible Petroleum Distillates. Keep away from heat, sparks, and open flame. Keep container tightly closed when not in use. Avoid prolonged breathing of vapor and use only in adequate ventilation. Repeated and prolonged overexposure to solvent vapor may cause brain and nervous system damage. May cause skin and eye irritation. Harmful or Fatal if swallowed. Use safety glasses, gloves, and skin protection when using this product. Protect building fresh air inlets from product vapors. Do not use in drinking water or food systems. Dispose in accordance to Federal, State, and local regulations. Do not reuse empty container.

ROOF X TENDER® 900 White Premium Thermoplastic SB Cool Roof Coating

- Prevention** Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash thoroughly after handling. Keep away from open flame.
- Response** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention.
- Storage/Disposal** Store in a closed container. Do not allow product to freeze. Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.



CAUTION - May cause eye and skin irritation on contact.

- Physical Form** * Liquid
-
- Color** * White Liquid.
-
- Odor** * Paint-Like Odor.
-
- Flash Point** * 80° F (27° C)
- OSHA (HCS2012)** * Skin Corrosion/Irritation - Category 3, Serious Eye Damage, Eye Irritation - Category 2A, Carcinogenicity - Category 2B, Flammable Liquids – Category 3
- WHMIS** * Class D - Poisonous and Infectious Materials - Division 2 - Subdivision B



*

NFPA: HEALTH HAZARD = 2 FIRE HAZARD = 3 REACTIVITY = 0

HMIS: HEALTH HAZARD = 2 FIRE HAZARD = 3 REACTIVITY = 0

Potential Health Effects

Inhalation

- Acute (Immediate)** * Inhalation of vapors or mists may cause central nervous system depression, light-headedness, headache, nausea and loss of coordination.
- Chronic (Delayed)** * Under normal conditions of use, no health effects are expected.

Skin

- Acute (Immediate)** * May cause irritation.
- Chronic (Delayed)** * Repeated and prolonged exposure to the skin may cause dermatitis.

Eye

- Acute (Immediate)** * Likely to cause eye irritation, burning, tearing, etc. on contact with the eyes. If swelling and irritation persist, seek medical attention.
- Chronic (Delayed)** * Direct contact may cause slight to moderate irritation.

ROOF X TENDER® 900 White Premium Thermoplastic SB Cool Roof Coating

Ingestion

- Acute (Immediate)** * May cause irritation. May affect the nervous system. May be harmful or fatal if swallowed.
- Chronic (Delayed)** * Repeated and prolonged exposure may cause gastrointestinal disturbances including diarrhea, nausea, and vomiting.

Carcinogenic Effects			
	CAS	IARC	NTP
Titanium Dioxide	13463-67-7	Group 2B-Possible Carcinogen	Evidence of Carcinogenicity

Section 3 - Composition/Information on Ingredients

Hazardous Components					
Chemical Name	Identifiers	%(weight)	LD50/LC50	Classifications According to Regulation/Directive	Comments
Xylene	CAS # - 1330-20-7	37%	Ingestion/Oral-Rat LD50 - 5000 mg/kg		
PCBTF (Oxsol 900)	CAS # - 98-56-6	21%	Ingestion/Oral-Rat LD50 6800 mg/kg		
Titanium Dioxide	CAS # - 13463-67-7	12%	Ingestion/Oral-Rat LD50 5000 mg/kg		
Zinc Oxide	CAS # - 1314-13-2	1%			
Barium Sulfate	CAS # - 7727-43-7	4%			
Talc	CAS # - 14807-96-6	4%			

Non-Hazardous Components					
Chemical Name	Identifiers	%(weight)	LD50/LC50	Classifications According to Regulation/Directive	Comments
Acrylic Resin	N/A	6%			

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

Section 4 - First Aid Measures

- Inhalation** * IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If signs/symptoms continue, get medical attention.
- Skin** * Rinse skin immediately with plenty of water for 15-20 minutes. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
- Eye** * If eye irritation persists: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Ingestion** * If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Section 5 - Fire Fighting Measures

- Extinguishing Media** * LARGE FIRE: Water spray, fog or regular foam.
 SMALL FIRES: Dry chemical, CO2, water spray or regular foam.
- Unsuitable Extinguishing Media** * No data available.

ROOF X TENDER® 900 White Premium Thermoplastic SB Cool Roof Coating

Firefighting Procedures	* Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Keep unauthorized personnel away.
Unusual Fire and Explosion Hazards	* Product containers may rupture when exposed to extreme heat. Precautions should be taken to prevent release of materials.
Hazardous Combustion Products	* Flammable and Combustible. Substance does burn and may decompose upon heating to produce toxic fumes.
Protection of Firefighters	* Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.
Flash Point	* 80° F (27° C) CC (Closed Cup)

Section 6 - Accidental Release Measures

Personal Precautions	* Do not handle damaged containers or spilled material unless wearing appropriate protective clothing.
Emergency Procedures	* Isolate the area and contain the spilled material. Persons not wearing the appropriate PPE should be removed from the area until the spill is cleaned up.
Environmental Precautions	* Avoid run off to waterways and sewers.
Containment/Clean-up Measures	* Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use appropriate Personal Protective Equipment (PPE)
Prohibited Materials	* Avoid contact with strong oxidizing agents and acids.

Section 7 - Handling and Storage

Handling	* KEEP OUT OF THE REACH OF CHILDREN! Keep containers tightly closed when not in use. Keep away from fire or flame. Protect building inlet from fumes/vapors when working on roofs.
Storage	* Avoid extreme temperatures and freezing. Keep container/package tightly closed and in a well-ventilated place.
Special Packaging Materials	* Not Applicable.
Incompatible Materials or Ignition Sources	* Avoid contact with strong oxidizing agents and acids.

Section 8 - Exposure Controls/Personal Protection

Personal Protective Equipment

Pictograms	*    
-------------------	---

Respiratory	* When used with adequate ventilation, a respirator is not normally required. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge or supplied air respirator. This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.
Eye/Face	* Wear ANSI approved safety glasses with side shields or safety goggles.
Hands	* Wear chemical resistant gloves with repeated or prolonged exposure.

ROOF X TENDER® 900 White Premium Thermoplastic SB Cool Roof Coating

Engineering Measures/Controls

* Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Use precaution to protect building intake from fumes and vapors created outdoors.

Exposure Limits/Guidelines					
	Result	Canada Ontario	Mexico	NIOSH	OSHA
Xylene (1330-20-7)	TWAs TLV	100 ppm 150 ppm	25 ppm 35 ppm	100 ppm 150 ppm	100 ppm 150 ppm
PCBTF (98-56-6)	TWAs	Not Established	Not Established	Not Established	N/A N/A
Titanium Dioxide (13463-67-7)	TWAs	10 mg/m3 TWAEV (total dust)	10 mg/m3 TWA (as Ti)	Not established	15 mg/m3 TWA (total dust)

Section 9 - Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	White liquid with the consistency of paint.
Color	White Liquid.	Odor	Paint-Like Odor.
Taste	No data available.	Particulate Type	Not relevant
Particulate Size	Not relevant	Aerosol Type	Not relevant
Odor Threshold	No data available		
General Properties			
Boiling Point	138 to 205° F	Melting Point	No data available
Decomposition Temperature	No data available	Heat of Decomposition	Not relevant
pH	Not Applicable	Specific Gravity/Relative Density	1.18 Water=1
Density	9.86 lbs/gal @ 25°C(77° F)	Bulk Density	No data available
Water Solubility	Insoluble	Solvent Solubility	100% Soluble
Viscosity	100 - 120 Krebs-Stormer (KU) @ 25 C(77 F)		
Volatility			
Vapor Pressure	18.0 mmHg (torr) @ 20 C(68 F)	Vapor Density	> 1 Air=1
Evaporation Rate	3 Normal Butyl Acetate = 1	VOC (Wt.)	3.66 lbs./Gal.
VOC (Vol.)	438 g/L	Volatiles (Wt.)	37%
Volatiles (Vol.)	68.0%		
Flammability			
Flash Point	80° F (27°C)	Flash Point Test Type	CC (Closed Cup)
UEL	No data available	LEL	No data available
Autoignition	No data available	Self-Accelerating Decomposition Temperature (SADT)	Not relevant
Heat of Combustion (ΔHc)	Not relevant	Burning Time	Not relevant
Flame Duration	Not relevant	Flame Height	Not relevant
Flame Extension	Not relevant	Ignition Distance	Not relevant
Environmental			
Half-Life	Not relevant	Octanol/Water Partition coefficient	Not relevant
Coefficient of Water	Not relevant	Bioaccumulation Factor	Not relevant
Bioconcentration Factor	Not relevant	Biochemical Oxygen Demand BOD/BOD5	Not relevant
Chemical Oxygen Demand	Not relevant	Persistence	Not relevant
Degradation	Not relevant		

ROOF X TENDER® 900 White Premium Thermoplastic SB Cool Roof Coating

Section 10 - Stability and Reactivity

- Stability** * Stable under normal temperatures and pressures.
- Hazardous Polymerization** * Hazardous polymerization not indicated.
- Conditions to Avoid** * Excessive heat and freezing.
- Incompatible Materials** * Strong oxidizers and acids.
- Hazardous Decomposition Products** * No known issues under normal usage conditions.

Section 11 - Toxicological Information

Component Name	CAS	Data
Titanium Dioxide	13463-67-7	Acute Toxicity: Oral-rat TDL _o :60 gm/kg; Irritation: skn-hmn 300 ug/3D-I MLD
Xylene	1330-20-7	Acute Toxicity: Oral-Rat LD50 · 5000 mg/kg
PCBTF	98-56-6	Acute Toxicity: Oral-Rat LD50 6800 mg/kg Irritation: skn-hmn 500 mg/7D MLD

Other Component Information * ACGIH has designated the following chemicals in this product as suspected human carcinogens (A1): Titanium Dioxide. Risk of cancer depends on duration and level of exposure to this product as a dust or aerosol mist.

Section 12 - Ecological Information

- Ecological Fate** * No data available.
- Persistence/Degradability** * No data available.
- Bioaccumulation Potential** * No data available.
- Mobility in Soil** * No data available.
- Other Information** * Do not allow product exposure to the ground or into any waterway. Do not allow entry into municipal sewer systems.

Section 13 - Disposal Considerations

Product * Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 – Transportation Information

DOT - United States - Department of Transportation - Shipping Name: UN 1263 Paint Related Materials, Hazard Class 3, Pkg Group 3

TDG - Canada - Transportation of Dangerous Goods - Shipping Name: UN 1263 Paint Related Materials, Hazard Class 3, Pkg Group 3

IMO/IMDG - International Maritime Transport - Shipping Name: UN 1263 Paint Related Materials Hazard Class 3, Pkg Group 3

IATA - International Air Transportation Association - Shipping Name: UN 1263 Paint Related Materials Hazard Class 3, Pkg Group 3

ROOF X TENDER® 900 White Premium Thermoplastic SB Cool Roof Coating

Section 15 - Regulatory Information

SARA Hazard Classifications * Acute, Chronic

State Right To Know					
Component	CAS	MA	MN	NJ	PA
Xylene	1330-20-7	Yes	Yes	Yes	Yes
PCBTF	98-56-6	No	No	No	Yes
Zinc Oxide	1314-13-2	Yes	Yes	Yes	Yes
Titanium Dioxide	13463-67-7	Yes	Yes	Yes	Yes
Barium Sulfate	7727-43-7	Yes	Yes	Yes	Yes
Talc	14807-96-6	Yes	Yes	Yes	Yes

Inventory			
Component	CAS	EU EINECS	TSCA
Xylene	1330-20-7	Yes	Yes
PCBTF	98-56-6	No	No
Zinc Oxide	1314-13-2	Yes	Yes
Titanium Dioxide	13463-67-7	Yes	Yes
Barium Sulfate	7727-43-7	Yes	Yes
Talc	14807-96-6	Yes	Yes

Canada

Labor

Canada - WHMIS - Classifications of Substances

- Titanium Dioxide 13463-67-7 5% TO 15% D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Titanium dioxide, mixture containing on Health Canada's WHMIS website.)

United States

Environment

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

- Xylene 1330-20-7 37%

United States - Rhode Island

Labor

U.S. - Rhode Island - Hazardous Substance List

- Titanium Dioxide 13463-67-7 12% Toxic
- Xylene 1330-20-7 37% Flammable

Other Information

* WARNING: This product contains a chemical known to the State of California to cause cancer.

ROOF X TENDER® 900 White Premium Thermoplastic SB Cool Roof Coating

Section 16 - Other Information

Preparation Date * 4/6/2016**Last Revision Date** * 4/6/2016**Disclaimer/Statement
of Liability**

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to verify the suitability and completeness of such information for particular use. Gardner Gibson or Beacon Sales Acquisition does not accept liability for any loss or damage that may occur from the use of this information.