

ROOF X TENDER® BLACK PREMIUM REPAIR TAPE

- NO ODOR
- AGGRESSIVE ADHESIVE
- FAST & EASY APPLICATION
- IDEAL FOR TPO, PVC & HYPALON ROOFS
- GREAT FOR SEALING, PATCHING & EMERGENCY REPAIRS

DESCRIPTION:

Roof X Tender® Black Premium Repair Tape with Shur-Stik® Adhesive Technology is an aggressive self-adhesive repair and flashing tape designed to immediately stop leaks and make a variety of roofing and waterproofing repairs. It will adhere to metal, wood, structural concrete, concrete block, brick, smooth BUR, smooth SBS, smooth APP, EPDM, TPO, Hypalon and PVC roofs. Manufactured with select thermoplastic elastomers, Roof X Tender® Shur-Stik® Tape provides a tough and durable repair. It's pressure sensitive properties allow a fast, clean and easy application.

PREPARATION:

Substrate should be clean, dry and free of dew, frost, oil, salt, dust and rust. Clean area first with a cloth and cleaner. On single ply roofs clean with rags and acetone to remove any oil or grime. In cold temperature conditions (< 40°F), use RXT primer on single ply and metal surfaces.

APPLICATION:

In cold climates, preheat roll in a warm room and warm the substrate with hot air. Cut to length. Shorter lengths (less than 4 ft) are easier to work with unless using a team of two or more applicators. Remove release film. Press in place using a gloved hand or a steel roller. Apply the exact length to predetermined location. Tape cannot be peeled up and reset. Always roll from the center out to remove trapped air pockets and fishmouths. Start in corners to eliminate "tenting". When applying in temperatures between -30°F and 40°F, apply primer prior to installation of tape.

PRECAUTIONS:

RXT Black Premium Repair Tape will not adhere to silicone surfaces. For best results, test adhesion on membranes before applying. Do NOT store at temperatures above 110°F. Do NOT stretch tape during installation. Do NOT use where acidic or alkaline chemicals are present (for example: lab fume hoods, vents, etc).



Peel Strength	21 lbs. +/-in width
Application Temperature	- 30°F to 200°F
Color	Black
Elongation	900%
Low Temperature Flexibility	Passes at - 65°F, no cracking
Permeability	.001 perms max
Shelf Life	5 years*
Tensile Break	4000+/-500 psi
Total Thickness	35 mils
UV Resistance	Excellent

*Storage at ambient room temperatures

SHIPPING:

4" X 50' ROLLS 12 per case	6" X 50' ROLLS 8 per case	12" X 50' ROLLS 4 per case
-------------------------------	------------------------------	-------------------------------

Manufactured by Gardner-Gibson, Inc. Distributed exclusively by Beacon Sales Acquisition, Inc.