

SECTION 1: PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME: ROOF X TENDER® 981

PRODUCT NUMBER: RX-981

CATEGORY: Liquid

PRODUCT USE: Elastomeric Sealant

MANUFACTURER: APOC

ADDRESS: 4161 E. 7th Avenue Tampa, FL 33605

PHONE: 813-248-2101

EMERGENCY PHONE: CHEMTREC: 1-800-424-9300

Outside USA and Canada: +703-527-3887

EFFECTIVE DATE: 4/19/2018

DISTRIBUTED BY: Beacon Sales Acquisition, Inc.

ADDRESS: 505 Huntmar Park Drive, Suite 300

Herndon, VA 20170

PHONE: 571-323-3939
INTERNET: www.becn.com

Section 2 - Hazards Identification

Emergency Overview

WARNING

Causes mild skin irritation. Harmful if swallowed.

Prevention Do not handle until all safety precautions have been read and understood. Use personal

protective equipment as required. Wash thoroughly after handling.

Response IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention.

Storage/Disposal Store in a closed container. Do not allow product to freeze. Dispose of content and/or container in

accordance with local, regional, national, and/or international regulations.





Classification:

Eye irritation, Category 2A Skin sensitization, Category 1 Carcinogenic, Category 2

Statements of Hazard:

Warning

H319 Causes serious eye irritation H317 May cause allergic skin reaction H351 Suspected of causing cancer

Precautions for Safe Handling:

P102 Keep out of the reach of children

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P261 Avoid breathing vapors or mists

P264 Wash hands thoroughly after handling

P272 Contaminated work clothing should not be allowed out of the workplace

P281 Use personal protective equipment as required

CAUTION - May cause eye and skin irritation on contact.

Physical Form

* Liquid

Color

* Liquid.

Odor

* Paint-Like Odor.

Flash Point

* 247 F

OSHA

* Irritant

WHMIS

* Class D - Poisonous and Infectious Materials - Division 2 - Subdivision B



GHS

* Skin Corrosion/Irritation - Category 1

Serious Eye Damage, Eye Irritation - Category 2A

Carcinogenic - Category 2B

NFPA:

Health: 2

Flammability: 1

Reactivity: 0

Personal Protection: G

Potential Health Effects

Inhalation

Acute (Immediate)

* Inhalation of vapors or mists may cause central nervous system depression, light-headedness, headache, nausea and loss of coordination.

Chronic (Delayed)

* Under normal conditions of use, no health effects are expected.

Skin

Acute (Immediate)

* May cause irritation.

Chronic (Delayed)

* Repeated and prolonged exposure to the skin may cause dermatitis.

Eye

Acute (Immediate)

* Likely to cause eye irritation, burning, tearing, etc. on contact with the eyes. If swelling and irritation persist, seek medical attention.



Chronic (Delayed) * Direct contact may cause slight to moderate irritation.

Ingestion

Acute (Immediate) * May cause irritation. May affect the nervous system. May be harmful or fatal if

swallowed.

Chronic (Delayed) * Repeated and prolonged exposure may cause gastrointestinal disturbances

including diarrhea, nausea, and vomiting.

Carcinogenic Effects						
	CAS IARC NTP					
Titanium Dioxide	13463-67-7	Group 2B-Possible Carcinogen	Evidence of Carcinogenicity			

Section 3 - Composition/Information on Ingredients

Hazardous Components						
Chemical Name	Identifiers	%(weigh t)	LD50/LC50	Classifications According to Regulation/Directive	Comment s	
Sylil-Terminated Poly Ether	CAS: 151865-59-7	40.0%	LD50 Oral - rat - > 3160 mg/kg			
Silica Quartz	CAS: 68476-25-5	54.0%				
Dinonyl Phthalate	CAS: 84-76-4	3.0%				
Titanium Dioxide	CAS: 13463-67-7	1.0%	LD50 Oral, rat · 60 gm/kg			
Black Iron Oxide	CAS: 12227-89-3	0.5%				
Fumed Silica	CAS: 112945-52-5	1.0%	LD50 Oral - rat - > 3160 mg/kg			
Aminopropyl Trimethoxy Silane	CAS: 13822-56-5	0.5%	LD50 Oral - rat - > 62.080 mg/kg			

Non-Hazardous Components						
Chemical Name	Identifiers	%(weight)	LD50/LC50	Classifications According to Regulation/Directive	Comments	

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

Section 4 - First Aid Measures

Inhalation * IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If signs/symptoms continue, get medical attention.

* Rinse skin immediately with plenty of water for 15-20 minutes. Take off contaminated

clothing. If skin irritation occurs: Get medical advice/attention.

* If eye irritation persists: Get medical advice/attention. IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Ingestion * If swallowed, do not induce vomiting: seek medical advice immediately and show this

container or label.

Section 5 - Fire Fighting Measures



Extinguishing Media

LARGE FIRE: Water spray, fog or regular foam.
 SMALL FIRES: Dry chemical, CO2, water spray or regular foam.

Unsuitable Extinguishing

Media

* No data available.

Firefighting Procedures

* Fire fighters should wear complete protective clothing including self-contained breathing apparatus.

Keep unauthorized personnel away.

Unusual Fire and Explosion *

Hazards

* Product containers may rupture when exposed to extreme heat. Precaustions should be taken to prevent release of materials.

Hazardous Combustion

Products
Protection of Firefighters

* Non-combustible, substance itself does not burn but may decompose upon heating to produce toxic fumes.

* Structural firefighters' protective clothing provides limited protection in fire situations

ONLY; it is not effective in spill situations where direct contact with the substance is

possible.

Flash Point

* 247 F(85 C) CC (Closed Cup)

Section 6 - Accidental Release Measures

Personal Precautions

* Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Emergency Procedures

* Isolate the area and contain the spilled material. Persons not wearing the appropriate PPE should be removed from the area until the spill is cleaned up.

Environmental Precautions

Containment/Clean-up

Measures

* Avoid run off to waterways and sewers.

* Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers

Use appropriate Personal Protective Equipment (PPE)

Prohibited Materials

* Avoid contact with strong oxidizing agents and acids.

Section 7 - Handling and Storage

Handling

* KEEP OUT OF THE REACH OF CHILDREN! Keep containers tightly closed when not in use.

Storage

* Avoid extreme temperatures and freezing. Keep container/package tightly closed and in a well-ventilated place.

Special Packaging Materials Incompatible Materials or * Not Applicable.

Incompatible Materials or Ignition Sources * Avoid contact with strong oxidizing agents and acids.

Section 8 - Exposure Controls/Personal Protection

Personal Protective Equipment

Pictograms









* Use with adequate ventilation. A respirator is required. Use a NIOSH-approved air purifying respirator with organic vapor cartridge or supplied air respirator. This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

Eye/Face

* Wear ANSI approved safety glasses with side shields or safety goggles.



Hands

* Wear chemical resistant gloves with repeated or prolonged exposure.

Engineering Measures/Controls

* Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Use precaution to protect building intake from fumes and vapors created outdoors.

Exposure Limits/Guidelines						
	Result	Canada Ontario	Mexico	NIOSH	OSHA	
Titanium Dioxide (13463-67-7)	TWAs	10 mg/m3 TWAEV (total dust)	10 mg/m3 TWA (as Ti)	10 mg/m3 - TWA	15 mg/m3 TWA (total dust)	
Black Iron Oxide (12227-89-3	TWAs	10 mg/m3 TWAEV (Total Dust)	10 mg/m3 TWA	10 mg/m3 TWA	10 mg/m3	
Fumed Silica (112945-52-5)	TWAs	10 mg/m3-TWAEV	10 mg/m3 TWA	6 mg/m3-TWA	6 mg/m3-TWA	

Section 9 - Physical and Chemical Properties Material Description Appearance/Description Physical Form Liquid liquid with heavy consistency. Color White Liquid. Paint-Like Odor. Taste No data available. Particulate Type Not relevant Particulate Size Not relevant Aerosol Type Not relevant Odor Threshold No data available General Properties **Boiling Point** >300 F Melting Point No data available Heat of Decomposition **Decomposition Temperature** No data available Not relevant 8 @ 25 C(77 F) Specific Gravity/Relative Density 1.50 Water=1 Density 12.55 lbs/gal @ 25 C(77 F) **Bulk Density** No data available Water Solubility Soluble 0 % @ 25 C(77 F) Solvent Solubility Not relevant 124,000 cps. @ 25 C(77 F) Viscosity Volatility 5.3 mmHg (torr) @ 20 C(68 F) > 1 Air=1 Vapor Pressure Vapor Density Evaporation Rate < 0.7 Ether = 1 VOC (Wt.) No data available VOC (Vol.) <10 g/L Volatiles (Wt.) No data available Volatiles (Vol.) No data available Flammability Flash Point 247 F Flash Point Test Type CC (Closed Cup) UEL No data available No data available Self-Accelerating Decomposition No data available Autoignition Not relevant Temperature (SADT) Heat of Combustion (ΔHc) Not relevant **Burning Time** Not relevant Flame Duration Not relevant Flame Height Not relevant Ignition Distance Flame Extension Not relevant Not relevant Environmental Half-Life Octanol/Water Partition coefficient Not relevant Not relevant Coefficient of Water Not relevant Bioaccumulation Factor Not relevant Biochemical Oxygen Demand Bioconcentration Factor Not relevant Not relevant BOD/BOD5 Not relevant Not relevant Chemical Oxygen Demand Persistence Degradation Not relevant



Section 10 - Stability and Reactivity

Stability

* Stable under normal temperatures and pressures.

Hazardous Polymerization

* Hazardous polymerization not indicated.

Conditions to Avoid Incompatible Materials

* Excessive heat and freezing.

Hazardous Decomposition

* Strong oxidizers and acids.

Products

* No known issues under normal usage conditions.

Section 11 - Toxicological Information

Component Name	CAS	Data	
Sylil-Terminated Poly Ether	151865-59-7	Acute Toxicity: LD50 Oral - rat - > 3160 mg/kg	
Fumed Silica	112945-52-5	Acute Toxicity: LD50 Oral - rat - > 3160 mg/kg	
Titanium Dioxide	13463-67-7	Acute Toxicity: LD50 Oral, rat · 60 gm/kg	
Aminopropyl Trimethoxy Silane	13822-56-5	Acute Toxicity: LD50 Oral - rat - > 62.080 mg/kg	

Other Component Information

* IARC has concluded that the following chemicals in this product are carcinogenic to humans(Group 1): ACGIH has designated the following chemicals in this product as suspected human carcinogens (A2): silica, quartz. NTP has listed the following chemicals in this product as known human carcinogens:. Risk of cancer depends on duration and level of exposure to this product as a dust or aerosol mist.

Section 12 - Ecological Information

Ecological Fate

* No data available.

Persistence/Degradability

* No data available.

Bioaccumulation Potential Mobility in Soil * No data available.

and the second

* No data available.

Other Information

* Do not allow product exposure to the ground or into any waterway. Do not allow entry into municipal sewer systems.

Section 13 - Disposal Considerations

Product

* Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transportation Information

DOT - United States - Department of Transportation - Shipping Name: Not Regulated.

TDG - Canada - Transportation of Dangerous Goods - Shipping Name: Not Restricted.

International Air Transportation Association - Not Regulated



Section 15 - Regulatory Information

SARA Hazard Classifications * Acute, Chronic

State Right To Know					
Component	CAS	MA	MN	NJ	PA
Sylil-Terminated Poly Ether	151865-59-7	Yes	Yes	Yes	Yes
Silica Quartz	68476-25-5	Yes	Yes	Yes	Yes
Dinonyl Phthalate	84-76-4	Yes	Yes	Yes	Yes
Titanium Dioxide	13463-67-7	Yes	Yes	Yes	Yes
Fumed Silica	112945-52-5	Yes	Yes	Yes	Yes
Black Iron Oxide	12227-89-3	Yes	Yes	Yes	Yes
Aminopropyl Trimethoxy Silane	13822-56-5	Yes	Yes	Yes	Yes

Inventory					
Component	CAS	EU EINECS	TSCA		
Sylil-Terminated Poly Ether	151865-59-7	Yes	Yes		
Silica Quartz	68476-25-5	Yes	Yes		
Dinonyl Phthalate	84-76-4	Yes	Yes		
Titanium Dioxide	13463-67-7	Yes	Yes		
Black Iron Oxide	12227-89-3	Yes	Yes		
Fumed Silica	112945-52-5	Yes	Yes		
Aminopropyl Trimethoxy Silane	13822-56-5	Yes	Yes		

Canada

Labor

Canada - WHMIS - Classifications of Substances

Sylil-

 Terminated Poly Ether
 151865-59-7
 D2B

 Silica Quartz
 68476-25-5
 D2B

 Dinonyl Phthalate
 84-76-4
 D2B

 Titanium Dioxide
 13463-67-7
 D2A

United States

Environment

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

Silica Quartz 68476-25-5

Sylil-

151865-59-7

Terminated Poly Ether

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

Sylil-

Terminated 151865-59-7

Poly Ether

United States - Rhode Island



Labor

U.S. - Rhode Island - Hazardous Substance List

Titanium Dioxide 13463-67-7
Fumed Silica 112945-52-5
Aminopropyl Trimethoxy 13822-56-5

Other Information

Silane

 WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information

Preparation Date

Last Revision Date

Disclaimer/Statement of
Liability

- * 5/10/2016
- * 5/10/2016

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to verify the suitability and completeness of such information for particular use. Gardner Gibson or Beacon Sales Acquisition does not accept liability for any loss or damage that may occur from the use of this information.