

## Product Comparison TRI-BUILT C Housewrap

	Tri-Built C	R-Wrap	Tyvek <sup>®</sup> HomeWrap <sup>®</sup>
Basis Weight (oz/yd <sup>2</sup> ) TAPPI-410	2.9	2.49	1.8
Breaking Strength		No breaking	No breaking
MD/CD (lbs)	55 / 44	strength data.	strength data.
ASTM D 5034		Strip tensile	Strip tensile
		reported as	reported as
		32/32 per ASTM	30/30 per ASTM
		D 882.	D 882.
Air Penetration	1200	1000	1200
Resistance (sec/100cc) TAPPI-460	1200	1000	1200
Water Vapor			
Transmission (perms)	50	56	54
ASTM E 96, Method B	50		
Water Penetration			
Resistance (cm)	250	220	250
(ATTCC -127)	250	220	200
Flame Spread Index			
ASTM E 84	Class A	Class A	Class A
Smoke Developed			
Index	Class A	Class A	Class A
ASTM E 84			
Ultra Violet Light	Carrowship	1	4
Exposure Rating	6 months	4 months	4 months
Translucent	Yes	Yes	No
Commercial Grade	Yes	Yes	No
Custom Print Minimum	8 rolls	1 pallet	4 pallets
Alternating logos & colors	Yes	No	No
ICC-ES Report	ESR-2246	ESR-1197	ESR-2375

Tyvek and Homewrap are registered trademarks of Dupont.

R-Wrap is a registered trademark of Berry Plastics.

All competitive data is from published technical literature and ICC-ES Reports and is considered accurate at the time. Tyvek Homewrap: <u>http://www2.dupont.com/Tyvek\_Weatherization/en\_US/assets/downloads/K-05031\_HW\_Prod\_Prop.pdf</u> R-Wrap: <u>http://www.berryplasticsbpg.com/files/data/rwrapdata.pdf</u>

## Product Comparison TRI-BUILT C-LP Housewrap

	Tri-Built C-LP	Typar <sup>®</sup> House Wrap	Weathermate <sup>™</sup> Plus
Basis Weight (oz/yd <sup>2</sup> ) TAPPI-410	2.9	2.8	n/a
Breaking Strength MD/CD (lbs) ASTM D 5034	58 / 47	80/87	No breaking strength data. Strip tensile reported as 20/20 per ASTM D 828.
Air Penetration Resistance (sec/100cc) TAPPI-460	2200 <b>(1)</b>	2500	300
Water Vapor Transmission (perms) ASTM E 96, Method B	12.7	11.7	6.7
Water Penetration Resistance (cm) (ATTCC -127)	350	865	210
60-minute Water Resistance Listed (ICC-ES Code Report)	Yes	Yes	No
Flame Spread Index ASTM E 84	Class A	Class A	Class A
Smoke Developed Index ASTM E 84	Class A	Class A	Class A
Ultra Violet Light Exposure Rating	6 months	6 months	4 months
Translucent	Yes	No	Yes
Commercial Grade	Yes	Yes	Yes
Custom Print Minimum	8 rolls	1 pallet <b>(2)</b>	No custom print
Alternating logos & colors	Yes	No	No
ICC-ES Report	ESR-2246	ESR-1404	NER-640

**n/a:** Data is not published and not available in the ICC-ES Report.

(1) Tri-Built C-LP exceeds code requirements for Air Penetration Resistance. Testing is in progress to update Air Penetration per TAPPI-460.

(2) Quantity not confirmed. Minimum order may be higher.

Typar is a registered trademark of Fiberweb, Inc.. <u>http://www.typar.com/pdfs/HouseWrapTypical.pdf</u>

Weathermate is a trademark of The Dow Chemical Co.

http://msdssearch.dow.com/PublishedLiteratureDOWCOM/dh\_04e9/0901b803804e9d11.pdf?filepath=styrofoam/pdfs/noreg/179-07168.pdf&fromPage=GetDoc

All competitive data is from published technical literature and ICC-ES Reports and is considered accurate at the time.



Distributed exclusively by Allied Building Products Corp. | 1.800.4.ALLIED