

# **TRI-BUILT® #15 & #30 Organic Roofing Felt** Midwest & Northeast Region

## **DESCRIPTION:**

TRI-BUILT<sup>®</sup> #15 & #30 Organic Felts are made from a tough organic felt saturated with asphalt.

#### **USES:**

TRI-BUILT<sup>®</sup> organic felts are accepted for use as an underlayment felt for steep-slope roofing shingles. The finished roofing product should be applied immediately after the installation of the TRI-BUILT<sup>®</sup> #15 & #30 Organic Felt.

#### **STORAGE:**

Always store rolls upright on pallets and in a dry protected area.

## **AVAILABILITY:**

#15 & #30 organic felt is available in the Northeast and Midwest regions of the United States. Check with your TRI-BUILT<sup>®</sup> representative for availability.

<b>PRODUCT DATA:</b> #15 Organic Felt		PRODUCT DATA: #30 Organic Felt	
Roll Dimensions	36" x 144'	Roll Dimensions	36" x 72'
Coverage	4 Squares	Coverage	2 Squares
Laying Lines	2", 4", 17"	Laying Lines	2", 4", 17"
Rolls per skid	30	Rolls per skid	30
Rolls per truck	1,500	Rolls per truck	1,620

# THIS PRODUCT IS SOLD "AS IS" WITHOUT WARRANTIES, EXPRESSED OR IMPLIED. INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.