



TRIBUILT® SHEATHING TAPE

OVERVIEW

TRIBUILT® Sheathing Tape is an aggressive joint sealing tape well suited for reducing air infiltration through wall systems.

TRIBUILT® Sheathing Tape is compatible with most building & house wraps and poly-faced sheathing materials.

INSTALLATION GUIDELINES

Ensure that the wall substrate is flat and free of dust or moisture before TRIBUILT® Sheathing Tape is applied. TRIBUILT® Sheathing Tape has excellent cold weather adhesion and may be applied down to 10° F (12° C).

Apply TRIBUILT® Sheathing Tape using firm, uniform pressure.

TRIBUILT® Sheathing Tape must be covered within 90 days of initial application.



TYPICAL PROPERTIES

PROPERTY	RESULTS
Total Product Thickness	3.0 Mils
Peel Adhesion - Stainless Steel	65 oz/inch
Peel Adhesion - Polyethylene	16 oz/inch
Shear Strength	> 96 hours
Tensile Strength	20 lb/inch width
Elongation	136%
WVTR	0.16 g/100 in 2/24 hr
Application Temperature	-20° F to 120° F
Service Temperature	-40° F to 275° F

PROPERTY	SIZE
Roll Size	1 7/8" x 55 yards
Rolls/Case	24
Cases/Pallet	36