MATERIAL SAFETY DATA SHEET

NPCA

FOR COATINGS, RESINS AND RELATED MATERIALS

(Approved by US Department of Labor Essentially Similar to Form OSHA 20)

Date Issued 03/2	23/06						
		SECTION I					
MANUFACTURER'S I GARDNER-GIBSOI STREET ADDRESS 4161 E 7 TH AVENUE EMERGENCY T 1-800-424-9300 PRODUCT CLASS WET SURFACE RO	TAMPA, FL UMBER MANU IDEN'	CITY, STATE, AND ZIP CODE TAMPA, FL 33605 MANUFACTURER'S CODE IDENTIFICATION					
TRADE NAME TRI-BUILT		AL-90	99				
	SECTIO	N II- HAZARDOUS I	NGREDIE	NTS			
INGREDIENT		PERCEN'I	TLV PPM	TLV Mg/M3	LEL	VAPOR PRESSURE	
PETROLEUM ASPHALT CAS # - 8052-42-4	<50%		0.5 Fume				
STODDARD SOLVENT CAS #- 8052-41-3 Inorganic filler	<20% <35%	100	10*				
CAS # - 1317-65-3 CELLULOSE FIBER	<10%		10*				
CAS #- 9004-34-6 Surfactant CAS # Mixture	<1%		**				
ADDITIONAL INFO		TRABLE FRACTION OF I	DUST. ** NOT	ESTABL	ISHED		
-		Reactivity 0	Person	Personal Protection C			
	SE	CTION III – PHYSIC	AL DATA				
BOILING RANGE:	300 °F - 390°F V	APOR DENSITY HEA	VIER	LIGHTEI	R, THAN	AIR	
EVAPORATION RATE	*	PERCENT VOTILE BY VOLUME <30 % WEIGHT PER GALLON BY VOLUME 9.6 LBS					
	SECTION IV -	FIRE AND EXPLOS	ION HAZ	ARD DA	ATA		
DOT CATEGORY - N	FLASH POIN	FLASH POINT- 105°F Minimum					
EXTINGUISHING MEI	DIA- CO2, FOAM, & D	RY CHEMICAL					
UNUSUAL FIRE AND E	EXPLOSION HAZARDS	S- CLOSED CONTAINERS I	MAY EXPLOD	E WHEN	EXPOSI	ED TO EXTI	

 \mathbf{E} HEAT. PRODUCTS OF COMBUSTION MAY BE TOXIC

SPECIAL FIRE FIGHTING PROCEDURES- WEAR SELF CONTAINED BREATHING APPARATUS. WATER MAY BE USED TO COOL CLOSED CONTAINERS. HIGH PRESSURE STREAM WILL SPREAD FIRE.

SECTION V – REACTIVITY DATA
SECTION V - REACTIVITY DATA
STABILITY: UNSTABLE STABLE CONDITIONS TO AVOID: HEAT, FLAMES, STRONG OXIDIZERS
INCOMPATIBILTY (MATERIALS TO AVOID): CARBON OXIDES
HAZARDOUS DECOMPOSITION PRODUCTS: NONE
HAZARDOUS POLYMERIZATION: MAY OCCUR WILL NOT OCCUR
CONDITIONS TO AVOID: NONE
SECTION VI-HEALTH HAZARD DATA
EFFECTS OF OVEREXPOSURE-ACUTE: SKIN: PROLONGED /REPEATED CONTACT MAY CAUSE IRRITATION, DEFATTING AND DERMATITISEYES: MAY CAUSE SEVERE IRRITATION, REDNESS TEARING AND BLURRED VISIONINHALATION: MAY CAUSE DIZINESS, WEAKNESS, HEADACHE, UNCONSCIOUSNESS AND EVEN ASPHYXIATIONINGESTION MAY CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Read and follow label directions and information given on Material Safety Data Sheets and use care when handling or using all petroleum products.
EMERGENCY FIRST AID PROCEDURE-SKIN: REMOVE CONTAMINATED CLOTHING. WASH EXPOSED AREA. WITH SOAP AND WATER. IF IRRITATION PERSISTS GET MEDICAL ATTENTION. EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXIGEN. IF BREATHING STOPS, GIVE ARTIFICIAL RESPIRATION AND SEEK MEDICAL ATTENTION IMMEDIATELY. INGESTION: DO NOT INDUCE VOMITING. ASPIRATION INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS, WHICH CAN BE FATAL. KEEP PERSON WARM AND QUIET.
SECTION VII – SPILL OR LEAK PROCEDURES
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ELIMINATE SOURCES OF IGNITION KEEP PRODUCT OUT OF SEWERS BY DIKING OR IMPOUNDING. SOAK UP SPILL WITH SAND OR OTHER ABSORBENT. PLACE IN CONTAINERS. WASH AREA.
WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH LOCAL, STATE OR FEDERAL REGULATIONS.
SECTION VIII – SPECIAL PROTECTION INFORMATION
RESPIRATORY PROTECTION: USE NIOSH/MSHA APPROVED RESPIRATOR WHEN TLV IS EXCEEDED.
VENTILATION: USE WITH ADEQUATE VENTILATION.
PROTECTIVE GLOVES: NITRILE RUBBER SHOULD BE USED.
EYE PROTECTION: SAFETY GOGGLES SHOULD BE USED.
OTHER PROTECTIVE EQUIPMENT: FACE SHIELD
SECTION IX – REGULATORY INFORMATION

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN COOL PLACE

OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINERS TIGHLY CLOSED.