

Submittal 09 29 00



American Gypsum
5960 Berkshire Ln., #800
Dallas, TX 75225
214-530-5500
www.americangypsum.com

Technical Information
1-800-545-6302 ext. 5607

M Bloc[®] 5/8" Type X

WITH MOLD & MOISTURE RESISTANCE

DESCRIPTION

M-Bloc[®] Type X gypsum panels were developed as an improved mold and moisture resistant wallboard with a fire resistant core encased in a mold and moisture resistant blue face paper and brown back paper manufactured from 100% recycled paper. Additionally the core has been reinforced with fibers, increasing its strength and providing fire resistance ratings when used in tested assemblies. At an independent laboratory accredited in accordance with ISO 17025-2005, M-Bloc panels have been tested to the industry's most rigorous standard achieving the best possible results per ASTM D3273, scoring a perfect 10 thus minimizing the risk of mold and mildew growth. American Gypsum products contain no asbestos and no detectable levels of formaldehyde.

GREENGUARD CERTIFIED FROM UL ENVIRONMENT

M-Bloc Type X gypsum panels have achieved UL Environment's GREENGUARD GOLD Certification. GREENGUARD Certified products are scientifically proven to meet some of the world's most rigorous, third-party chemical emissions standards, helping reduce indoor air pollution and the risk of chemical exposure while aiding in the creation of healthier indoor environments. For more information, visit www.ul.com/gg.

BASIC USES

M-Bloc Type X gypsum panels are a lightweight cost efficient wall or ceiling panel for use throughout a project as well as the adhesive application of ceramic or plastic tile in limited wet areas, e.g., bathrooms, kitchens, laundry, and utility rooms. M-Bloc Type X gypsum panels are also approved for exterior soffits and/or sidewalls in protected corridors/breezeways with indirect exposure to the weather. With joints covered, M-Bloc Type X gypsum wallboard will resist the passage of smoke. For additional information on smoke barriers, refer to Gypsum Association publication, "Building and Inspecting Smoke Barriers" (GA-618).

LIMITATIONS

The use of M-Bloc Type X gypsum panels in actual job site conditions may not produce the same mold resistant results as were achieved in a controlled laboratory setting. While no material can or should be considered mold proof, the use of good design and construction practices is the most effective strategy to manage the growth of mold and mildew.

M-Bloc Type X gypsum wallboard is a nonstructural panel and should not be used as a nailing base.

Avoid exposure to temperatures exceeding 125°F (52°C) for extended periods of time.

Resilient channels are not recommended where tile or similar finish is to be applied to panel.

Not to be used in areas with direct exposure to water or continuous high humidity, tiled tub and shower areas, saunas, steam rooms, gang showers or indoor swimming pools.

M-Bloc Type X gypsum panels that is to receive tile or other surfacing which may act as a vapor retarder shall not have a vapor retarder placed behind the panel. A single layer of asphalt impregnated felt, #15 or less, applied as part of the wall system, shall not be considered a vapor retarder.

On wall applications, maintain a gap of 1/4" between the bottom edges or ends of the panels and floors, or any other horizontal surface where water could accumulate.

A fast setting joint compound is recommended for filling, taping and finishing of M-Bloc Type X gypsum wallboard used for exterior soffits and/or sidewalls in protected corridors/breezeways with indirect exposure to the weather.

When used in exterior ceiling applications, install fascia so that its drip line is at least 1/4" below the face of the panel.

MAXIMUM SPACING OF FRAMING (WOOD OR METAL)			
	SINGLE PLY THICKNESS	APPLICATION	MAXIMUM FRAMING O/C SPACING
CEILINGS	5/8"	Parallel to Framing Perpendicular to Framing	16" o/c
	5/8"		24" o/c
WALLS	5/8"	Parallel to or Perpendicular to Framing	24" o/c

To prevent noticeable sag in ceilings, the weight of overlaid unsupported insulation should not exceed the following recommendations:

FRAMING	PRODUCT	PSF (LBS. PER S/F) OF INSULATION
24" o/c	5/8" M-Bloc Type X	2.2 (10.7 kg/M ²)

Insulation blankets or batts should be recessed, with flanges attached or friction fitted to the sides of the studs or joists.

STORAGE AND HANDLING

Gypsum board does not generate or support the growth of mold when it is properly transported, stored, handled, installed, and maintained. However, mold spores are present everywhere and when conditions are favorable; mold can grow on practically any surface. GYPSUM BOARD MUST BE KEPT DRY to prevent the growth of mold. Gypsum board must be stored in an area that protects it from adverse weather conditions, condensation, and other forms of moisture. Job site conditions that can expose gypsum board to water or moisture must be avoided.

M Bloc TYPE X

MOLD & MOISTURE RESISTANT

AMERICAN GYPSUM

Made in the USA

AMERICAN GYPSUM

Panel Tipo X resistente al moho la humedad

