# MATERIAL SAFETY DATA SHEET

American Hydrotech, Inc. 303 East Ohio Street, 2700 Chicago, IL 60611

INFORMATION TELEPHONE: (312) 337-4998

**EMERGENCY TELEPHONE:** 

DATE OF PREPARATION:

September 25, 2000

## SECTION: PRODUCT IDENTIFICATION

PRODUCT NAME(S):

COOL-CAP M-100 WHITE COAT AND M-700 BASE COAT

PRODUCT NUMBER(S):

PRODUCT CLASS:

**ACRYLIC LATEX ROOF COATING** 

#### HAZARDOUS INGREDIENTS SECTION II

COMPONENTS	Wt. %	CAS NO.	TLV	PEL
Titanium Dioxide	< 10.0 %	13463-67-7	10mg/m3	10mg/m3
Zinc Oxide	< 5.0 %	1314-13-2	10mg/m3	10mg/m3

## SECTION II - PHYSICAL DATA

**BOILING RANGE:** 

212°F/100°C

**VAPOR DENSITY:** 

HEAVIER THAN AIR.

**EVAPORATION RATE:** 

SLOWER THAN ETHER

**VOLATILE VOLUME: 55%** 

**WEIGHT PER GALLON:** 

APPROX. 11 Lb.

## SECTION IN FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: OSHA, None.

EXTINGUISHING MEDIA: CO2 DRY CHEMICAL,

WATER MIST OR WATER FOG.

DOT: NOT REGULATED.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** CLOSED CONTAINER MAY EXPLODE IN

FLASH POINT: NON-COMBUSTIBLE. (PMCC)

EXTREME HEAT.

LEL: NONE.

SPECIAL FIRE FIGHTING PROCEDURES:

NONE.

## SECTION V - HEALTH HAZARD DATA

**EFFECTS OF OVEREXPOSURE:** 

BREATHING OF HIGH VAPOR CONCENTRATIONS MAY CAUSE NAUSEA.

DIZZINESS, IRRITATION TO NASAL AND RESPIRATORY PASSAGES.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY OVEREXPOSURE: UNKNOWN.

PRIMARY ROUTE(S) OF ENTRY:

INHALATION, INGESTION, SKIN OR EYE CONTACT.

**EMERGENCY FIRST AID PROCEDURES:** 

INHALATION: MOVE SUBJECT TO FRESH AIR.

INGESTION: DRINK 2 GLASSES OF WATER, DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN.

WASH THOROUGHLY WITH SOAP AND WATER.

SKIN:

EYES: FLUSH WITH WATER FOR 15 MINUTES, IF IRRITATION PERSISTS CONSULT A PHYSICIAN.

## SECTION V! - REACTIVITY DATA

STABILITY: STABLE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION PRODUCTS: NONE KNOWN.

**CONDITIONS TO AVOID:** EXTREME HEAT.

INCOMPATIBILITY (Materials to Avoid): MATERIALS WHICH REACT WITH WATER.

## SECTION VI - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SOAK UP WITH ABSORBENT

MATERIAL. LET DRY. DISCARD IN DISPOSABLE CONTAINERS.

**WASTE DISPOSAL METHOD:** AS SOLID WASTE PER LOCAL, STATE AND FEDERAL REGULATIONS.

## SECTION VELOSAFE HANDLING AND USE INFORMATION

**RESPIRATORY PROTECTION:** USE NIOSH APPROVED AIR RESPIRATOR WHEN SPRAYING MATERIAL.

**VENTILATION:** PROVIDE SUFFICIENT NATURAL OR ARTIFICIAL VENTILATION.

PROTECTIVE GLOVES: OPTIONAL

EYE PROTECTION: SAFETY GLASSES OR EYE SHIELD.

OTHER PROTECTIVE EQUIPMENT: NONE.

## SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: USE AND STORE THIS PRODUCT BETWEEN 40°F

AND 100°F WITH ADEQUATE VENTILATION.

OTHER PRECAUTIONS: KEEP AWAY FROM CHILDREN. DO NOT TAKE INTERNALLY.