

Flex-Flash F



A SIKA COMPANY

GENERAL DESCRIPTION

Flex-Flash F is a spunbonded polyester fabric.

BASIC USE

Flex-Flash F is designed to be used as the standard reinforcement material for Hydrotech's Monolithic Membrane 6125® roofing and waterproofing membrane. It is used to reinforce the membrane over cracks, construction joints and changes-in-plane. It is also used in between layers of MM6125® over the entire substrate area to form the "FR" or fabric reinforced assembly.

Flex Flash F is not intended to be used as drains, expansion joints, or as an exposed flashing.



SIZES

Flex-Flash F is available in standard widths of 6, 12 and 39 inches and the standard length of 600 feet.

TECHNICAL DATA

PROPERTY	TEST METHOD	RESULTS
COLOR		White
UNIT WEIGHT (oz/sq yd)	ASTM D1910	1.35
% ELONGATION (to break)	ASTM D2523	42
TEAR STRENGTH (lb)	ASTM D2263	8
BREAKING STRENGTH (lb)	ASTM D2523	25
DE MATIA FLEX CYCLES	ASTM D813	100,000

(values published are min. req)

LEED INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	0	
Manufacture Location		Old Hickory, TN
Extraction/Harvesting Location		Old Hickory, TN
VOC Content (g/L)		0

This information is intended only for general conceptual purposes. It is based on data and knowledge considered to be true and correct. It is offered for the user's consideration, investigation and verification and is not intended to substitute for the advice provided by appropriate professionals. Hydrotech assumes no liability for the use of this information. The determination of the suitability and applicability of this information is the sole responsibility of the user.