

HydroSeal Finish-Color/ Finish-Textured



GENERAL DESCRIPTION

HydroSeal Finish resins - HydroSeal Finish-Color / HydroSeal Finish-Textured - are UV stabilized, pigmented, high performance, two-component, rapid curing, poly methyl-methacrylate based acrylic finishes.

HydroSeal Finish-Color and Finish-Textured are available in a variety of standard colors. Please reference Hydrotech's HydroSeal Resin Color Finish information sheet.

BASIC USE

HydroSeal Finish resins are used to provide a variety of surfacing options and sealers over completed HydroSeal Deck Membrane applications. Reference Hydrotech's HydroSeal Deck Membrane TechData Sheet for specifics.

APPLICATION

Reference Hydrotech's HydroSeal Deck Membrane Tech Data Sheet for specific use and application information for each Finish application

PACKAGING/SIZES/COVERAGE

HydroSeal Finish-Color is supplied in 10 kg resealable drums with locking rings. HydroSeal Finish-Textured is supplied in 15 kg resealable drums with locking rings.

On normal surfaces, each 10 kg unit of Finish-Color will cover approximately 154 sqft (14.3 sqm) when using 0.4-0.8 mm aggregates and 134 sqft (12.4 sqm) when using 0.7-1.2 mm aggregates. Each 15 kg unit of Finish-Textured will cover approximately 90 sqft (8.3 sqm). Yields will vary depending upon system selected and the smoothness and absorbency of substrate.

Approximate coverage rates:

Finish-Color

- 0.4-0.8 mm aggregates: 0.06 kg/sqft (0.7 kg/sqm)

- 0.7-1.2 mm aggregates: 0.07 kg/sqft (0.8 kg/sqm)

Finish-Textured 0.17 kg/sqft (1.8 kg/sqm)

PRECAUTIONS

Keep away from open fire, flame or any ignition source. Vapors may form explosive mixture with air. Avoid skin and eye contact with this material. Avoid breathing fumes. Do not eat, drink or smoke in area of application. Refer to product Material Safety Data Sheet (MSDS) for additional information pertaining to this product and prior to use or handling.

Workers should wear appropriate clothing to protect from accidental skin contact. When mixing or applying this product workers must use butyl rubber or nitrile gloves. Safety glasses with side shields are required for eye protection. In enclosed spaces, use local exhaust ventilation to maintain worker exposure below TLV. If the airborne concentration poses a health hazard, become irritating or exceeds recommended limits, use a NIOSH approved respirator in accordance with OSHA Respirator Protection requirements under 29 CFR 1910.134. The specific type of respirator will depend on the airborne concentrations. A filtering face piece or dusk mask is not acceptable for use with this product if TLV filtering levels have been exceeded.

Catalyzed and cured resin may be disposed of in standard landfills. Uncured resin is considered a hazardous material and must be handled as such, in accordance with local, state and federal regulations.

This information is intended only for general conceptual purposes. It is based on data and knowledge considered to be true and correct. It is offered for the user's consideration, investigation and verification and is not intended to substitute for the advice provided by appropriate professionals. Hydrotech assumes no liability for the use of this information. The determination of the suitability and applicability of this information is the sole responsibility of the user.