

**1 Identification**

- **Product identifier**
- **Trade name:** HydroSeal® Mortar
- **Article number:** HSMORTAR15
- **Application of the substance / the mixture** Self-levelling mortar
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
American Hydrotech, Inc.  
541 N Fairbanks  
Chicago, IL 60611 USA  
Tel: 312 337-4998  
Fax: 312 661-0731  
www.hydrotechusa.com
- **Information department:** Division product safety
- **Emergency telephone number:** PERS #11540 - (800) 633-8253

**2 Hazard(s) identification**

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger

- **Hazard-determining components of labeling:**

methyl methacrylate

2-ethylhexyl acrylate

Fatty acid, C 18 - unsaturated, dimers, reaction products with N, N-dimethyl-1,3-propanediamine

- **Hazard statements**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

- **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing vapours.

P280 Wear protective gloves/ eye protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

(Contd. on page 2)

**Trade name: HydroSeal® Mortar**

(Contd. of page 1)

P312 Call a poison center/doctor if you feel unwell.  
 P403+P235 Store in a well-ventilated place. Keep cool.

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Does not meet the PBT-criteria of Annex XIII of REACH (self assessment).
- **vPvB:** Does not meet the vPvB-criteria of Annex XIII of REACH (self assessment).

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 80-62-6 Index number: 607-035-00-6	methyl methacrylate	10-25%
CAS: 103-11-7 Index number: 607-107-00-7	2-ethylhexyl acrylate	≥2.5-<10%
CAS: 13463-67-7	titanium dioxide	≥0.1-≤0.5%
CAS: 162627-17-0	Fatty acid, C 18 - unsaturated, dimers, reaction products with N, N-dimethyl-1,3-propanediamine	≥0.1-≤0.5%

- **Additional information:**  
 Product does not contain respirable particulate matter. Classification with H373 / H372 does not apply to the preparation.

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
 Immediately remove any clothing soiled by the product.  
 Take affected persons out of danger area and lay down.  
 Personal protection for the First Aider.  
 Involve doctor immediately.
- **After inhalation:**  
 In case of unconsciousness place patient stably in side position for transportation.  
 Take affected persons into fresh air and keep quiet.  
 Seek medical treatment.
- **After skin contact:**  
 Immediately wash with water and soap and rinse thoroughly.  
 If skin irritation continues, consult a doctor.  
 Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not induce vomiting; immediately call for medical help.

(Contd. on page 3)  
 US —

**Trade name: HydroSeal® Mortar**

(Contd. of page 2)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
Irritant to skin, eyes and respiratory system.
- **Indication of any immediate medical attention and special treatment needed**  
After inhalation, even in the absence of signs of disease, inhaled corticosteroid (eg Ventolair) give.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**  
Can form explosive gas-air mixtures.  
In case of fire, the following can be released:  
Carbon monoxide (CO)  
Nitrogen oxides (NO<sub>x</sub>)  
Vapours are heavier than air.  
Crawling vapors can result in greater distance from the ignition!
- **Advice for firefighters**
- **Protective equipment:**  
Wear fully protective suit.  
Wear self-contained respiratory protective device.
- **Additional information**  
Cool endangered receptacles with water spray.  
Collect contaminated fire fighting water separately. It must not enter the sewage system.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation



Keep away from ignition sources

Use respiratory protective device against the effects of fumes/dust/aerosol.  
Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:**  
Do not allow to enter sewers/ surface or ground water.  
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**  
Do not flush with water or aqueous cleansing agents  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

80-62-6	methyl methacrylate	17 ppm
103-11-7	2-ethylhexyl acrylate	15 ppm
	Glasperlen	15 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	0.075 mg/m <sup>3</sup>
13463-67-7	titanium dioxide	30 mg/m <sup>3</sup>

(Contd. on page 4)

**Trade name: HydroSeal® Mortar**

	PEG 200 DMA	(Contd. of page 3) 30 mg/m <sup>3</sup>
107-98-2	1-methoxy-2-propanol	100 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
1317-61-9	C.I.Pigment black 11	21 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	5 ppm
20344-49-4	iron hydroxide oxide	24 mg/m <sup>3</sup>
1309-37-1	diiron trioxide	15 mg/m <sup>3</sup>
7447-41-8	lithium chloride	2.3 mg/m <sup>3</sup>
7631-86-9	silicon dioxide, chemically prepared	18 mg/m <sup>3</sup>
21645-51-2	aluminium hydroxide	8.7 mg/m <sup>3</sup>
1314-23-4	zirconium oxide	14 mg/m <sup>3</sup>
67-68-5	dimethyl sulfoxide	150 ppm

**· PAC-2:**

80-62-6	methyl methacrylate	120 ppm
103-11-7	2-ethylhexyl acrylate	120 ppm
	Glasperlen	170 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	33 mg/m <sup>3</sup>
13463-67-7	titanium dioxide	330 mg/m <sup>3</sup>
	PEG 200 DMA	330 mg/m <sup>3</sup>
107-98-2	1-methoxy-2-propanol	160 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
1317-61-9	C.I.Pigment black 11	230 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	200 ppm
20344-49-4	iron hydroxide oxide	260 mg/m <sup>3</sup>
1309-37-1	diiron trioxide	360 mg/m <sup>3</sup>
7447-41-8	lithium chloride	25 mg/m <sup>3</sup>
7631-86-9	silicon dioxide, chemically prepared	740 mg/m <sup>3</sup>
21645-51-2	aluminium hydroxide	73 mg/m <sup>3</sup>
1314-23-4	zirconium oxide	110 mg/m <sup>3</sup>
67-68-5	dimethyl sulfoxide	290 ppm

**· PAC-3:**

80-62-6	methyl methacrylate	570 ppm
103-11-7	2-ethylhexyl acrylate	150 ppm
	Glasperlen	990 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	200 mg/m <sup>3</sup>
13463-67-7	titanium dioxide	2,000 mg/m <sup>3</sup>
	PEG 200 DMA	2,000 mg/m <sup>3</sup>
107-98-2	1-methoxy-2-propanol	660 ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
1317-61-9	C.I.Pigment black 11	1,400 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	3000* ppm
20344-49-4	iron hydroxide oxide	1,600 mg/m <sup>3</sup>
1309-37-1	diiron trioxide	2,200 mg/m <sup>3</sup>
7447-41-8	lithium chloride	150 mg/m <sup>3</sup>
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m <sup>3</sup>
21645-51-2	aluminium hydroxide	440 mg/m <sup>3</sup>
1314-23-4	zirconium oxide	680 mg/m <sup>3</sup>

(Contd. on page 5)

**Trade name: HydroSeal® Mortar**

67-68-5 dimethyl sulfoxide	(Contd. of page 4) 1,800 ppm
----------------------------	---------------------------------

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Cool down container when heated. Cool containers exposed to heat with water. Emergency cooling must be provided in the event of an ambient fire. Keep container tightly closed to prevent heat build up (pressure increase). Avoid heat.  
Do not refill residue into storage receptacles.  
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).  
at least 7-fold air changes per hour  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Highly volatile, flammable constituents are released during processing.  
Keep ignition sources away - Do not smoke.  
Fumes can combine with air to form an explosive mixture.  
Only explosion-proof equipment.  
Protect against electrostatic charges.  
Protect from heat.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store only in the original receptacle.  
Store in a cool location.
- **Information about storage in one common storage facility:**  
Store away from oxidizing agents.  
Store away from foodstuffs.
- **Further information about storage conditions:**  
Store in cool, dry conditions in well sealed receptacles.  
Storage in a collecting room is required.  
Store under lock and key and with access restricted to technical experts or their assistants only.  
max. Storage temperature 30 ° C  
Keep receptacle tightly sealed.  
Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

**80-62-6 methyl methacrylate (10-25%)**

PEL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
REL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 410 mg/m <sup>3</sup> , 100 ppm Long-term value: 205 mg/m <sup>3</sup> , 50 ppm
DSEN	

- **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 6)

**Trade name: HydroSeal® Mortar**

(Contd. of page 5)

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· **Breathing equipment:**

Ensure good ventilation.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Check protective gloves prior to each use for their proper condition.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

· **Material of gloves**



Butyl rubber gloves - butyl e.g. KCL BUTOJET

Recommended thickness of the material:  $\geq 0.7$  mm

Breakthrough time:  $\geq 480$  min

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

Our Recommendation is mainly on a one-time use as a short-term protection Liquid splashes. For other applications, you should contact a glove manufacturer.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:** Butyl rubber, BR

· **Not suitable are gloves made of the following materials:** Leather gloves

· **Eye protection:**



Tightly sealed goggles

· **Body protection:**



Protective work clothing

Trade name: HydroSeal® Mortar

(Contd. of page 6)

## 9 Physical and chemical properties

· <b>Information on basic physical and chemical properties</b>	
· <b>General Information</b>	
· <b>Appearance:</b>	
<b>Form:</b>	Fluid
<b>Color:</b>	Grey
· <b>Odor:</b>	Ester-like
· <b>Odor threshold:</b>	not be determined.
· <b>pH-value:</b>	Not determinable.
· <b>Change in condition</b>	
<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	Undetermined.
· <b>Flash point:</b>	12 °C (53.6 °F) (DIN EN ISO 3679:2015-06)
· <b>Ignition temperature:</b>	430 °C (806 °F) (MMA)
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible. Not determined.
· <b>Explosion limits:</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
· <b>Vapor pressure:</b>	Not determined.
· <b>Density at 20 °C (68 °F):</b>	1.7 g/cm <sup>3</sup> (14.19 lbs/gal) (EN ISO 2811-1)
· <b>Evaporation rate</b>	No data available.
· <b>Solubility in / Miscibility with Water:</b>	
	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b> log Pow: 4,29 (2-EHA); (25 °C, OECD 107) log Pow: 1,38 (MMA)	
· <b>Viscosity:</b>	
<b>Dynamic at 20 °C (68 °F):</b>	10,500 mPas (EN ISO 2555)
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	0.4 %
<b>VOC content:</b>	0.37 % 6.3 g/l / 0.05 lb/gal
<b>Solids content:</b>	84.0 %
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** see Section 10.2
- **Chemical stability** No decomposition if used according to specifications.
- **Possibility of hazardous reactions**  
Exothermic reaction.  
Reacts with peroxides and other radical forming substances.  
A hazardous polymerization may occur after the exhaustion of the inhibitor.
- **Conditions to avoid** Avoid heat. Avoid direct sunlight.
- **Incompatible materials:** Heftige Reaktionen mit Peroxiden und anderen Reduktionsmittel
- **Hazardous decomposition products:** No dangerous decomposition products known.

(Contd. on page 8)

**Trade name: HydroSeal® Mortar**

(Contd. of page 7)

· **Additional information:**

Emergency procedures will vary depending on individual circumstances. The customer should have a contingency plan to the workplace may be present.

## 11 Toxicological information

· **Information on toxicological effects** There were no toxicological findings to the mixture.

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**ATE (Acute Toxicity Estimate)**

Oral	LD50	94,017 mg/kg (rat)
Inhalative	LC50/4h	282 mg/l (rat)

**80-62-6 methyl methacrylate**

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
	NOAEL	2,000 ppm (rat) drinking water, 6-2000 ppm Findings: No toxic effects
Dermal	LC50	>5,000 mg/kg (rabbit)
Inhalative	NOAEL	25 ppm (rat) 25 - 400 ppm Findings: Damage to mucous membranes in the nose at 400 ppm
	LC50/4h	29.8 mg/l (rat)

**103-11-7 2-ethylhexyl acrylate**

Oral	LD50	4,435 mg/kg (rat) (BASF-Test)
Dermal	LC50	7,520 mg/kg (hare)

**13463-67-7 titanium dioxide**

Oral	LD50	>20,000 mg/kg (rat)
Dermal	LC50	>10,000 mg/kg (hare)
Inhalative	LC50/4h	>6.82 mg/l (rat)

· **Primary irritant effect:**

· **on the skin:** Irritability

· **on the eye:** Irritating effect.

· **Sensitization:** Sensitization possible through skin contact.

· **Other information (about experimental toxicology):**

Due to the high vapor pressure is a harmful concentration in the air quickly been reached. At high concentrations can occur narcotic effect.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

80-62-6	methyl methacrylate	3
103-11-7	2-ethylhexyl acrylate	3
14808-60-7	Quartz (SiO <sub>2</sub> )	1
13463-67-7	titanium dioxide	2B
1309-37-1	diiron trioxide	3
128-37-0	Butylated hydroxytoluene	3
7631-86-9	silicon dioxide, chemically prepared	3

(Contd. on page 9)



**Trade name: HydroSeal® Mortar**

(Contd. of page 8)

· <b>NTP (National Toxicology Program)</b>	
14808-60-7 Quartz (SiO <sub>2</sub> )	K
· <b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>	
None of the ingredients is listed.	

## 12 Ecological information

· <b>Toxicity</b>	
<b>80-62-6 methyl methacrylate</b>	
EC3/16h	100 mg/l (Pseudomonas putida) (Cell proliferation inhibition test, Bringmann-Kühn)
· <b>Aquatic toxicity:</b>	
<b>80-62-6 methyl methacrylate</b>	
EC50/48h	69 mg/l (daphnia magna) (OECD 202)
LC50/96h	>79 mg/l (Rainbow trout) (OECD 203)
ErC50/72h	>110 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
NOEC/72h	>110 mg/l (Selenastrum capricornutum) (OECD 201)
EC50/72h	>110 mg/l (Selenastrum capricornutum) (OECD 201)
NOEC	9.4 mg/l (Danio rerio) (OECD 210) fish early life stage test, 35 days
	37 mg/l (daphnia magna) (OECD 211) 21 days
<b>103-11-7 2-ethylhexyl acrylate</b>	
other (28d)	>1,000 mg/kg (Soil microorganisms) (OECD 217) The product has not been tested. The statement has been derived from products of a similar structure or composition.
EC50/48h (static)	1.3 mg/l (daphnia magna) (OECD-Richtline 202) Part 1
LC50/96h (static)	1.81 mg/l (Rainbow trout) (OECD 203)
NOEC/21d	0.19 mg/l (daphnia magna) The details of the toxic effect relates to the analytically determined concentration. The product has not been tested. The statement has been derived from products of a similar structure or composition.
EC50/72h (static)	1.71 mg/l (scenedesmus subspicatus) (OECD 201) Die Angaben der toxischen Wirkung bezieht sich auf die analytisch ermittelte Konzentration.

- **Persistence and degradability** No further relevant information available.
- **Other information:** The product is easily biodegradable.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil**  
MMA: A binding to the solid phase of soil, sediment and sewage sludge is not expected. From the water surface the substance is slowly evaporated into the atmosphere. Where the substance into the environment he verleiht preferably in the compartment into which it has emerged.
- **Additional ecological information:**
- **BSB5-value:** 0.14 g/g (MMA)
- **General notes:**  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow product to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Does not meet the PBT-criteria of Annex XIII of REACH (self assessment).
- **vPvB:** Does not meet the vPvB-criteria of Annex XIII of REACH (self assessment).

(Contd. on page 10)

**Trade name: HydroSeal® Mortar**

(Contd. of page 9)

- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**

Hazardous waste according to Waste Catalogue (EWC). If recycling is not possible, waste must be in compliance with local regulations to be removed.

- **Recommendation:**






Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncured product residues are special waste.  
Cured product residues are not hazardous waste.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

· <b>UN-Number</b> · <b>DOT, ADR, IMDG, IATA</b>	UN1263
· <b>UN proper shipping name</b> · <b>DOT</b> · <b>ADR</b> · <b>IMDG, IATA</b>	Paint 1263 PAINT PAINT
· <b>Transport hazard class(es)</b> · <b>DOT</b>	
	
· <b>Class</b> · <b>Label</b>	3 Flammable liquids 3
· <b>ADR</b>	
	
· <b>Class</b> · <b>Label</b>	3 (F1) Flammable liquids 3
· <b>IMDG, IATA</b>	
	
· <b>Class</b> · <b>Label</b>	3 Flammable liquids 3
· <b>Packing group</b> · <b>DOT, ADR, IMDG, IATA</b>	III

(Contd. on page 11)

**Trade name: HydroSeal® Mortar**

(Contd. of page 10)

· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	Warning: Flammable liquids
· <b>Hazard identification number (Kemler code):</b> -	
· <b>EMS Number:</b>	F-E, S-E
· <b>Stowage Category</b>	A
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Remarks:</b>	Classification according to viscosity clause [(173.120 (2) (d) and 173.121 (b) (iv)]
· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>Remarks:</b>	Classification according to viscosity clause (2.2.3.1.4) > 450 litres Packing group II
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>Remarks:</b>	Classification according to viscosity clause (2.3.2.2) > 450 litres Packing group II
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, III

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

80-62-6 methyl methacrylate

· **TSCA (Toxic Substances Control Act):**

80-62-6	methyl methacrylate	ACTIVE
103-11-7	2-ethylhexyl acrylate	ACTIVE
	Glasperlen	ACTIVE
14808-60-7	Quartz (SiO <sub>2</sub> )	ACTIVE
13463-67-7	titanium dioxide	ACTIVE
	PEG 200 DMA	ACTIVE
107-98-2	1-methoxy-2-propanol	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
1317-61-9	C.I.Pigment black 11	ACTIVE
3147-75-9	2-(2H-benzotriazol-2-yl)-4-(1,1,3,3-tetramethylbutyl)phenol	ACTIVE
123-86-4	n-butyl acetate	ACTIVE
20344-49-4	iron hydroxide oxide	ACTIVE

(Contd. on page 12)

**Trade name: HydroSeal® Mortar**

(Contd. of page 11)

8002-74-2	Paraffin waxes and Hydrocarbon waxes	ACTIVE
1309-37-1	diiron trioxide	ACTIVE
128-37-0	Butylated hydroxytoluene	ACTIVE
	Silan, dichlordimethyl-, Reaktionsprodukte mit Siliciumdioxid	ACTIVE
7447-41-8	lithium chloride	ACTIVE
7631-86-9	silicon dioxide, chemically prepared	ACTIVE
21645-51-2	aluminium hydroxide	ACTIVE
1314-23-4	zirconium oxide	ACTIVE
67-68-5	dimethyl sulfoxide	ACTIVE

· **Hazardous Air Pollutants**

80-62-6 methyl methacrylate

· **Proposition 65**

· **Chemicals known to cause cancer:**

14808-60-7 Quartz (SiO<sub>2</sub>)

13463-67-7 titanium dioxide

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

80-62-6 methyl methacrylate

E, NL

· **TLV (Threshold Limit Value established by ACGIH)**

80-62-6 methyl methacrylate

A4

14808-60-7 Quartz (SiO<sub>2</sub>)

A2

13463-67-7 titanium dioxide

A4

1309-37-1 diiron trioxide

A4

128-37-0 Butylated hydroxytoluene

A4

1314-23-4 zirconium oxide

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7 Quartz (SiO<sub>2</sub>)

13463-67-7 titanium dioxide

· **National regulations:**

· **Information about limitation of use:**

Employment restrictions concerning young persons must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**\* 16 Other information**

These figures relate to the product as delivered.

Sector of Use

Relevant identified uses of the mixture

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU19 Building and construction work

(Contd. on page 13)

**Trade name: HydroSeal® Mortar**

(Contd. of page 12)

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

SU21 Consumer uses: Private households / general public / consumers

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Training hints**

Teaching about hazards and precautions to hand the operating instructions (Technical Rule 555). Instruction must take place before the start of employment and at least annually thereafter.

**· Date of preparation / last revision 08/25/2020 / -****· Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety &amp; Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

**· Sources**[www.gestis.de](http://www.gestis.de)[www.echa.eu](http://www.echa.eu)[logkow.cisti.nrc.ca](http://logkow.cisti.nrc.ca)**· \* Data compared to the previous version altered.**