



## Hydrotech® HydroSeal Primer-Flashing

Revision Date 01/07/2025

Print Date 01/07/2025

### SECTION 1. IDENTIFICATION

Product name : Hydrotech® HydroSeal Primer-Flashing

Company name : Sika Corporation  
201 Polito Avenue  
Lyndhurst, NJ 07071  
USA  
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300  
INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 2

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitization : Category 1

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

#### GHS label elements

Hazard pictograms :  

Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.



## Hydrotech® HydroSeal Primer-Flashing

Revision Date 01/07/2025

Print Date 01/07/2025

H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.

Precautionary Statements

:

**Prevention:**

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.  
No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing mist or vapors.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.



## Hydrotech® HydroSeal Primer-Flashing

Revision Date 01/07/2025

Print Date 01/07/2025

### Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

### Other hazards

Intentional misuse by deliberate concentration and inhalation of vapor may be harmful or fatal.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Mixtures

#### Components

| Chemical name                                                                                 | CAS-No.     | Classification                                                                      | Concentration (% w/w) |
|-----------------------------------------------------------------------------------------------|-------------|-------------------------------------------------------------------------------------|-----------------------|
| methyl methacrylate                                                                           | 80-62-6     | Flam. Liq. 2; H225<br>Skin Irrit. 2; H315<br>Skin Sens. 1; H317<br>STOT SE 3; H335  | $\geq 50 - < 70$      |
| bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq 700$ )        | 25068-38-6  | Skin Irrit. 2; H315<br>Eye Irrit. 2A; H319<br>Skin Sens. 1; H317                    | $\geq 20 - < 30$      |
| 2-ethylhexyl acrylate                                                                         | 103-11-7    | Skin Irrit. 2; H315<br>Skin Sens. 1B; H317<br>STOT SE 3; H335                       | $\geq 5 - < 10$       |
| alpha, alpha'-(2,2-Diméthylpropane-1,3-diyl)bis{omega-(acryloyloxy)poly[oxy(méthyléthylène)]} | 84170-74-1  | Skin Sens. 1B; H317                                                                 | $\geq 1 - < 5$        |
| aromatic amine ethoxylated                                                                    | 103671-44-9 | Acute Tox. 4; H302<br>Skin Irrit. 2; H315<br>Eye Dam. 1; H318<br>Skin Sens. 1; H317 | $\geq 0.1 - < 1$      |

Actual concentration is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.



## Hydrotech® HydroSeal Primer-Flashing

Revision Date 01/07/2025

Print Date 01/07/2025

|                                                             |   |                                                                                                                                                                                                                                                                                              |
|-------------------------------------------------------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                             |   | Keep eye wide open while rinsing.<br>If eye irritation persists, consult a specialist.                                                                                                                                                                                                       |
| If swallowed                                                | : | Clean mouth with water and drink afterwards plenty of water.<br>Do not induce vomiting without medical advice.<br>Do not give milk or alcoholic beverages.<br>Never give anything by mouth to an unconscious person.<br>Obtain medical attention.                                            |
| Most important symptoms and effects, both acute and delayed | : | Causes skin irritation.<br>May cause an allergic skin reaction.<br>Causes serious eye irritation.<br>May cause respiratory irritation.<br>irritant effects<br>sensitizing effects<br>Cough<br>Respiratory disorder<br>Allergic reactions<br>Excessive lachrymation<br>Erythema<br>Dermatitis |
| Notes to physician                                          | : | Treat symptomatically.                                                                                                                                                                                                                                                                       |

---

### SECTION 5. FIRE-FIGHTING MEASURES

|                                                |   |                                                                                                                                                                                                                                                                         |
|------------------------------------------------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable extinguishing media                   | : | Alcohol-resistant foam<br>Carbon dioxide (CO <sub>2</sub> )<br>Dry chemical                                                                                                                                                                                             |
| Unsuitable extinguishing media                 | : | Water<br>High volume water jet                                                                                                                                                                                                                                          |
| Specific hazards during fire fighting          | : | Do not use a solid water stream as it may scatter and spread fire.                                                                                                                                                                                                      |
| Further information                            | : | Use water spray to cool unopened containers.<br>Collect contaminated fire extinguishing water separately. This must not be discharged into drains.<br>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
| Special protective equipment for fire-fighters | : | In the event of fire, wear self-contained breathing apparatus.                                                                                                                                                                                                          |

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES



## Hydrotech® HydroSeal Primer-Flashing

Revision Date 01/07/2025

Print Date 01/07/2025

- |                                                                     |   |                                                                                                                                                                                                                                 |
|---------------------------------------------------------------------|---|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Personal precautions, protective equipment and emergency procedures | : | Use personal protective equipment.<br>Remove all sources of ignition.<br>Deny access to unprotected persons.<br>Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.             |
| Environmental precautions                                           | : | Prevent product from entering drains.<br>If the product contaminates rivers and lakes or drains inform respective authorities.<br>Local authorities should be advised if significant spillages cannot be contained.             |
| Methods and materials for containment and cleaning up               | : | Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). |

---

### SECTION 7. HANDLING AND STORAGE

- |                                                 |   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-------------------------------------------------|---|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advice on protection against fire and explosion | : | Use explosion-proof equipment.<br>Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.<br>Take precautionary measures against electrostatic discharges.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Advice on safe handling                         | : | Do not breathe vapors or spray mist.<br>Avoid exceeding the given occupational exposure limits (see section 8).<br>Do not get in eyes, on skin, or on clothing.<br>For personal protection see section 8.<br>Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.<br>Smoking, eating and drinking should be prohibited in the application area.<br>Take precautionary measures against static discharge.<br>Open drum carefully as content may be under pressure.<br>Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).<br>Follow standard hygiene measures when handling chemical products. |
| Conditions for safe storage                     | : | Store in original container.<br>Store in cool place.<br>Keep in a well-ventilated place.<br>Containers which are opened must be carefully resealed and kept upright to prevent leakage.<br>Observe label precautions.<br>Store in accordance with local regulations.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |



## Hydrotech® HydroSeal Primer-Flashing

Revision Date 01/07/2025

Print Date 01/07/2025

Materials to avoid : Explosives  
Oxidizing agents  
Poisonous gases  
Poisonous liquids

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

| Components          | CAS-No. | Value type<br>(Form of exposure) | Control parameters / Permissible concentration | Basis    |
|---------------------|---------|----------------------------------|------------------------------------------------|----------|
| methyl methacrylate | 80-62-6 | TWA                              | 100 ppm<br>410 mg/m <sup>3</sup>               | OSHA Z-1 |
|                     |         | TWA                              | 100 ppm<br>410 mg/m <sup>3</sup>               | OSHA P0  |

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.  
The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

#### Personal protective equipment

**Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.  
  
The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.



## Hydrotech® HydroSeal Primer-Flashing

Revision Date 01/07/2025

Print Date 01/07/2025

|                          |   |                                                                                                                                                                                                                                                                                                                                                |
|--------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Skin and body protection | : | Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.                                                                                                                                                                                                       |
| Hygiene measures         | : | Avoid contact with skin, eyes and clothing.<br>Wash hands before breaks and immediately after handling the product.<br>Remove respiratory and skin/eye protection only after vapors have been cleared from the area.<br>Remove contaminated clothing and protective equipment before entering eating areas.<br>Wash thoroughly after handling. |

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

|                                                  |   |                                            |
|--------------------------------------------------|---|--------------------------------------------|
| Appearance                                       | : | liquid                                     |
| Color                                            | : | white                                      |
| Odor                                             | : | No data available                          |
| Odor Threshold                                   | : | No data available                          |
| pH                                               | : | not determined                             |
|                                                  | : | not determined                             |
| Boiling point/boiling range                      | : | ca. 214 °F / 101 °C                        |
| Flash point                                      | : | ca. 63 °F / 17 °C<br>(Method: closed cup)  |
| Evaporation rate                                 | : | No data available                          |
| Flammability (solid, gas)                        | : | No data available                          |
| Upper explosion limit / Upper flammability limit | : | No data available                          |
| Lower explosion limit / Lower flammability limit | : | No data available                          |
| Vapor pressure                                   | : | 40 hpa                                     |
| Relative vapor density                           | : | No data available                          |
| Density                                          | : | ca. 1.08 g/cm <sup>3</sup> (68 °F / 20 °C) |
| Solubility(ies)<br>Water solubility              | : | immiscible                                 |



## Hydrotech® HydroSeal Primer-Flashing

Revision Date 01/07/2025

Print Date 01/07/2025

|                                          |   |                                                                                          |
|------------------------------------------|---|------------------------------------------------------------------------------------------|
| Solubility in other solvents             | : | No data available                                                                        |
| Partition coefficient: n-octanol/water   | : | No data available                                                                        |
| Autoignition temperature                 | : | No data available                                                                        |
| Decomposition temperature                | : | No data available                                                                        |
| Viscosity                                |   |                                                                                          |
| Viscosity, dynamic                       | : | No data available                                                                        |
| Viscosity, kinematic                     | : | Not applicable                                                                           |
| Explosive properties                     | : | No data available                                                                        |
| Oxidizing properties                     | : | No data available                                                                        |
| Volatile organic compounds (VOC) content | : | 9.0 g/l<br>Hydrotech® HydroSeal Primer-Flashing + Hydrotech® HydroSeal Catalyst Combined |

---

### SECTION 10. STABILITY AND REACTIVITY

|                                    |   |                                                                                             |
|------------------------------------|---|---------------------------------------------------------------------------------------------|
| Reactivity                         | : | No dangerous reaction known under conditions of normal use.                                 |
| Chemical stability                 | : | The product is chemically stable.                                                           |
| Possibility of hazardous reactions | : | Stable under recommended storage conditions.<br>Vapors may form explosive mixture with air. |
| Conditions to avoid                | : | Heat, flames and sparks.                                                                    |
| Incompatible materials             | : | No data available                                                                           |
| Hazardous decomposition products   | : | No decomposition if stored and applied as directed.                                         |

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified due to lack of data.

#### Components:

##### **methyl methacrylate:**

|                           |   |                                |
|---------------------------|---|--------------------------------|
| Acute oral toxicity       | : | LD50 Oral (Rat): > 5,000 mg/kg |
| Acute inhalation toxicity | : | LC50 (Rat): 29.8 mg/l          |



## Hydrotech® HydroSeal Primer-Flashing

Revision Date 01/07/2025

Print Date 01/07/2025

Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

### **bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700):**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

### **2-ethylhexyl acrylate:**

Acute oral toxicity : LD50 Oral (Rat): 4,435 mg/kg

### **Skin corrosion/irritation**

Causes skin irritation.

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### **Respiratory or skin sensitization**

#### **Skin sensitization**

May cause an allergic skin reaction.

#### **Respiratory sensitization**

Not classified due to lack of data.

#### **Germ cell mutagenicity**

Not classified due to lack of data.

### **Carcinogenicity**

Not classified due to lack of data.

**IARC** Group 2B: Possibly carcinogenic to humans  
2-ethylhexyl acrylate

103-11-7

**OSHA** Not applicable

**NTP** Not applicable

### **Reproductive toxicity**

Not classified due to lack of data.

### **STOT-single exposure**

May cause respiratory irritation.

### **STOT-repeated exposure**

Not classified due to lack of data.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.



## Hydrotech® HydroSeal Primer-Flashing

Revision Date 01/07/2025

Print Date 01/07/2025

### Aspiration toxicity

Not classified due to lack of data.

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### **methy methacrylate:**

Toxicity to fish : NOEC (Danio rerio (zebra fish)): 9.4 mg/l

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 69 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

NOEC: 37 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 202

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 37 mg/l  
Exposure time: 21 d

##### **bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700):**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.8 mg/l  
Exposure time: 48 h

##### **2-ethylhexyl acrylate:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.81 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.3 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 1.71 mg/l  
Exposure time: 72 h

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available



## Hydrotech® HydroSeal Primer-Flashing

Revision Date 01/07/2025

Print Date 01/07/2025

### Other adverse effects

#### Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.  
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
May be harmful to the environment if released in large quantities.  
Water polluting material.

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### **IATA-DGR**

UN/ID No. : UN 1263  
Proper shipping name : Paint  
Class : 3  
Packing group : II  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

##### **IMDG-Code**

UN number : UN 1263  
Proper shipping name : PAINT  
(epoxy resin)  
Class : 3  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : yes



## Hydrotech® HydroSeal Primer-Flashing

Revision Date 01/07/2025

Print Date 01/07/2025

### Domestic regulation

#### 49 CFR

UN/ID/NA number : UN 1263  
Proper shipping name : Paint  
Class : 3  
Packing group : II  
Labels : FLAMMABLE LIQUID  
ERG Code : 128  
Marine pollutant : no

DOT: For Limited Quantity exceptions reference 49 CFR 173.150 (b)

IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

**TSCA list** : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

### CERCLA Reportable Quantity

| Components          | CAS-No. | Component RQ (lbs) |
|---------------------|---------|--------------------|
| methyl methacrylate | 80-62-6 | 1000               |

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Respiratory or skin sensitization  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Specific target organ toxicity (single or repeated exposure)

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:



## Hydrotech® HydroSeal Primer-Flashing

Revision Date 01/07/2025

Print Date 01/07/2025

methyl methacrylate 80-62-6

>= 50 - < 70 %

### Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):  
methyl methacrylate 80-62-6 >= 50 - < 70 %

### California Prop. 65

 **WARNING:** This product can expose you to chemicals including 2-ethylhexyl acrylate, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

|                |   |                                                                                  |
|----------------|---|----------------------------------------------------------------------------------|
| OSHA P0        | : | USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)               |
| OSHA Z-1       | : | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| OSHA P0 / TWA  | : | 8-hour time weighted average                                                     |
| OSHA Z-1 / TWA | : | 8-hour time weighted average                                                     |

### Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikausa.com](http://www.sikausa.com) or 201-933-8800.

Revision Date 01/07/2025

100000060794  
US / Z8