PRODUCT DATA SHEET Hydrotech LiteTop® Aggregate

GENERAL DESCRIPTION

Hydrotech LiteTop Aggregate is an expanded, lightweight aggregate (i.e., expanded shale, clay, slate, pumice and scoria).

BASIC USE

Hydrotech LiteTop Aggregate is used to fill the cups of Hydrotech's Gardendrain[®] 30 and 50 elements, as required, to enhance available water holding capacity for plant root systems and to increase compressive strength of the Gardendrain component. Can also be used as lightweight fill.

INSTALLATION

Vollume to Fill (GR30): 2 CY per 1,000 sq.ft. Vollume to Fill (GR50): 3 CY per 1,000 sq.ft.

TECHNICAL DATA

SIZE GRADATION:

Nominally 3/8" (depending on blender locality)

LEED® INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	Varies regionally, contact Hydrotech	
Manufacture Location		40+ locations, contact Hydrotech for more information
Extraction/Harvesting Location		40+ locations, contact Hydrotech for more information
VOC Content (g/L)		0

This information is intended only for general conceptual purposes. It is based on data and knowledge considered to be true and correct. It is offered for the user's consideration, investigation and verification and is not intended to substitute for the advice provided by appropriate professionals. Hydrotech assumes no liability for the use of this information. The determination of the suitability and applicability of this information is the sole responsibility of the user.

American Hydrotech, Inc. 303 East Ohio Street, Chicago, IL 60611 • (312)337-4998 • (312)661-0731 fax • 10/18



