

Hydrotech® LiteTop® Aggregate

formerly known as LiteTop® Aggregate



BUILDING TRUST



GENERAL DESCRIPTION

Hydrotech LiteTop Aggregate is an expanded, lightweight aggregate (i.e., expanded shale, clay, slate, pumice and scoria).

BASIC USE

Hydrotech LiteTop Aggregate is used to fill the cups of Hydrotech’s Gardendrain® GR30 and GR50 elements, as required, to enhance available water holding capacity for plant root systems and to increase compressive strength of the Gardendrain component.



INSTALLATION

Vollume to Fill (GR30): 2 CY per 1,000 sq.ft.
 Vollume to Fill (GR50): 3 CY per 1,000 sq.ft.

TECHNICAL DATA

SIZE GRADATION: Nominally 3/8” (depending on blender locality)

LEED® INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	Varies regionally, contact Hydrotech	
Manufacture Location	40+ locations, contact Hydrotech for more information	
Extraction/Harvesting Location	40+ locations, contact Hydrotech for more information	
VOC Content (g/L)	0	

Note to Designers:

The information in this product data sheet is general in nature and is not intended to be a stand-alone document to describe Hydrotech’s LiteTop Aggregate. This product data sheet must be used in combination with test results for the locally available LiteTop Aggregate for the project.

Contact Hydrotech for further information.

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA’s Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.