VM Water Based Adhesive



GENERAL DESCRIPTION

VM Water Based Adhesive is a water-based, rubber-based, low-tack adhesive primer.

BASIC USE

VM Water Based Adhesive is used on dry surfaces to condition them to be dust free, so the substrate is suitable for the application of Hydrotech's VM 60 sheet waterproofing membrane.

APPLICATION

- VM Water Based Adhesive may be applied with roller or brush at temperatures of 40°F and rising.
- Apply VM Water Based Adhesive to a clean, dry, dust free, and frost-free surface at a coverage rate of approximately 350 to 400 square feet per gallon on concrete.
- Exterior gypsum sheathing board products will vary in texture, performance, and porosity.
- The coverage rate for VM Water Based Adhesive will vary due to substrate texture and porosity. Specific testing for coverage is recommended.
- The liquid adhesive should be spread sufficiently to avoid areas of excess material. Areas of excess material will lengthen the curing time on the application of the VM Water Based Adhesive.

LIMITATIONS/PRECAUTIONS

- Limit the application of liquid adhesive to what can be covered with VM 60 Membrane in one working day.
- Any areas not covered with membrane, must be recoated.
- Be sure to cover all open containers when not applying liquid adhesive.

CONTAINER/CONVERAGE

VM Water Based Adhesive is available in 5-gallon pails and cartons of four 1-gallon pails. VM Water Based Adhesive should be applied at a rate of 350 - 400 square feet per gallon.

LEED® INFORMATION

	Credit 4	Credit 5	
Recycled Content (% by weight)	0		
Manufacture Location		Corsicana, TX	
Extraction/Harvesting Location			
VOC Content (g/L)			100

This information is intended only for general conceptual purposes. It is based on data and knowledge considered to be true and correct. It is offered for the user's consideration, investigation and verification and is not intended to substitute for the advice provided by appropriate professionals. Hydrotech assumes no liability for the use of this information. The determination of the suitability and applicability of this information is the sole responsibility of the user.