



# Hydrotech® VM Water Based Adhesive

formerly known as VM Water Based Adhesive

## GENERAL DESCRIPTION

VM Water Based Adhesive is a water-based, rubber-based, low-tack adhesive primer.

## BASIC USE

VM Water Based Adhesive is used on dry surfaces to condition them to be dust free, so the substrate is suitable for the application of Hydrotech's VM 60 sheet waterproofing membrane.

## APPLICATION

- VM Water Based Adhesive may be applied with roller or brush at temperatures of 40°F and rising.
- Apply VM Water Based Adhesive to a clean, dry, dust free, and frost-free surface at a coverage rate of approximately 350 to 400 square feet per gallon on concrete.
- Exterior gypsum sheathing board products will vary in texture, performance, and porosity.
- The coverage rate for VM Water Based Adhesive will vary due to substrate texture and porosity. Specific testing for coverage is recommended.
- The liquid adhesive should be spread sufficiently to avoid areas of excess material. Areas of excess material will lengthen the curing time on the application of the VM Water Based Adhesive.

## LIMITATIONS/PRECAUTIONS

- Limit the application of liquid adhesive to what can be covered with VM 60 Membrane in one working day.
- Any areas not covered with membrane, must be recoated.
- Be sure to cover all open containers when not applying liquid adhesive.

## CONTAINER/CONVERAGE

VM Water Based Adhesive is available in 5-gallon pails and cartons of four 1-gallon pails. VM Water Based Adhesive should be applied at a rate of 350 - 400 square feet per gallon.

## LEED® INFORMATION

|                                | Credit 4 | Credit 5      |
|--------------------------------|----------|---------------|
| Recycled Content (% by weight) | 0        |               |
| Manufacture Location           |          | Corsicana, TX |
| Extraction/Harvesting Location |          |               |

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.