


# **SAFETY DATA SHEET**

### VM Water Based Adhesive

GHS product identifier	: VM Water Based Adhesive	
Product code	Not available.	
Other means of identification	: Not available.	
Product type	: Liquid.	
Relevant identified uses o	f the substance or mixture and uses advised against	
Identified uses		
Water based liquid adhesiv	e for use with sheet waterproofing membranes.	
Supplier's details	: American Hydrotech, Inc. 541 N Fairbanks Suite 2700 Chicago, IL 60611 (800) 877-6125	
Emergency telephone number (with hours of operation)	: PERS #11540 800-633-8253 24/7	
Section 2. Hazard	d(s) identification	
OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).	
Classification of the substance or mixture	: TOXIC TO REPRODUCTION (Unborn child) - Category 2 AQUATIC HAZARD (ACUTE) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 2	
<u>GHS label elements</u> Hazard pictograms	:	



- Warning
- : H361d Suspected of damaging the unborn child.
  - H411 Toxic to aquatic life with long lasting effects.

### Precautionary statements

# Section 2. Hazard(s) identification

Prevention	<ul> <li>P201 - Obtain special instructions before use.</li> <li>P202 - Do not handle until all safety precautions have been read and understood.</li> <li>P280 - Wear protective gloves, protective clothing and eye or face protection.</li> <li>P273 - Avoid release to the environment.</li> </ul>
Response	<ul> <li>P391 - Collect spillage.</li> <li>P308 + P313 - IF exposed or concerned: Get medical advice or attention.</li> </ul>
Storage	: P405 - Store locked up.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified (US)	: None known.

# Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

Ingredient name	% (w/w)	CAS number
Alkanes, C14-C16, Chloro	1 - 5	1372804-76-6
Toluene	0.1 - 1	108-88-3
Ammonia	0.1 - 1	1336-21-6
Ammonia, anhydrous	0.1 - 1	7664-41-7
Diuron	<0.1	330-54-1
Carbendazim	<0.1	10605-21-7

United States: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

Canada: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with the amended HPR as of April 2018.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

**Description of necessary first aid measures** 

Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention if irritation occurs.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	<ul> <li>Flush contaminated skin with plenty of water. Continue to rinse for at least 20 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.</li> </ul>

### Section 4. First aid measures

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

Potential acute health effe	<u>cts</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sym	<u>ptoms</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate me	dical attention and special treatment needed. if necessary
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

<u>Extinguishing media</u>	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.

may

# Section 5. Fire-fighting measures

Specific hazards arising from the chemical	: This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: No specific data.
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Methods and materials for co	ontainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly
	closed when not in use. Empty containers retain product residue and can be hazardous.

# Section 7. Handling and storage

VM Water BasedAdhesive

	Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

### Control parameters

### United States

### **Occupational exposure limits**

Ingredient name	Exposure limits
Alkanes, C14-C16, Chloro Toluene	None. OSHA PEL Z2 (United States, 2/2013). TWA: 200 ppm 8 hours. CEIL: 300 ppm AMP: 500 ppm 10 minutes. NIOSH REL (United States, 10/2016). TWA: 100 ppm 10 hours. TWA: 375 mg/m <sup>3</sup> 10 hours. STEL: 150 ppm 15 minutes. STEL: 560 mg/m <sup>3</sup> 15 minutes. ACGIH TLV (United States, 3/2019). TWA: 20 ppm 8 hours.
Ammonia Ammonia, anhydrous	None. ACGIH TLV (United States, 3/2019). TWA: 25 ppm 8 hours. TWA: 17 mg/m <sup>3</sup> 8 hours. STEL: 35 ppm 15 minutes. STEL: 24 mg/m <sup>3</sup> 15 minutes. NIOSH REL (United States, 10/2016). TWA: 25 ppm 10 hours. TWA: 18 mg/m <sup>3</sup> 10 hours. STEL: 35 ppm 15 minutes. STEL: 27 mg/m <sup>3</sup> 15 minutes. OSHA PEL (United States, 5/2018). TWA: 50 ppm 8 hours. TWA: 35 mg/m <sup>3</sup> 8 hours.
Diuron Carbendazim	ACGIH TLV (United States, 3/2019). TWA: 10 mg/m <sup>3</sup> 8 hours. NIOSH REL (United States, 10/2016). TWA: 10 mg/m <sup>3</sup> 10 hours. None.

### <u>Canada</u>

**Occupational exposure limits** 

VM Water BasedAdhesive

# Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
Toluene	CA Alberta Provincial (Canada, 6/2018). Absorbed through skin. 8 hrs OEL: 50 ppm 8 hours. 8 hrs OEL: 188 mg/m <sup>3</sup> 8 hours. CA British Columbia Provincial (Canada, 5/2019). TWA: 20 ppm 8 hours. CA Ontario Provincial (Canada, 1/2018). TWA: 20 ppm 8 hours. CA Quebec Provincial (Canada, 1/2014). Absorbed through skin. TWAEV: 50 ppm 8 hours. TWAEV: 188 mg/m <sup>3</sup> 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). Absorbed through skin. STEL: 60 ppm 15 minutes. TWA: 50 ppm 8 hours.
Ammonia, anhydrous	CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 17 mg/m <sup>3</sup> 8 hours. 8 hrs OEL: 25 ppm 8 hours. 15 min OEL: 35 ppm 15 minutes. 15 min OEL: 24 mg/m <sup>3</sup> 15 minutes. CA British Columbia Provincial (Canada, 5/2019). TWA: 25 ppm 8 hours. STEL: 35 ppm 15 minutes. CA Ontario Provincial (Canada, 1/2018). TWA: 25 ppm 8 hours. STEL: 35 ppm 15 minutes. CA Quebec Provincial (Canada, 1/2014). TWAEV: 25 ppm 8 hours. STEV: 35 ppm 15 minutes. STEV: 35 ppm 15 minutes. STEV: 35 ppm 15 minutes. STEV: 35 ppm 15 minutes. STEV: 24 mg/m <sup>3</sup> 15 minutes. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 35 ppm 15 minutes. TWA: 25 ppm 8 hours.
Diuron	CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 10 mg/m <sup>3</sup> 8 hours. CA British Columbia Provincial (Canada, 5/2019). TWA: 10 mg/m <sup>3</sup> 8 hours. CA Ontario Provincial (Canada, 1/2018). TWA: 10 mg/m <sup>3</sup> 8 hours. CA Quebec Provincial (Canada, 1/2014). TWAEV: 10 mg/m <sup>3</sup> 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 20 mg/m <sup>3</sup> 15 minutes. TWA: 10 mg/m <sup>3</sup> 8 hours.

# Section 8. Exposure controls/personal protection

Appearance	
Section 9. Physic	al and chemical properties
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Skin protection Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Individual protection meas	<u>ures</u>
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.
Appropriate engineering controls	: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
-	· · ·

Physical state	: Liquid.
Color	: Orange/Pink.
Odor	: Not available.
Odor threshold	: Not available.
рН	: 7 to 10 [Conc. (% w/w): 1%]
Melting/freezing point	: Not available.
Initial boiling point and boiling range	: 100°C (212°F)
Flash point	: Not available.
Evaporation rate	: Not available.
Flammability (solid, gas)	: Notavailable.

# Section 9. Physical and chemical properties

: Not available.
: Not available.
: Not available.
: 0.99
: Not available.
: Notavailable.
: Not available.
: Not available.
: 5 g/l

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

### Information on toxicological effects

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Toluene	LC50 Inhalation Vapor	Rat	49 g/m <sup>3</sup>	4 hours
Ammonia	LD50 Oral	Rat	350 mg/kg	-
Ammonia, anhydrous	LC50 Inhalation Gas.	Rat	9500 ppm	1 hours
	LC50 Inhalation Gas.	Rat	2000 ppm	4 hours
Diuron	LD50 Dermal	Rat	>5 g/kg	-
	LD50 Oral	Rat	1 g/kg	-
Carbendazim	LD50 Dermal	Rabbit	8500 mg/kg	-
	LD50 Dermal	Rat	2 g/kg	-
	LD50 Oral	Rat	>5050 mg/kg	-

Irritation/Corrosion

#### VM Water BasedAdhesive

# Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes 100 mg	-
	Eyes - Mild irritant	Rabbit	-	870 µg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2	-
	Skin - Mild irritant	Pig	_	mg 24 hours 250	_
				μL	
	Skin - Mild irritant	Rabbit	-	435 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
				mg	
	Skin - Moderate irritant	Rabbit	-	500 mg	-
Ammonia	Eyes - Severe irritant	Rabbit	-	250 ug	-
	Eyes - Severe irritant	Rabbit	-	0.5 minutes 1	-
				mg	

### **Sensitization**

There is no data available.

### **Mutagenicity**

There is no data available.

### **Carcinogenicity**

### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Toluene	-	3	-

### Reproductive toxicity

There is no data available.

#### **Teratogenicity**

There is no data available.

#### Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
Toluene Ammonia	Category 3 Category 3	-	Narcotic effects Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Toluene	Category 2	-	hearing organs
Diuron	Category 2	-	-

#### **Aspiration hazard**

Name	Result
Toluene	ASPIRATION HAZARD - Category 1

Information of	on the likely	
routes of exp	osure	

: Routes of entry anticipated: Oral, Dermal, Inhalation.

# Section 11. Toxicological information

Potential acute health	effects
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the	ne physical. chemical and toxicological characteristics
Eye contact	: No known significant effects or critical hazards.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths

	skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effe	Delayed and immediate effects and also chronic effects from short and long term exposure				
<u>Short term exposure</u>					
Potential immediate effects	: No known significant effects or critical hazards.				
Potential delayed effects	: No known significant effects or critical hazards.				
Long term exposure					
Potential immediate effects	: No known significant effects or critical hazards.				
Potential delayed effects	: No known significant effects or critical hazards.				
Potential chronic health eff	ects				
General	: No known significant effects or critical hazards.				
Carcinogenicity	: No known significant effects or critical hazards.				
Mutagenicity	: No known significant effects or critical hazards.				
Reproductive toxicity	: Suspected of damaging the unborn child.				

### Numerical measures of toxicity

### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	(vapors)	Inhalation (dusts and mists) (mg/ I)
Toluene	N/A	N/A	N/A	49	N/A
Ammonia	350	N/A	N/A	N/A	N/A
Ammonia, anhydrous	N/A	N/A	2000	N/A	N/A
Diuron	1000	N/A	N/A	N/A	N/A
Carbendazim	N/A	2000	N/A	N/A	N/A

# Section 12. Ecological information

### Toxicity

Product/ingredient name	Result	Species	Exposure
Toluene	Acute EC50 11600 µg/L Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6000 µg/L Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Chronic NOEC 2 mg/L Fresh water	Daphnia - Daphnia magna	21 days
Ammonia	Acute LC50 37 ppm Fresh water	Fish - Gambusia affinis - Adult	96 hours
Ammonia, anhydrous	Acute EC50 29.2 mg/L Marine water	Algae - Ulva fasciata - Zoea	96 hours
	Acute LC50 2080 µg/L Fresh water	Crustaceans - Gammarus pulex	48 hours
	Acute LC50 0.53 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 300 µg/L Fresh water	Fish - Hypophthalmichthys nobilis	96 hours
	Chronic NOEC 0.204 mg/L Marine water	Fish - Dicentrarchus labrax	62 days
Diuron	Acute EC50 2.26 µg/L Marine water	Algae - Coccolithus huxleyi - Exponential growth phase	72 hours
	Acute EC50 0.0007 mg/L Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 0.005 mg/L Fresh water	Aquatic plants - Lemna sp.	96 hours
	Acute EC50 8.4 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute IC50 2.41 µg/L Marine water	Aquatic plants - Halodule uninervis	72 hours
	Acute LC50 380 µg/L Fresh water	Crustaceans - Gammarus Iacustris	48 hours
	Acute LC50 500 µg/L Fresh water	Fish - Morone saxatilis - Larvae	96 hours
	Chronic EC10 0.11 µg/L Fresh water	Algae - Fragilaria capucina - Exponential growth phase	96 hours
	Chronic NOEC 0.34 µg/L Marine water	Aquatic plants - Zostera muelleri	72 hours
	Chronic NOEC 26.4 ppb	Fish - Pimephales promelas	60 days
Carbendazim	Acute EC50 19.0562 mg/L Fresh water	Algae - Scenedesmus acutus var. acutus	96 hours
	Acute EC50 20 µg/L Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 77 µg/L Fresh water	Crustaceans - Gammarus pulex - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 7 µg/L Fresh water	Fish - Ictalurus punctatus - Yolk- sac fry	96 hours
	Chronic EC10 10 µg/L Fresh water	Crustaceans - Gammarus pulex - Adult	21 days
	Chronic NOEC 3.1 ppb Fresh water	Daphnia - Daphnia magna	21 days

### Persistence and degradability

There is no data available.

### **Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Toluene	2.73	90	low
Diuron	2.84	5.2	low
Carbendazim	1.52	2.51	low

# **Section 12. Ecological information**

### Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

### **Other adverse effects** : No known significant effects or critical hazards.

### **Section 13. Disposal considerations**

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and
	sewers.

### Section 14. Transport information

	<b>DOT Classification</b>	<b>TDG Classification</b>	IMDG	ΙΑΤΑ
UN number	UN3082	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Alkanes, C14-C16, Chloro)			
Transport hazard class(es)	9	9	9	9
Packing group	Ш	Ш	111	Ш
Environmental hazards	Yes.	Yes.	Yes.	Yes.

**AERG :** 171

### Additional information

**DOT Classification** 

: Non-bulk packages of this product are not regulated as hazardous materials in package sizes less than the product reportable quantity, unless transported by inland waterway. The marine pollutant mark is not required when transported on inland waterways in sizes of ≤5 L or ≤5 kg.

**<u>Reportable quantity</u>** 34722.2 lbs / 15763.9 kg [502.34 gal / 1901.6 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

# **TDG Classification**: Product classified as per the following sections of the Transportation of Dangerous<br/>Goods Regulations: 2.43-2.45 (Class 9), 2.7 (Marine pollutant mark).<br/>Non-bulk packages of this product are not regulated as dangerous goods when<br/>transported by road or rail.

# Section 14. Transport information

-	
IMDG	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
Special precautions for user	: <b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
Transport in bulk according to IMO instruments	: Not available.

# Section 15. Regulatory information

U.S. Federal regulations	: TSCA 8(a) PAIR: Naphthalene; Acetaldehyde; Diuron		
	TSCA 8(a) CDR Exempt/Partial exemption: Not determined		
	Clean Water Act (CWA) 307: Toluene; Zinc oxide; Naphthalene		
	<b>Clean Water Act (CWA) 311</b> : Toluene; Ammonia, anhydrous; Naphthalene; Quinoline; Formaldehyde; Ammonia; Maleic Anhydride; Acetaldehyde; Diuron		
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Listed		
Clean Air Act Section 602 Class I Substances	: Notlisted		
Clean Air Act Section 602 Class II Substances	: Notlisted		
DEA List I Chemicals (Precursor Chemicals)	: Notlisted		
DEA List II Chemicals (Essential Chemicals)	: Notlisted		
SARA 302/304			

**Composition/information on ingredients** 

			SARA 3	02 TPQ	SARA 3	04 RQ
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
Ammonia, anhydrous	≤0.3	Yes.	500	-	100	-
Formaldehyde	≤0.0025	Yes.	500	73.9	100	14.8
Ethylene oxide	≤0.001	Yes.	1000	-	10	-

SARA 304 RQ

: 52045.4 lbs / 23628.6 kg [753 gal / 2850.3 L]

### SARA 311/312

Classification : TOXIC TO REPRODUCTION (Unborn child) - Category 2

**Composition/information on ingredients** 

# Section 15. Regulatory information

Name	%	Classification
Toluene	≥0.3 - <1	FLAMMABLE LIQUIDS - Category 2 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A TOXIC TO REPRODUCTION (Unborn child) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 ASPIRATION HAZARD - Category 1

### **State regulations**

Massachusetts	: None of the components are listed.
New York	: None of the components are listed.
New Jersey	: None of the components are listed.

- None of the components are listed.
- **Pennsylvania**
- : None of the components are listed.

### California Prop. 65

MARNING: This product can expose you to chemicals including Anionic / Nonionic, Ethylene oxide and 4-Methylpentan-2-one, which are known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Diuron, Naphthalene, Quinoline and its strong acid salts, Formaldehyde, Acetaldehyde and 1,4-Dioxane, which are known to the State of California to cause cancer, and Toluene, Methanol and Ethanediol, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Toluene	-	Yes.
Diuron	-	-
Methanol	-	Yes.
Naphthalene	Yes.	-
Anionic / Nonionic	-	-
Quinoline and its strong acid salts	-	-
Formaldehyde	Yes.	-
Ethanediol	-	Yes.
Acetaldehyde	Yes.	-
Ethylene oxide	Yes.	Yes.
1,4-Dioxane	Yes.	-
4-Methylpentan-2-one	-	-

### **Canadian lists**

Canadian NPRI

: None of the components are listed.

### **CEPA Toxic substances**

: None of the components are listed.

### International regulations

Chemical Weapon Convention List Schedules I. II & III Chemicals Not listed.

### Montreal Protocol

Not listed.

### Stockholm Convention on Persistent Organic Pollutants

# Section 15. Regulatory information

Not listed.

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

Inventory list	
Australia	: Not determined.
Canada	: All components are listed or exempted.
China	: Not determined.
Europe	: Not determined.
Japan	: Japan inventory (ENCS): Notdetermined. Japan inventory (ISHL): Not determined.
New Zealand	: Not determined.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: Not determined.
Thailand	: Not determined.
Turkey	: Not determined.
United States (TSCA 8b)	: All components are active or exempted.
Viet Nam	: Not determined.

### Section 16. Other information

### Procedure used to derive the classification

Classification	Justification
TOXIC TO REPRODUCTION (Unborn child) - Category 2	Calculation method
AQUATIC HAZARD (ACUTE) - Category 2	Calculation method
AQUATIC HAZARD (LONG-TERM) - Category 2	Calculation method

<u>History</u>		
Data of		

Date of issue/Date of revision	: 10/15/2020
Date of previous issue	: Not applicable
Version	: 1
Prepared by	: KMK Regulatory Services Inc.
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

### Section 16. Other information

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.