



Hydrotech® VM Masticseal

formerly known as VM Masticseal

GENERAL DESCRIPTION

VM Masticseal is a rubberized asphalt mastic sealant.

BASIC USE

VM Masticseal is used to seal all termination edges, cut edges and seam "T" joints of Hydrotech's VM 60 sheet waterproofing membrane.

APPLICATION

- A 1/2 - 1 inch wide bead of Masticseal should be applied at all VM 60 sheet membrane edges that required cutting (flashings, adjacent field sheets), all horizontal sheet termination edges (top and bottom of wall/footing) and along all seam edges (horizontal and vertical) that occur at the junction of the wall and footing.
- VM Masticseal should be applied to all sheet terminations at the end of each days work.

CONTAINER/WEIGHT

VM Masticseal is available in 5 gallon pails, weighing 48 pounds, and a case of 12 - 30 ounce tubes, weighing 27 pounds per case. The pails will cover approximately 100 feet per gallon with a 1 inch bead. Each tube will cover approximately 65 feet with a 1/2 inch bead.

LEED® INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	0	
Manufacture Location		Corsicana, TX
Extraction/Harvesting Location		

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.