
METALACCESSORIES

N-66 Narrow Wing Casing Bead is primarily a West Coast product with a profile similar to the X-66, but without the expanded flange. Nail and keying holes are provided in the flange, which is approximately 1-3/8" wide. Weep holes are optional.

Ground	Length	Pieces/ carton	Finish	Weight/ carton	Cartons/ pallet	Pallet weight
3/8"	10'	30	Galvanized Zinc*	37 lbs. 35 lbs.	30	1110 lbs. 1050 lbs.
1/2"	10'	30	Galvanized	39 lbs.	30	1170 lbs.
3/4"	10'	30	Galvanized	44 lbs.	30	1320 lbs.
7/8"	10'	30	Galvanized	47 lbs.	30	1410 lbs.
1"	10'	30	Zinc*	45 lbs.	30	1350 lbs.



J-Metal Bead is used with one-coat stucco systems or thin veneer stone. Optional holes in ground are spaced at 6" centers.

Ground A	Length	Pieces/ bundle	Nailing flange height B	Weight/ bundle	Bundles/ pallet
3/8"	10'	10	3 1/2"	26 lbs.	50
1/2"	10'	10	3 1/2"	28 lbs.	50
3/4"	10'	10	3 1/2"	29 lbs.	50
7/8"	10'	10	3 1/2"	30 lbs.	50
1 3/8"	10'	10	1 3/4" 3 1/2"	21 lbs. 35 lbs.	100 50
1 1/2"	10'	10	1 3/4" 3 1/2"	24 lbs. 36 lbs.	100 50



Foundation Weep Screed (FHA #7) is required at the base of walls as part of a drainage system for exterior stucco or veneer stone applications. The 3½" nailing flange serves as flashing when Grade D building paper or Tilath™ Starter Strip is installed over the flange. Holes are punched into the nailing flange for easy attachment to the wall. Holes are also placed on top of the "V" portion of the flange to provide keying of the stucco mud when wet.

Ground A	Pieces/ bundle	Nailing flange width	Finish	Weight/ bundle	Bundles/ pallet
1/2"	10	3 1/2"	Galvanized Zinc*	32 lbs. 28 lbs.	100
5/8"	10	3 1/2"	Galvanized Zinc*	34 lbs. 30 lbs.	100
7/8"	10	3 1/2"	Galvanized Zinc* Stainless*	36 lbs. 32 lbs. 36 lbs.	100 100 100
1 3/8"	10	3 1/2"	Galvanized Zinc*	41 lbs. 37 lbs.	100
1 1/2"	10	3 1/2"	Galvanized Zinc*	43 lbs. 39 lbs.	100

