# HYDRODRY MID-WALL WEEP SCREED

#### FOR STUCCO AND PLASTER INSTALLATIONS

AMIFLOW Mid-Wall Drain Screed has integrated drain slots to allow water and excess moisture to escape from the back of a stucco mem-brane. This screed also performs as an expansion (control) joint with multiple grounds. It is typically installed where a framed stucco surface meets a masonry (concrete block) stucco surface. This condition is common between floors on 2-story homes and at the base of a gable receiving stucco.

The flange features pre-punch attachment holes every 4" for easy installation. The 3-1/2 nailing flange also offers plenty surface area to tie the trim into the weather plane of the wall. The weather barrier, drain screen and lath should be installed over the solid upper flange to direct water to the foundation weep screed. The profile is manufactured with a  $3\frac{1}{2}$ " nailing flange as required by code.

All butt joints, intersections, and ends should be joined, embedded and sealed in a quality sealant compatible with exterior paint finish.

Product Submittal	Product Number	Color
	HDAMDWV35078010	White
	HDAMDWV35078010G	Gray
	HDAMDWV35078010T	Tan
Manufactured with a 3½" Nailing Flange as Required by IBC 2510, 2511		
Grounds Top: 7/8", Bottom: 1/2", 5/8", 7/8", 1		
1/4" Standard Length is 10-Feet		



SUBMITTAL DETAILS

04 73 00

#### FINISH

The finish on all AMICO vinyl stucco accessories is compatible with standard lathing and paint finishes.

### COLORS

Standard color is white. This profile can be specified and ordered with the exposed area in tan or gray.

gray

tan

#### REFERENCES

PVC complies with ASTM D4316 and ASTM D1784 Meets IBC 2510 and IBC 2511 Refer to ASTM C1063 for support spacing, lath selection, fastener selection and further information regarding the proper installation of metal lath and accessories. Meets Buy American Procurement Requirements Made in the United States of America LEED: 100% post industrial recyclable content

All information contained herein is accurate as known at the time of publication. Specifications may change and AMICO reserves the right to change product specifications without notice and without incurring obligations.

## ALABAMA METAL INDUSTRIES CORPORATION

3245 Fayette Avenue & Birmingham, AL 35208 & Telephone 800/366-2642 & Facsimile 205/786-6527

June 2024

