

Aluminum Grating

RECTANGULAR BAR SWAGE-LOCKED

1-3/16" Center to Center of Bearing Bars



19-SR-4
Cross Rods 4" C/C



19-SR-2
Cross Rods 2" C/C

PRESS-LOCKED

1-3/16" Center to Center of Bearing Bars



19-AP-4
Cross Bars 4" C/C



19-AP-2
Cross Bars 2" C/C

LOAD & DEFLECTION TABLE

U = safe uniform load, psf

C = safe concentrated load, pfw

D = deflection, inches

E = modulus of elasticity, 10,000,000 psi

F = fiber stress, 12,000 psi

Material: ASTM B-221, 6063 or 6061

Deflection: Spans and loads to the right of the bold line exceed 1/4" deflection for uniform load of 100 psf which provides safe pedestrian comfort. These can be exceeded for other types of loads with engineer's approval.

Serrated Bars: For serrated grating, the depth of grating required for a specified load is 1/4" deeper than that shown in the table.

General: Loads and deflections are theoretical and based on static loading.

Finish: Mill finish unless otherwise specified

SB/AP-19 PANEL WIDTH (inches)

Note: Includes 1/4" (1/8" each side) for extended cross rods on swage-locked (SR) and extended cross bars on press-locked (AP).

S.R./A.P. FRAME WIDTH (inches)															locked (SR) and extended cross bars on press-locked (AP).						
No. of Bars	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16						
1/8" Bar	19 ⁹ / ₁₆	23 ⁴ / ₈	31 ⁵ / ₁₆	51 ¹ / ₈	65 ¹ / ₁₆	71 ¹ / ₂	81 ¹ / ₁₆	97 ⁸ / ₁₆	111 ¹ / ₁₆	121 ¹ / ₄	137 ¹ / ₁₆	145 ⁸ / ₁₆	151 ⁹ / ₁₆	17	183 ¹ / ₁₆						
3/16" Bar	15 ⁵ / ₈	21 ³ / ₁₆	4	53 ¹ / ₁₆	63 ¹ / ₈	79 ¹ / ₁₆	83 ³ / ₄	91 ⁵ / ₁₆	111 ¹ / ₈	125 ¹ / ₁₆	131 ¹ / ₂	141 ¹ / ₁₆	157 ⁸ / ₁₆	171 ¹ / ₁₆	181 ¹ / ₄						
No. of Bars	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31						
1/8" Bar	193 ¹ / ₈	209 ⁹ / ₁₆	213 ¹ / ₄	221 ⁵ / ₁₆	241 ¹ / ₈	255 ¹ / ₁₆	261 ¹ / ₂	271 ¹¹ / ₁₆	287 ⁸ / ₁₆	301 ¹ / ₁₆	311 ¹ / ₄	327 ¹ / ₁₆	335 ⁹ / ₁₆	341 ¹³ / ₁₆	36						
3/16" Bar	197 ¹ / ₁₆	205 ⁸ / ₁₆	211 ³ / ₁₆	23	243 ¹ / ₁₆	253 ¹ / ₈	269 ¹ / ₁₆	273 ³ / ₄	281 ¹⁵ / ₁₆	301 ¹ / ₈	315 ¹ / ₁₆	321 ² / ₁	331 ¹¹ / ₁₆	347 ⁸ / ₁₆	361 ¹ / ₁₆						