VINYL MID WALL WEEP SCREED

FOR STUCCO AND PLASTER INSTALLATIONS

AMICO Vinyl Mid Wall Weep Screed performs as an unpunched weep screed allowing excess moisture to escape the back of a stucco membrane. This screed also performs as an expansion (control) joint with twin grounds. It is installed where a framed stucco surface meets a masonry (concrete block) surface. This condition is common between floors on 2-story homes and at the base of a gable receiving stucco. The unpunched flange above must be installed extending at least one inch below the framing/concrete joint. The weather barrier and lath should be installed over the solid upper flange to direct water to the foundation weep screed.

Product Submittal	Product Number	Ground Description
	AMMWS-780-500	1/2"
	AMMWS-780-580	5/8"
Manufactured with a 3½" Nailing Flange as Required by IBC 2510, 2511		
Standard Length is 10-Feet		

FINISH


The finish on all AMICO vinyl stucco accessories is compatible with standard lathing and paint finishes.


COLORS

Standard color is white. This profile can be specifed and ordered with the exposed area in tan, brown or gray.



All butt joints, intersections, and ends should be joined, embedded and sealed in a quality sealant compatible with exterior paint finish.





CAD Detail Name: Vinyl Mid Wall Weep Screed Click Link to go to Print Details

The unpunched fl ange above must be installed extending at least 1-inch below the framing / concrete joint. The weather barrier and lath should be installed over he solid upper flange to direct moisture to the foundation weep screed.

REFERENCES

PVC complies with ASTM D4216 and ASTM D1784 Meets IBC 2510 and IBC 2511

Refer to ASTM C1063 for support spacing, lath selection, fastener selection and further information regarding the proper installation of metal lath and accessories.

Meets Buy American Procurement Requirements Made in the United States of America

LEED: 100% post industrial recyclable content

All information contained herein is accurate as known at the time of publication. SpecificationsmaychangeandAMICOreserves the right to change product specificationswithoutnoticeandwithoutincurringobligations.

ALABAMA METAL INDUSTRIES CORPORATION

3245 Fayette Avenue ♦ Birmingham, AL 35208 ♦ Telephone 800/366-2642 ♦ Facsimile 205/786-6527

