



COMPLIANCE: Exceeds performance requirements of ASTM D41. MIAMI-DADE APPROVED. ASBESTOS FREE.

DESCRIPTION: APOC® 103 Premium Asphalt Primer is a professional grade primer formulated with a high penetrating solvent and select asphalt. It is designed to promote superior adhesion of roofing materials. APOC® 103 can be used to prime newly laid concrete or cement decks, gypsum, masonry thermal insulation and weathered roofing prior to applying built-up roofing. APOC® 103 can also be applied to weathered roofing prior to application of black or reflective coatings. Allow primer to cure 30 days prior to application of reflective coatings.

PREPARATION: All surfaces must have proper drainage and be clean, dry and free of surface rust and any other foreign matter. Repair all problem areas with an approved APOC® Cement. MIX THOROUGHLY. DO NOT HEAT OR THIN. DO NOT APPLY IF RAIN IS EXPECTED WITHIN 24 HOURS.

FOR BEST RESULTS: Apply on clear sunny day when surface temperatures are between 35 °F and 120 °F. In colder weather product should be stored in heated room (65 °F to 80 °F) at least 24 hours prior to application.

APPLICATION: For exterior use only. Protective clothing, gloves, and eyewear should be used during application of these products. Apply with professional airless sprayer, brush or roller.

APPLICATION RATE: 0.25 - 1 gallon per 100 sq. ft. depending on porosity of surface and method of application. Work material to a smooth and even consistency. Avoid excessive build up or puddles of primer. DO NOT APPLY TO ASPHALT DRIVEWAYS.

SPRAY INFO: 100 - 500 PSI, .019 - .031 Tip Size, 0.5 - 2.0 GPM

STORAGE & HANDLING PRECAUTIONS: When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 110 °F. This manufacturer also disclaims liability for flat surface application where poor drainage or moisture may prevail. Do not reuse empty containers. Do not use in drinking water or food systems.

CLEAN-UP: Clean tools with paint thinner or mineral spirits.

©2010 Gardner-Gibson, Inc.
Manufactured by / Fabricado por: Gardner-Gibson, Inc.P.O.
Box 5449, Tampa, FL 33675

See SDS for more info

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS:

Weight Per Gallon	7.4-7.9 lbs.
Residue by Evaporation, %	60 min.
Consistency	Brush or Spray
Tack Time (50% Relative Humidity, 70 °F)	30 minutes
Full Cure (50% Relative Humidity, 70 °F)	24-48 hours
Application Temperatures	35° - 120°F
Clean-up Tools	Paint Thinner, Mineral Spirits

Approx. Shipping Weights: (Note: All approx. weights include container)

1 gallon (3.4 L)	8 lbs.
5 gallons (18.9L)	40 lbs.
55 drums (208.2L)	460 lbs.

VOC: 350 g/L (regulatory)

HANDLING PRECAUTIONS: Product safety information required for safe use is not included. Before handling, read product safety data sheets and container labels for safe use and for physical and health hazard information. Safety data sheets are available on the APOC website at www.apoc.com. You can also obtain a copy from your local APOC Distributor or APOC sales representative.

LIMITED WARRANTY AND DISCLAIMER: To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance and is subject to change without prior notice. User must contact APOC to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. Liability, if any, is limited to replacement of product unless installed by an approved contractor in accordance with APOC warranty procedures and program.

For limited warranty and disclaimer information, visit our website at:
www.apoc.com/productwarrantyinfo.