



DESCRIPTION: APOC® 11 White Top No. 11 Ceramic Roofing Granules are composed of a high quality mineral rock and are the same granules used on BUR, SBS and APP mineral-surfaced sheets. APOC® 11 uses only premium grade pigments and a high tech ceramic coating process to permanently protect and coat the granules. APOC® granules provide a durable layer of protection over asphaltic and polymeric materials preventing UV deterioration and premature aging. They are also used to add toughness and durability to a variety of coating when used in walkway systems or other substrates which receive a lot of wear.

FOR BEST RESULTS: APOC® 11 should be used wherever hot mopping asphalt or cold process adhesive extends onto the finished roof surface. APOC® 11 should be applied while asphalt is hot or cold process adhesive is still “wet,” and should be pressed into the asphalt surface to insure proper adhesion.

HANDLING PRECAUTIONS: Product safety information required for safe use is not included. Before handling, read product safety data sheets and container labels for safe use and for physical and health hazard information. Safety Data Sheets are available on the APOC website at www.apoc.com. You can also obtain a copy from your local APOC Distributor or APOC sales representative.

LIMITED WARRANTY AND DISCLAIMER: To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance and is subject to change without prior notice. User must contact APOC to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. Liability, if any, is limited to replacement of product unless installed by an approved contractor in accordance with APOC warranty procedures and program.

For limited warranty and disclaimer information, visit our website at: www.apoc.com/productwarrantyinfo.

©2010 Gardner-Gibson, Inc.
Manufactured by / Fabricado por:
Gardner-Gibson, Inc.
P.O. Box 5449, Tampa, FL 33675

See SDS for more info

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS:

Dust	0.2% Maximum <100 Mesh US Sieve (150 µm)
Moisture Content	0.3% Maximum
Hardness	6.0 - 7.0 Moh's Mineral Scale
Specific Gravity	2.55 - 2.70

Approx. Shipping Weights: (Note: All approx. weights include container)

5 gallons	53 lbs.
-----------	---------

