



TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS:

Dust	0.2% Maximum <100 Mesh US Sieve (150 µm)
Moisture Content	0.3% Maximum
Hardness	6.0 - 7.0 Moh's Mineral Scale
Specific Gravity	2.55 - 2.70

Approx. Shipping Weights:

(Note: All approx. weights include container)

5 gallons	53 lb.
-----------	--------

DESCRIPTION:

APOC® 11 White Top No. 11 Ceramic Roofing Granules are composed of a high quality mineral rock and are the same granules used on BUR, SBS and APP mineral-surfaced sheets. APOC® 11 uses only premium grade pigments and a high tech ceramic coating process to permanently protect and coat the granules. APOC® granules provide a durable layer of protection over asphaltic and polymeric materials preventing UV deterioration and premature aging. They are also used to add toughness and durability to a variety of coating when used in walkway systems or other substrates which receive a lot of wear.

PREPARATION:

Completely read all application instructions and check weather conditions prior to starting any work. Apply to roofs in structurally sound condition.

FOR BEST RESULTS:

APOC® 11 should be used wherever hot mopping asphalt or cold process adhesive extends onto the finished roof surface. APOC® 11 should be applied while asphalt is hot or cold process adhesive is still "wet," and should be pressed into the asphalt surface to insure proper adhesion.

COVERAGE RATE:

Approximately 40-60 lbs. per sq.

CLEAN-UP:

Paint thinner or mineral spirits.

STORAGE & HANDLING PRECAUTIONS:

All containers should be stored upright on a clean, flat surface. When transporting this product, ensure that the lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure on top of 6 mil plastic sheeting to prevent damage due to accidental spills or loosening of lids.

WARRANTY & DISCLAIMER:

Register your warranty for extended warranty terms within 60 days of the completion of the project at www.apoc.com/pages/warranty. APOC Roofing Systems, LLC hereby warrants to the original purchaser, contingent upon original proof of purchase, that this product will be free from any defects that may materially and adversely affect the product's performance for a period of one year from the date of original purchase.