



## ALL-PRO SBS RUBBERIZED FLASHING CEMENT Data Sheet

**COMPLIANCE:** Exceeds performance requirements ASTM D3409, ASTM D4586, TYPE I. MIAMI-DADE APPROVED. ASBESTOS FREE.

**DESCRIPTION:** APOC® 128 All-Pro SBS Rubberized Flashing Cement is a professional grade roof cement that provides superior adhesion to vertical surfaces. It will not run or sag. APOC® 128 is manufactured with select asphalt, solvent and extra long fibers to provide a durable patching compound. APOC® 128 is excellent for setting and repairing flashing, gutters, sills, lintels, copings, chimneys, skylights, seams, expansion joints and all types of roofing and siding repairs. APOC® 128 is also an excellent utility mastic for use below grade in heavy duty foundation water-proofing and damp-proofing.

**PREPARATION:** All surfaces must be clean, have proper drainage and be free of surface rust and any other foreign matter. DO NOT HEAT OR THIN.

**FOR BEST RESULTS:** Apply when surface temperatures are between 50° and 120°F. In colder weather product should be stored in heated room (65° to 80° F.) at least 24 hours prior to application. Product formulated to be used year round. After a minimum of 45 days cure time, apply a reflective coating. This will greatly extend the life of the roof.

**APPLICATION:** For exterior use only. Protective clothing and eyewear should be used during application of this product. Apply with a trowel or putty knife. Work material to an even consistency over and into the area to be repaired. Apply 1/8" to 1/4" thick, two to three inches beyond the problem area. For cracks or holes 1/4" to 3/4" wide, press a strip of APOC® Glass Fabric into the cement and cover with an additional layer of roof cement. Form a cant with the cement around chimneys and other roof projections. Coverage rate is approximately 12 1/2 sq. ft. when applied 1/8" thick.

**PRECAUTIONS:** When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 110° F. This manufacturer also disclaims liability for flat surface application where poor drainage or moisture may prevail. For exterior use only. Do not reuse empty containers. Do not use in drinking water or food systems.

**CLEAN-UP:** Clean tools with paint thinner or mineral spirits.

### TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight Per Gallon	8.5 lbs.
Residue by Evaporation	70 min.
Consistency	Trowel
Cure Time (50% Relative Humidity, 70°F)	4-8 hours
Full Cure (50% Relative Humidity, 70°F)	24-48 hours
Application Temperatures	35° - 120°F
Clean-up Tools	Paint Thinner, Mineral Spirits

**Approx. Shipping Weights:** (Note: All approx. weights include container.)

1 gallon (3.8L)	9 lbs.
(6) 1 gallon containers/case	54 lbs.
3 gallons (11.3L)	28 lbs.
5 gallons (18.9L)	45 lbs.

### CAUTION – COMBUSTIBLE MIXTURE CAUTION!: HARMFUL OR FATAL IF SWALLOWED. EYE, SKIN AND RESPIRATORY IRRITANT.

Contains Petroleum Distillate. Keep away from heat, sparks and open flame. If swallowed DO NOT induce vomiting. Call physician immediately. In case of : Eye contact - flush with large amounts of room temperature water for 15 minutes; Skin contact - wash thoroughly with soap and water; Irregular or stopped breathing - administer oxygen, give artificial respiration and get medical attention immediately. Avoid prolonged breathing of vapor or spray mist.

**FOR EXTERIOR USE ONLY**  
**Use with adequate Ventilation**  
**Keep Out of Reach of Children**  
**VOC/VOS - 248 g/l max. (2.1 lbs./gal.)**

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

**WARRANTY AND DISCLAIMER:** To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance and is subject to change without prior notice. User must contact APOC to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. Liability, if any, is limited to replacement of product unless installed by an approved contractor in accordance with APOC warranty procedures and program.

For limited warranty and disclaimer information, visit our website at: [www.apoc.com/productwarrantyinfo](http://www.apoc.com/productwarrantyinfo).

©2010 Gardner Asphalt Corporation Manufactured by / Fabricado por: Gardner Asphalt Corporation P.O. Box 5449, Tampa, FL 33675



See MSDS for more info



Gardner Asphalt Corporation • P.O. Box 5449 • Tampa, Florida 33675-5449  
Phone: (813) 248-2101 • Fax (813) 248-6768 • [www.apoc.com](http://www.apoc.com)