



MIAMI-DADE COUNTY  
APPROVED

### TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS:

Weight Per Gallon	8.5 lb.
Residue by Evaporation	70 min.
Consistency	Trowel
Cure Time (50% Relative Humidity, 70 °F)	4 - 8 hours
Full Cure (50% Relative Humidity, 70 °F)	24 - 48 hours
Application Temperatures	35°F - 120°F

### Approx. Shipping Weights:

(Note: All approx. weights include container)

3 gallons (11.4L)	28 lb.
5 gallons (18.9L)	45 lb.

**VOC: 248 g/L max. (regulatory)**

### DESCRIPTION:


**APOC® 128 All-Pro SBS Modified Flashing Cement** is a professional grade roof cement that provides superior adhesion to vertical surfaces and is designed for winter temperatures. APOC® 128 is manufactured with select asphalt, solvent and extra long fibers to provide a durable patching compound. APOC® 128 is excellent for setting and repairing flashing, gutters, sills, lintels, copings, chimneys, skylights, seams, expansion joints and all types of roofing and siding repairs. APOC® 128 is also an excellent utility mastic for use below grade or in conjunction with foundation water-proofing and damp-proofing systems.

### PREPARATION:

All surfaces must be clean, have proper drainage and be free of surface rust, dust and any other foreign matter. **DO NOT HEAT OR THIN.**

### APPLICATION:

Apply when surface temperatures are between 50 °F and 120 °F. In colder weather product should be stored in heated room (65 °F to 80 °F.) at least 24 hours prior to application. Product formulated to be used year round. After a minimum of 45 days cure time, apply a reflective coating. this will greatly extend the life of the roof. For exterior use only. Protective clothing, gloves, and eyewear should be used during application of this product. Apply with a trowel or putty knife. Work material to an even consistency over and into the area to be repaired. Apply 1/8" to 1/4" thick, two to three inches beyond the problem area. For cracks or holes 1/4" to 3/4" wide, press a strip of APOC® Reinforcing Fabric into the cement and cover with an additional layer of roof cement. Form a cant with the cement around chimneys and other roof projections.



### COVERAGE RATE:

Approximately 12 ½ sq. ft. per gallon when applied 1/8" thick

### CLEAN-UP:

Paint thinner or mineral spirits

### STORAGE & HANDLING PRECAUTIONS:

When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 110°F. Do not reuse empty containers. do not use in drinking water or food systems. **DO NOT HEAT OR THIN. HARMFUL OR FATAL IF SWALLOWED. EYE, SKIN AND RESPIRATORY IRRITANT.** Contains petroleum based product. Keep away from heat, sparks and open flame. If swallowed **DO NOT** induce vomiting. Call physician immediately. In case of : Eye contact - flush with large amounts of room temperature water for 15 minutes; Skin contact - wash thoroughly with soap and water; Irregular or stopped breathing - administer oxygen, give artificial respiration and get medical attention immediately. Avoid prolonged breathing of vapor or spray mist.

### PERSONAL PROTECTIVE EQUIPMENT



EYEWEAR



PROTECTIVE  
CLOTHING



GLOVES

### WARRANTY & DISCLAIMER:

Register your warranty for extended warranty terms within 60 days of the completion of the project at [www.apoc.com/pages/warranty](http://www.apoc.com/pages/warranty). APOC Roofing Systems, LLC hereby warrants to the original purchaser, contingent upon original proof of purchase, that this product will be free from any defects that may materially and adversely affect the product's performance for a period of one year from the date of original purchase.