



Section 1 - Product and Company Identification

Material Name • Rubberized Asphalt Base Coat
Chemical Category • Mixture
Product Code • AP-1395
Product Description • Black, non-fibered liquid asphalt roof foundation coating.
Manufacturer • APOC
4161 E. 7th Avenue
Tampa, FL 33605

Telephone

Technical • 813-248-2101 - Customer Service: 8 AM - 5 PM M-F Eastern Standard Time
Emergency • 800-424-9300 - CHEMTREC
Emergency • 703-527-3887 - CHEMTREC (Outside US)

Section 2 - Hazards Identification

GHS HAZARDS AND PRECAUTIONS

SIGNAL WORD: WARNING!

Flammable liquid and vapor. Contains Combustible Petroleum Distillates. Harmful or Fatal if swallowed. Keep away from heat, sparks, and open flame. Avoid prolonged breathing of vapor and use only in adequate ventilation. Repeated and prolonged overexposure to solvent vapor may cause brain and nervous system damage, respiratory tract irritation, dizziness, or loss of consciousness. May cause skin and eye irritation.

Prevention Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking. Do not eat, drink or smoke when using this product. Do not handle until all safety precautions have been read and understood. Keep out of reach of children. Keep container tightly closed.

Response IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.



Physical Form • Liquid
Color • Black
Odor • Petroleum Hydrocarbon / Solvent odor.
Flash Point • 105°F(40.5°C) CC (Closed Cup)
UEL • 6 %
LEL • 0.9 %
OSHA(HCS2012) • Flammable Liquids - Category 3, Specific Target Organ Toxicity Repeated Exposure - Category 2,

- WHMIS** Skin Corrosion/Irritation - Category 3, Serious Eye Damage, Eye Irritation - Category 2B
- Combustible Liquids - B3, Other Toxic Effects - D2A
- GHS**
- Flammable Liquids - Category 3, Specific Target Organ Toxicity Repeated Exposure - Category 2, Skin Corrosion/Irritation - Category 3, Serious Eye Damage, Eye Irritation - Category 2B

Potential Health Effects

Inhalation:

- Acute (Immediate)**
- Excessive breathing of high vapor concentration can cause possible unconsciousness and even asphyxiation.
- Chronic (Delayed)**
- Refer to other information found in Section 11-Toxicology.

Skin:

- Acute (Immediate)**
- May cause irritation.
- Chronic (Delayed)**
- Repeated and prolonged exposure may be harmful. Repeated and prolonged exposure may cause dermatitis.

Eye:

- Acute (Immediate)**
- Causes eye irritation.
- Chronic (Delayed)**
- Repeated and prolonged exposure may cause irritation.

Ingestion:

- Acute (Immediate)**
- May be harmful or fatal if swallowed.
- Chronic (Delayed)**
- No data available.

- Carcinogenic Effects**
- This product or one of its ingredients present at 0.1% or more is listed as a carcinogen by NTP, IARC or OSHA. See Section 11 - Toxicological Information for more details. See Section 11 - Toxicological Information.

| Carcinogenic Effects | | | |
|-----------------------------|------------|------------------------------|---------------------|
| | CAS | IARC | NTP |
| Asphalt | 8052-42-4 | Group 2B-Possible Carcinogen | Under Consideration |

See Section 12 for Ecological Information.

Section 3 - Composition/Information on Ingredients

| Hazardous Components | | | | | |
|---|--|------------------|---|--|--|
| Chemical Name | Identifiers | %(weight) | LD50/LC50 | Classifications According to Regulation/Directive | |
| Asphalt | CAS:8052-42-4 UN:NA1999 EINECS:232-490-9 | 50% TO 70% | Ingestion/Oral-Rat LD50 • >5000 mg/kg Inhalation-Rat LC50 • >94.4 mg/m ³ | WHMIS: Other Toxic Effects - D2A UN GHS: Carc. 2; Eye Irrit. 2A; Skin Irrit. 2 | |
| Mineral Spirits | CAS:8052-41-3 EINECS:232-489-3 | 15% TO 25% | | EU DSD/DPD: Carc.Cat.2; R45 Muta.Cat.2; R46 Xn; R65 | |
| Solvent naphtha (petroleum), light aromatic | CAS:64742-95-6 EINECS:265-199-0 | 10% TO 20% | | UN GHS: Asp. Tox. 1; Carc. 1B EU DSD/DPD: Carc.Cat.2; R45Muta.Cat.2; R46Xn; R65 | |
| SBS Polymer | CAS:9003-55-8 | 5% TO 15% | | | |
| Benzene, 1,3,5-trimethyl | CAS:108-67-8 EINECS:203-604-4 | 1% TO 5% | | EU DSD/DPD: R10 Xi; R37 N; R51 R53 | |
| 1,2,4-Trimethylbenzene | CAS:95-63-6 EINECS:202-436-9 | 0.1% TO 0.5% | Ingestion/Oral-Rat LD50 • 5 g/kg Inhalation-Rat LC50 • 18000 mg/m ³ 4 Hour(s) | ANSI: WHMIS: Comb. Liq. - B3 | |

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

See Section 11 for Toxicological Information.

Section 4 - First Aid Measures

- Inhalation** • Remove to fresh air. Call a physician or poison control center. If breathing is difficult, give oxygen. If not breathing, give artificial respiration.
- Skin** • IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Remove contaminated clothing and shoes. Wash clothing before reuse.
- Eye** • Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first five minutes, then continue rinsing eye. If eye irritation persists: Get medical advice/attention.
- Ingestion** • Call a physician or poison control center immediately. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. Never give anything by mouth to an unconscious person.
- Antidotes** • No information, consult physician.
- Notes to Physician** • Aspiration of liquid into the lungs during swallowing or vomiting can cause lung inflammation, serious lung damage and even death from chemical pneumonitis.

See Section 2 for Potential Health Effects.

Section 5 - Fire Fighting Measures

- Extinguishing Media** • Use CO₂, dry chemical, or foam.
- Unsuitable Extinguishing Media** • Do not use halogenated extinguishing agents.
- Firefighting Procedures** • Fight advanced or massive fires from safe distance or protected location. Avoid water in a straight hose stream as the stream will cause splatter and spread fire. If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and can be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.
- Unusual Fire and Explosion Hazards** • Combustible liquid. May release irritating or toxic gases, fumes, or vapors. Vapors may travel to source of ignition and flash back. Containers may explode when heated.
- Hazardous Combustion Products** • Carbon monoxide, carbon dioxide, hydrocarbons.
- Protection of Firefighters** • Fire fighters should wear complete protective clothing including self-contained breathing apparatus.
- Flash Point** • 105°F(40.5°C) CC (Closed Cup)
- Explosion Limits** • •
- Upper** • 6 %
- Lower** • 0.9 %
- Autoignition Temperature** • 450°F(232°C)

Section 6 - Accidental Release Measures

- Personal Precautions** • Do not handle damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation to remove vapors, fumes, dust etc. Stay upwind.
- Emergency Procedures** • ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area) Isolate the area and contain the spilled material. Persons not wearing the appropriate PPE should be removed from the area until the spill is cleaned up. Ventilate closed spaces before entering.

- Environmental Precautions**
 - Prevent entry into waterways, sewers, basements or confined areas. Do NOT wash away into sewer.
- Containment/Clean-up Measures**
 - Contain and recover liquid when possible. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in suitable container. Do not flush to sewer or allow to enter waterways. Do not use water to flush spill area. Use appropriate Personal Protective Equipment (PPE).
- Prohibited Materials**
 - Avoid contact with strong oxidizing agents or bases.

Section 7 - Handling and Storage

- Handling**
 - KEEP OUT OF THE REACH OF CHILDREN! Keep away from heat, sparks, and flame – No Smoking. Keep containers tightly closed when not in use. Use only in well ventilated areas. Protect building inlets from fumes and vapors when working on roofs.
- Storage**
 - Store in a cool/low-temperature, well-ventilated dry place away from heat and ignition sources. Keep away from incompatible materials. Do not store and transport with oxidizers, acids, etc. Keep container tightly closed.
- Special Packaging Materials**
 - Not Applicable.
- Incompatible Materials or Ignition Sources**
 - Avoid contact with strong oxidizing agents.

Section 8 - Exposure Controls/Personal Protection

Personal Protective Equipment



- Respiratory**
 - When used with adequate ventilation, a respirator is not normally required. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge or supplied air respirator.
- Eye/Face**
 - Wear ANSI approved safety glasses with side shields or safety goggles.
- Hands**
 - Wear chemical protective gloves made of Nitrile or Neoprene.
- Skin/Body**
 - Wear clothing that covers the skin to prevent skin exposure.
- General Industrial Hygiene Considerations**
 - Avoid contact with skin, eyes or clothing. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco.
- Engineering Measures/Controls**
 - Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Use precaution to protect building intake from fumes and vapors created outdoors.
- Exposure Limits/Guidelines**
 - Refer to listed exposure limits in state information of this section.

| Exposure Limits/Guidelines | | | | | |
|-----------------------------|--------|---|--|-----------------------------|----------------------------|
| | Result | Canada Ontario | Mexico | OSHA | United States - California |
| Mineral spirits (8052-41-3) | TWAs | 525 mg/m3 TWA (140°C Flash aliphatic solvent) | 100 ppm TWA LMPE-PPT; 523 mg/m3 TWA LMPE-PPT | 500 ppm TWA; 2900 mg/m3 TWA | 100 ppm PEL; 525 mg/m3 PEL |
| Asphalt (8052-42-4) | TWAs | 0.5 mg/m3 TWA (fume, inhalable, as Benzene-soluble aerosol) | 5 mg/m3 TWA LMPE-PPT | Not established | 5 mg/m3 PEL (fume) |

Exposure Control Notations

ACGIH

- Asphalt (8052-42-4): **Carcinogens:** (A4 - Not Classifiable as a Human Carcinogen (fume, coal tar-free))

Section 9 - Physical and Chemical Properties

| Material Description | | | |
|----------------------|--------------------------------------|-----------------------------------|---------------------------------------|
| Physical Form | Liquid | Appearance/Description | Thick black semi-liquid. |
| Color | Black | Odor | Petroleum Hydrocarbon / Solvent odor. |
| General Properties | | | |
| Boiling Point | 315 to 550 F(157.2222 to 287.7778 C) | Melting Point | No data available |
| pH | No data available | Specific Gravity/Relative Density | 0.937 Water=1 |
| Density | ~7.8 lbs/gal | Water Solubility | No data available |
| Viscosity | See TDS | | |
| Volatility | | | |
| Vapor Pressure | 2 mmHg (torr) @ 68 F(20 C) | Vapor Density | 4.9 Air=1 |
| Evaporation Rate | 1 Ether = 1 | VOC (Vol.) | < 350 g/L |
| Flammability | | | |
| Flash Point | 105°F(40.55°C) CC (Closed Cup) | UEL | 6 % |
| LEL | 0.9 % | Autoignition | 450°F(232.2222 C) |

Section 10 - Stability and Reactivity

- Stability**
 - Stable under normal temperatures and pressures.
- Hazardous Polymerization**
 - Hazardous polymerization not indicated.
- Conditions to Avoid**
 - Avoid contact with strong oxidizing agents and flame.
- Incompatible Materials**
 - Strong oxidizers.
- Hazardous Decomposition Products**
 - Carbon monoxide, carbon dioxide and hydrocarbons.

Section 11 - Toxicological Information

| Component Name | CAS | Data |
|--|------------|---|
| Asphalt (50% TO 70%) | 8052-42-4 | Acute Toxicity: orl-rat LD50:>5000 mg/kg; ihl-rat LC50:>94.4 mg/m ³ ; Tumorigen/Carcinogen: skn-mus TDLo:905 gm/kg/2Y-I |
| Mineral spirits (15% TO 25%) | 8052-41-3 | Acute Toxicity: orl-rat LD :>5 gm/kg; ihl-rat LC50:>1400 ppm/8H; Irritation: eye-hmn 100 ppm MLD |
| Solvent naphtha (petroleum), light aromatic (10% TO 20%) | 64742-95-6 | Acute Toxicity: orl-qal LD50:>2150 mg/kg; orl-rat LD50:8400 mg/kg |
| Benzene, 1,3,5-trimethyl (1% TO 5%) | 108-67-8 | Acute Toxicity: orl-rat LD50:5000 mg/kg; ihl-rat TCLo:100 ppm/6H/20D-I; Irritation: skn-rbt 20 mg/24H MOD |

- Other Component Information**
- IARC has concluded that the following chemicals in this product are carcinogenic to humans(Group 1): silica, quartz. ACGIH has designated the following chemicals in this product as suspected human carcinogens (A2): silica, quartz. NTP has listed the following chemicals in this product as known human carcinogens: silica, quartz. Risk of cancer depends on duration and level of exposure to this product as a dust or aerosol mist.

- Other Information**
- This product contains petroleum asphalt. Petroleum asphalt is not listed as a carcinogen by OSHA or NTP. The National Institute of Occupational Safety and Health (NIOSH), has concluded that at higher temperatures roofing asphalt fumes are a potential occupational carcinogen. If this product is heated or comes in contact with heated material, avoid breathing fumes. This product may contain small amounts of polycyclic aromatic hydrocarbons (PAH's) which are recognized carcinogens in humans and experimental animals. Mouse skin painting studies of roofing asphalt vapor concentrate have shown evidence of tumor formation associated with localized skin irritation in recent studies. Inhalation studies of high airborne concentrations of asphalt/bitumen fumes in rats and mice produced bronchitis, pneumonitis, and lung changes such as fibrosis and cell damage.

Section 12 - Ecological Information

- Ecological Fate** • No data available.
Persistence/Degradability • No data available.
Bioaccumulation Potential • No data available.
Mobility in Soil • No data available.

Section 13 - Disposal Considerations

Product • Dispose in accordance with applicable federal, state, and local government regulations. Do not allow into any sewer on the ground, or into any body of water.

Section 14 - Transportation Information

DOT: Combustible Liquid, UN1993; Hazard Class:3; Packing Group: III **DOT: Not restricted** if shipped in containers <450L (119 gallons) Restricted if shipped in containers >450L (119 gallons)

TDG - Canada Transportation of Dangerous Goods: Tars, Liquids; UN1999; Hazard Class: 3; Packing Group: III

IMO/IMDG –International Maritime Transport • TARS, LIQUID; UN1999; Hazard Class: 3; Packing Group: III –IMDG Code 2.3.2.5 - exempted from marking, labeling & testing of packages.

IATA - International Air Transport Association - TARS, LIQUID; UN1999; Hazard Class: 3; Packing Group: III.

Section 15 - Regulatory Information

SARA Hazard Classifications • Acute, Chronic

Risk & Safety Phrases • California PROP 65: Asphalt and Asphalt Fumes may contain detectable amounts of chemicals known to the State of California to cause cancer or reproductive harm.

| State Right To Know | | | |
|---|------------|-----|-----|
| Component | CAS | MA | NJ |
| Asphalt | 8052-42-4 | Yes | Yes |
| mineral spirits | 8052-41-3 | Yes | Yes |
| Solvent naphtha (petroleum), light aromatic | 64742-95-6 | No | No |
| SBS Polymer | 9003-55-8 | No | No |
| Benzene, 1,3,5-trimethyl | 108-67-8 | Yes | No |
| 1,2,4-Trimethylbenzene | 95-63-6 | Yes | Yes |

| Inventory | | |
|---|------------|------|
| Component | CAS | TSCA |
| Asphalt | 8052-42-4 | Yes |
| mineral spirits | 8052-41-3 | Yes |
| Solvent naphtha (petroleum), light aromatic | 64742-95-6 | Yes |
| Benzene, 1,3,5-trimethyl | 108-67-8 | Yes |
| 1,2,4-Trimethylbenzene | 95-63-6 | Yes |

Canada

Labor

Canada - WHMIS - Classifications of Substances

- | | | | |
|--|------------|--------------|------------|
| •Asphalt | 8052-42-4 | 50% TO 70% | Not Listed |
| •1,2,4-Trimethylbenzene | 95-63-6 | 0.1% TO 0.5% | B3 |
| •Solvent naphtha (petroleum), light aromatic | 64742-95-6 | 10% TO 20% | B3, D2B |
| •mineral spirits | 8052-41-3 | 15% TO 25% | B3, D2B |

| | | | |
|---------------------------|-----------|-----------|---|
| •Benzene, 1,3,5-trimethyl | 108-67-8 | 1% TO 5% | B3 |
| •SBS Polymer | 9003-55-8 | 5% TO 15% | Uncontrolled product according to WHMIS classification criteria |

United States

Environment

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

| | | | |
|--|------------|--------------|--------------------------------|
| •Asphalt | 8052-42-4 | 50% TO 70% | Not Listed |
| •1,2,4-Trimethylbenzene | 95-63-6 | 0.1% TO 0.5% | 1.0 % de minimis concentration |
| •Solvent naphtha (petroleum), light aromatic | 64742-95-6 | 10% TO 20% | Not Listed |
| •mineral spirits | 8052-41-3 | 15% TO 25% | Not Listed |
| •Benzene, 1,3,5-trimethyl | 108-67-8 | 1% TO 5% | Not Listed |
| •SBS Polymer | 9003-55-8 | 5% TO 15% | Not Listed |

Section 16 - Other Information

Prepared By

- GG Inc.

Last Revision Date

- 7/24/2017

Disclaimer/Statement of Liability

- This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to verify the suitability and completeness of such information for particular use. APOC does not accept liability for any loss or damage that may occur from the use of this information.

