



COMPLIANCE: ASBESTOS FREE, Exceeds performance of ASTM D1227.

DESCRIPTION: APOC® 325 Pro-Gard Foundation & Roof Coating is an emulsion based coating for use in the construction of homes and buildings. Pro-Gard is manufactured using a unique milling Process that emulsifies asphalt resin to create an easy to use, yet extremely durable coating. Pro-Gard can be used to seal a variety of surfaces including foundations, roofs, retaining walls, concrete, wood, metal and other building materials. Pro-Gard has excellent weathering qualities, is non-flammable and virtually odorless. It is also ideal for use as an anti-corrosive coating. Finally, APOC® 325 contains no solvents so it will not deteriorate or harm insulation or styrofoam boards and is easy to use and clean up. **DO NOT ALLOW STORED PRODUCT TO FREEZE.**

PREPARATION: All surfaces must be clean, have proper drainage and be free of surface rust, dust and any other foreign matter. Roof surface may be damp (from morning dew), however surfaces may not be saturated with water. Brush clean all cracks, holes, and damaged or rusted areas with a wire brush. Repair using APOC White Roof Patch and Glass or Polyester Fabric. **DO NOT HEAT OR THIN. DO NOT APPLY IF RAIN IS EXPECTED WITHIN 36 HOURS.**

APPLICATION: For exterior use only. Protective clothing and eyewear should be used during application of this product. Always apply on a clear, warm sunny day. Apply in morning hours to allow maximum cure time. Application should be completed a minimum of 4 hours prior to sunset. Temperatures must be above 55 °F (for 24 hours) and rising, but not above 110 °F. Apply using professional airless sprayer, brush or 1/2" to 3/4" nap roller. See system specifications for coverage rates. Cure times vary depending on coverage rates, humidity, temperature and texture of surface. Allow a minimum of 4 hours between coats. **DO NOT HEAT OR THIN. DO NOT APPLY TO DRIVEWAY SURFACES.**

SPRAY INFO: 1000-1500 PSI, .061-.099 Tip Size, 3-6 GPM

PRECAUTIONS: Do not store at temperatures below 50 °F. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 110 °F. This manufacturer also disclaims liability for flat surface application where poor drainage or moisture may prevail. Seal container when not in use.

CLEAN-UP: Clean tools with warm water and soap.

©2008 Gardner-Gibson, Inc.
Manufactured by / Fabricado por:
Gardner-Gibson, Inc.
P.O. Box 5449, Tampa, FL 33675

See SDS for more information

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS:

Weight Per Gallon	8.5 lbs.
Residue by Evaporation*	42%
Adhesion to Polyurethane Foam	Excellent
Tool Application	Brush or Spray
Skin Time (50% Relative Humidity, 70 °F)	4 - 8 hours
Full Cure (50% Relative Humidity, 70 °F)	24 - 48 hours
Application Temperatures	55 °F - 110 °F
Clean-up Tools	Warm water, soap

*Note: Percentage may vary + or - 5%

Approx. Shipping Weights: (Note: All approx. weights include container)

55 gallon drum (208.2L)	510 lbs.
275 gallon tote (1,039.5L)	2,450 lbs.

VOC: <10 (regulatory)

HANDLING PRECAUTIONS: Product safety information required for safe use is not included. Before handling, read product safety data sheets and container labels for safe use and for physical and health hazard information. Safety data sheets are available on the APOC website at www.apoc.com. You can also obtain a copy from your local APOC Distributor or APOC sales representative.

LIMITED WARRANTY AND DISCLAIMER: For limited warranty and disclaimer information, contact the Gardner-Gibson, Inc. office at 1-800-237-1155.