



482F FIRM POLYESTER REINFORCING FABRIC

TECHNICAL DATA SHEET



DESCRIPTION:

APOC® 482F Firm Polyester Reinforcing Fabric stitchbonded polyester is a high quality and durable reinforcement used in roof restoration systems, repair of roof splits, and base flashing details. APOC® 482F is typically used with asphalt emulsion and/or solvent-based cold process systems. It can also be used as a reinforcement for cements, neoprene sealants, asphalt coatings, white roof mastic and white elastomeric coatings.

Stitchbonding offers an unusual combination of high strength properties with good elongation for excellent thermal stress force accommodations.

APOC® 482F is a firm polyester that will track straight in field areas. It is also much easier to handle and apply without ridging or wrinkles.

See specifications for detailed application instructions.

STORAGE & HANDLING PRECAUTIONS:

Before handling, read product safety data sheets and container labels for safe use and for physical and health hazard information. Safety Data Sheets are available on the APOC website at www.apoc.com. You can also obtain a copy from your local APOC Distributor or APOC sales representative.

WARRANTY & DISCLAIMER:

Register your warranty for extended warranty terms within 60 days of the completion of the project at www.apoc.com/pages/warranty. APOC Roofing Systems, LLC hereby warrants to the original purchaser, contingent upon original proof of purchase, that this product will be free from any defects that may materially and adversely affect the product's performance for a period of one year from the date of original purchase.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS:

Weight	2.7 oz. per sq. yd.
Tensile Strength (ASTM D-5034)	49 lbs.*
Elongation (ASTM D-5034)	38%*
Ball Burst (ASTM D-3787)	69 lbs.
Trapezoid (ASTM D-1117)	17 lbs.

*Average machine and cross machine direction

Approx. Shipping Weights:

(Note: All approx. weights include container)

Roll Size	Carton Weight
40" x 324'	22 lb.

