



COMPLIANCE: ASBESTOS FREE. California products meet Los Angeles County A.P.C.D. (Rule#102).

DESCRIPTION: **APOC® 567 PRO-TAC** Reinforced Self Adhering Membrane is an easy to apply SBS Rubberized Membrane used for a variety of roofing and waterproofing applications. APOC® 567 comes in 12" and 36" rolls that are 50 ft. in length. It's 12" width is primarily used for flashing perimeter metal edge, curbs, drains and metal flanges. Full width sheets can be used to flash under HVAC units and over metal and wood covers on curbs. Can also be used as a base ply or patch and repair systems over insulation board. It's high tensile and elongation make it an excellent split repair reinforcement for existing BUR, SBS and APP modified bitumen systems. It requires no open flame torch or adhesive to apply. Remove release paper before applying. APOC® reflective coating must be applied to protect surface from the sun and UV exposure.

APPLICATION: For exterior use only. It is recommended to prime asphalt and metal surfaces with APOC® 103 Asphalt Primer prior to application. For wood or gypsum type decks use APOC® 560 SA Primer. Application should take place in temperatures a minimum of 50 °F and rising to a clean, dry and sound substrate. For specific instructions see APOC specifications and details.

©2010 Gardner-Gibson, Inc.
Manufactured by / Fabricado por:
Gardner-Gibson, Inc.
P.O. Box 5449, Tampa, FL 33675

See SDS for more info

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS:

Application Method	Self Adhered Membrane
Thickness (ASTM D1777)	75 mils
Elongation (ASTM D1682)	85% MD
Water Vapor Permeance (ASTM E96)	0.1 perm max.
Application Temperature	50 °F & Rising
Puncture Resistance (ASTM E154)	200 lbs.
Size 3 rolls @ 12" x 50'	1.5 sq.
Size 36" x 50'	1.5 sq.

HANDLING PRECAUTIONS: Product safety information required for safe use is not included. Before handling, read product safety data sheets and container labels for safe use and for physical and health hazard information. Safety Data Sheets are available on the APOC website at www.apoc.com. You can also obtain a copy from your local APOC Distributor or APOC sales representative.

LIMITED WARRANTY AND DISCLAIMER: To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance and is subject to change without prior notice. User must contact APOC to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. Liability, if any, is limited to replacement of product unless installed by an approved contractor in accordance with APOC warranty procedures and program.

For limited warranty and disclaimer information, visit our website at: www.apoc.com/productwarrantyinfo.