

PRO'S CHOICE™

PC200 Asphalt Roof Primer

COMPLIANCE: EXCEEDS PERFORMANCE REQUIREMENTS OF ASTM D 41. ASBESTOS FREE.

DESCRIPTION: Pro's Choice™ PC200 Asphalt Roof Primer is an asphalt based primer used for priming built up and modified roofing products. It is also excellent for priming metal surfaces and accessories. Asphalt primer provides superior adhesion and allows better bonding of coatings and repair materials. It is also an ideal product for priming concrete surfaces.

PREPARATION: All surfaces must have proper drainage and be clean, dry and free of surface rust and any other foreign matter. Repair all problem areas with PC801 All Weather Rubberized Cement. MIX THOROUGHLY. DO NOT HEAT OR THIN. DO NOT APPLY IF RAIN IS EXPECTED WITHIN 24 HOURS.

FOR BEST RESULTS: Apply on clear sunny day when surface temperatures are between 40° and 120° F. In colder weather product should be stored in heated room (65° to 80°F) at least 24 hours prior to application.

APPLICATION: For exterior use only. Product should be applied according to NRCA guidelines. Protective clothing and eye wear should be used during application of these products. Apply with professional airless sprayer, brush or roller. Work material to a smooth and even consistency. Avoid excessive build up or puddles of primer. DO NOT APPLY TO ASPHALT DRIVEWAYS. For professional use only.

PRECAUTIONS: When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 110° F. This manufacturer also disclaims liability for flat surface application where poor drainage or moisture may prevail. For exterior use only. Do not reuse empty containers. Do not use in drinking water or food systems. Seal container when not in use.

CLEAN-UP: Clean tools with paint thinner or mineral spirits.

WARRANTY AND DISCLAIMER: This product is warranted to free from any manufacturing defects at the time this product is manufactured. Remedy for this warranty is strictly limited to the replacement of product. For full warranty terms and conditions visit www.proschoice.us.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight Per Gallon	7.4-7.9 lbs.
Combustible Solvents	Mineral Spirits
Consistency	Brush or Spray
Cure Time (50% Relative Humidity, 70°F)	4-8 hours
Full Cure (50% Relative Humidity, 70°F)	24-48 hours
Application Temperatures	40° - 120°F
Flammability	105°F
Clean-up Tools	Paint Thinner, Mineral Spirits

Approx. Shipping Weights: (Note: All approx. weights include container.)

Size	Product Code	Weight
5 gallons (18.9L)	6011-9-30	40 lbs.
55 drums (208.2L)	6011-9-55	440 lbs.

**CAUTION! COMBUSTIBLE MIXTURE
N.Y.F.D. C. OF A. NO. 4792
CAUTION – COMBUSTIBLE MIXTURE
CAUTION!: HARMFUL OR FATAL IF SWALLOWED. EYE,
SKIN AND RESPIRATORY IRRITANT.**

Contains Petroleum Distillate. Keep away from heat, sparks and open flame. If swallowed DO NOT induce vomiting. Call physician immediately. In case of : Eye contact - flush with large amounts of room temperature water for 15 minutes; Skin contact - wash thoroughly with soap and water; Irregular or stopped breathing - administer oxygen, give artificial respiration and get medical attention immediately. Avoid prolonged breathing of vapor or spray mist.

**FOR EXTERIOR USE ONLY
Use with adequate Ventilation
Keep Out of Reach of Children
VOC/VOS - 350 g/l max. (2.9 lbs./gal.)**

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

PETROLEUM ASPHALT C.A.S.# 8052-42-4
MINERAL SPIRITS C.A.S.# 8052-41-3

©2008 Gardner Asphalt Corporation Manufactured
by / Fabricado por: Gardner Asphalt Corporation
P.O. Box 5449, Tampa, FL 33675

See MSDS for more info



Gardner Asphalt Corporation • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardnerasphalt.com