

PRO'S CHOICE™

PC601 Cold Process Adhesive & Lap Cement

COMPLIANCE: EXCEEDS PERFORMANCE REQUIREMENTS OF ASTM D3019. MIAMI-DADE COUNTY PRODUCT CONTROL APPROVED. ASBESTOS FREE.

DESCRIPTION: Pro's Choice™ PC601 Cold Process Adhesive & Lap Cement is designed for adhering a variety of roofing sheets and membranes. This adhesive may be used with smooth surfaced, slate surfaced, cold process roofing membranes or double coated sheets. It is also recommended for laying glass roofing sheets, is excellent for bonding selvage edge roofing and can be used in polyester maintenance systems. Not recommended with 15, 20, or 30 lb. uncoated felts.

PREPARATION: All surfaces must have proper drainage and be clean, dry and free of surface rust and any other foreign matter. Repair all problem areas with PC801 All Weather Rubberized Cement. MIX THOROUGHLY. DO NOT HEAT OR THIN.

FOR BEST RESULTS: Apply on clear sunny day when surface temperatures are between 40° and 120° F. In colder weather product should be stored in heated room (65° to 80° F) at least 24 hours prior to application. After a minimum of 45 days cure time, apply a reflective roof coating. This will greatly extend the life of the roof.

APPLICATION: For exterior use only. Product should be applied according to NRCA guidelines. Protective clothing and eye wear should be used during application of these products. DO NOT APPLY IF RAIN IS EXPECTED WITHIN 24 HOURS. Apply with a brush or trowel to form a thin and continuous film. Avoid heavy mounds of mass accumulation. The cement will remain tacky for approximately 1 hour after application. Allow open time to permit some solvent evaporation, but sheets should be fully adhered in position before adhesive sets. For best results - roll of use a push broom to press the sheets into place after they are set to ensure a tight bond between plies. Coverage rate is approximately 1 to 2 gallons per 100 sq. ft.

PRECAUTIONS: When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 110°F. This manufacturer also disclaims liability for flat surface application where poor drainage or moisture may prevail. Do not reuse empty containers. Do not use in drinking water or food systems. Seal container when not in use.

CLEAN-UP: Clean tools with paint thinner or mineral spirits.

WARRANTY AND DISCLAIMER: This product is warranted to free from any manufacturing defects at the time this product is manufactured. Remedy for this warranty is strictly limited to the replacement of product. For full warranty terms and conditions visit www.proschoice.us.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight Per Gallon	8.0-8.5 lbs.
Combustible Solvents	Mineral Spirits
Consistency	Brush
Cure Time (50% Relative Humidity, 70°F)	24-48 hours
Full Cure (50% Relative Humidity, 70°F)	90 Days
Application Temperatures	40° - 120°F
Flammability	105°F
Clean-up Tools	Paint Thinner, Mineral Spirits

Approx. Shipping Weights: (Note: All approx. weights include container.)

Size	Product Code	Weight
5 gallons (18.9L)	6156-9-30	43 lbs.
55 drums (208.2L)	6156-9-55	475 lbs.

CAUTION! COMBUSTIBLE MIXTURE
N.Y.F.D. C. OF A. NO. 4792
CAUTION – COMBUSTIBLE MIXTURE
CAUTION!: HARMFUL OR FATAL IF SWALLOWED. EYE,
SKIN AND RESPIRATORY IRRITANT.

Contains Petroleum Distillate. Keep away from heat, sparks and open flame. If swallowed DO NOT induce vomiting. Call physician immediately. In case of : Eye contact - flush with large amounts of room temperature water for 15 minutes; Skin contact - wash thoroughly with soap and water; Irregular or stopped breathing - administer oxygen, give artificial respiration and get medical attention immediately. Avoid prolonged breathing of vapor or spray mist.

FOR EXTERIOR USE ONLY
Use with adequate Ventilation
Keep Out of Reach of Children
VOC/VOS - 250 g/l max. (2.1 lbs./gal.)

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

PETROLEUM ASPHALT	C.A.S.# 8052-42-4
MINERAL SPIRITS	C.A.S.# 8052-41-3
CELLULOSE FIBER	C.A.S.# 9004-34-6
INORGANIC FILLER	C.A.S.# 1317-65-3

©2008 Gardner Asphalt Corporation Manufactured
by / Fabricado por: Gardner Asphalt Corporation
P.O. Box 5449, Tampa, FL 33675

See MSDS for more info

MIAMI-DADE COUNTY
APPROVED



Gardner Asphalt Corporation • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardnerasphalt.com