

SAFETY DATA SHEET SDS No. M1.1.1.A

Date prepared: MARCH 2010 Date revised: DECEMBER 2024

SDS No. IM.1.1.1.A

Section 1 – Product Identification

IDENTITY:

(: Product Name: InjectPro-PM3811-SoilStabilizer InjectPro-PM3811-Flex InjectPro-PM3811-UltraSeal (SDS 1 of 3) Component – A (liquid resin)

Chemical Characterization: Aqueous preparation on basis of a specific methacrylate Product Use Description: Injection resin

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

AQUAFIN, INC. 505 BLUE BALL RD. #160 ELKTON, MD 21921 24 hr Emergency Phone: Chem-Tel(800) 255-3924Information Phone No.(410) 392-2300www.aquafin.netinfo@aquafin.net

Recommended use of the chemical and restriction on use:

Refer to the product technical data sheet. For industrial and professional users.

Section 2 – Hazards Identification

GHS Classification:

Skin irritation, Category 2 Skin sensitizer, Category 1 Eye irritation, Category 2A

GHS Label element:

Hazard Pictograms



Signal Word:

Hazard Statements:	Causes skin irritation.
H315:	Causes serious eye irritation.
H319: H317	May cause an allergic skin reaction.

Warning

Precautionary Statements: **Prevention:**

- P101: If medical advice is needed, have product container or label at hand.
- P102: Keep out of reach of children.
- P103: Read label before use.
- P264: Wash throughly after handling.
- P280: Wear protective gloves/protective clothing/eye protection/face protection.
- P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
- P272 Contaminated work clothing should not be allowed out of the workplace.

Response:

P305 + P351: P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



SAFETY DATA SHEET SDS No. M1.1.1.A

Response: P337+P313: P302 + P352: P362 + P364: P333 + P313:	If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water. Take off contaminated clothing. Wash it before reuse. If skin irritation or a rash occurs: Get medical advice/attention.
Storage: P403 + P410: P405:	Store in a well-ventilated place. Protect from sunlight. Store locked up.
Disposal: P501:	Dispose of contents/container to an approved waste disposal site.

Section 3 – Composition / Information on Hazardous Ingredients

PM3811-UltraSeal (COMPONENT-A-Liquid Resin)

Components	CAS No.	OSHA PEL	ACGIH TLV	Percent
2-hydroxyethyl methacrylate	868-77-9			> 90
proprietary acrylate	TS			TS

Note: There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Section 4 – First Aid Measures

Inhalation: Supply fresh air and consult a physician if breathing becomes difficult.

- Ingestion: Immediately drink plenty of milk or water and get medical attention. Only induce vomiting if directed by a physician. Never give anything by mouth to an unconscious person.
- **Skin Contact:** Rinse skin with soap and plenty of water immediately. Do not use solvents or thinners. Remove contaminated clothing and shoes. Seek medical advice. Wash clothing before reuse.
- **Eye Contact:** Rinse cautiously with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Remove contact lenses. Obtain medical attention without delay, preferably from an ophthalmologist.

Section 5 – Fire Fighting Measures

Extinguishing Media:	Use water spray, alcohol resistant foam, dry chemical or carbon dioxide.
Other Flammable Properties:	Explosive mixtures may occur at temperatures at or above the flashpoint.
Fire Fighting Procedures:	As in any fire, wear self-contained breathing apparatus pressure- demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Containers can build up pressure if exposed to heat (fire). Cool with water spray. Do not scatter material with high pressure water streams.



Hazardous Decomposition Products: Not known.

Unusual Fire and Explosion Hazards: Bursting and explosion of container possible due to increase of pressure when exposed to increasing heat. In case of fire, cool nearby containers with water fog.

Section 6 – Accidental Release MeasuresPerson-related Safety Precautions:Provide plenty of fresh air. Avoid eye and skin contact. Avoid inhalation
of vapors. Wear personal protective equipment.Methods for cleaning-up:Contain and collect spillage with non-combustible, absorbent materials.
I.e. sand, earth, vermiculite, diatomaceous earth, universal binders,
sawdust and place in container for disposal.Waste Disposal Method:Dispose in accordance with local, state and federal regulations.Ecological Information:Do not allow product to reach ground water, bodies of water, or storm
water or sewage systems.

Section 7 – Handling and Storage

- **Handling:** Avoid breathing vapor or mist. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Follow all SDS/label precautions even after the container is emptied because it may retain product residues.
- **Storage:** Keep container closed when not in use. Do not store in direct sunlight. Keep in the original container at a temperature not exceeding 30°C (86°F). Store in a cool, dry place. Fill the container by approximately 90% as oxygen (air) is required for stabilization. With large storage containers make sure the oxygen (air) supply is sufficient to ensure stability.

Section 8 – Exposure Controls / Personal Protection

General Information:	Eye-wash bottle must be available. The product does not contain any relevant quantities of materials that have to be monitored at the workplace.
Engineering Controls:	Use adequate ventilation.
Respiratory Protection:	Use local exhaust ventilation.
Skin Protection:	Wear chemical resistant protective clothing and footwear impervious to the product if there is a potential for skin contact.
Hand Protection:	Glove(s): neoprene.
Eye Protection:	Use safety goggles or face shield.
Other Protective Equipment:	A safety shower and eye wash fountain should be readily available.
Work/Hygienic Practices:	Wash hands before breaks and after work, and before eating, drinking or smoking.



IDENTITY: IDENTITY: InjectPro-PM3811-SoilStabilizer, PM3811-Flex, PM3811-UltraSeal (COMPONENT-A-Liquid Resin)

SAFETY DATA SHEET SDS No. M1.1.1.A

Section 9 – Physical and Chemical Properties

Physical state:	Liquid
Color:	Clear to brownish
Odor:	Acrylic
Solubility in water:	at 20°C / 68°F miscible
pH-value:	N/A
Boiling point:	>100°C (>212°F)
Flash point:	103°C (>217°F) DIN EN 22719
Specific Gravity (water = 1) at 20°C:	1.07 g/cm ³
Viscosity, (kinematic) at 20°C:	1 – 3 cps
VOC:	0 g/L
Vapor density (air = 1):	is heavier than air
Vapor pressure:	0.08 hPa (= mbar) at 20 °C / 68 °F (OECD 104, dynamic method)
Evaporation rate:	is slower than butyl acetate
VOC:	0 g/L
Odor threshold:	not available
Auto ignition Temperature:	No data available
Lower explosion Limit:	No data available
Upper explosion Limit:	No data available

Section 10 – Stability and Reactivity

Reactivity:	No dangerous reaction known under conditions of normal use.
Hazardous Decomposition:	None if used as directed.
Chemical Stability:	Stable under normal temperatures and pressures.
Conditions To Avoid:	See 'Hazardous Polymerization' for conditions to avoid.
Hazardous Polymerization:	The product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is noticeably exceeded, the product may polymerize with heat evolution. Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.
Incompatibilities:	Reducing agents. Tertiary amines. Heavy metals. Peroxides. Oxidizing agents. Mineral acids.

Section 11 – Toxicological Information

Acute toxicity:

None available.

Section 12 – Ecological Information

Information on Elimination (Persistence and Degradability)

• **Biodegradability** readily degradable, OECD 301 D, Closed Bottle Test, 28 d (plant or external testing) Related to substance: 2-hydroxyethyl methacrylate 84%



 Ecotoxicological Effect Fish Toxicity LC50 Pimephales promelas, flow through, 96 h Related to substance: 2-hydroxyethyl methacrylate Daphnia Toxicity 		227 mg/l
 NOEC Daphnia magna, OECD 202 part 2, flow th Related to substance: 2-hydroxyethyl methacrylate EC50 Daphnia magna, OECD 202 part 1, static te Related to substance: 2-hydroxyethyl methacrylate 		24.1 mg/l g/l
 Bacteria Toxicity EC0 Pseudomonas fluorescens, DEV L8, 16 h (plant or external testing) Related to substance: 2-hydroxyethyl methacrylate 	> 3,00	0 mg/l
Further lafe we find an Eastern	II	

Further Information on Ecology:

Do not allow to enter soil, waterways or waste water.

Section 13 – Disposal Considerations

Product waste: Must be disposed of in a manner consistent with federal, state and local regulations.

Packaging waste: Must be disposed of in a manner consistent with federal, state and local regulations.

Section 14 – Transport Information

USDOT (Domestic Surface):	Not regulated
IMDG Information: (Ocean)	Not regulated
IATA/ICAO (Air):	Not regulated
Canada TDG:	Not regulated
Hazard Class:	Not applicable
Packaging:	Not applicable

Section 15 – Regulatory Information

TSCA Status: Listed or exempt

TSCA Status:	Listed or exempt
SARA 311/312 Hazard	
Categories (40CFR370):	Acute

US State Regulatory Information:

Component/CASRN	New	Pennsylva	Massachuse	California	California
	Jersey	nia	tts	Prop. 65	Prop. 65
	RTK	RTK	RTK	Cancer	Reproduction
2-hydroxyethyl methacrylate (CASRN 868-77-9)	NO	NO	NO	NO	NO

SARA 313 Notification:

This product contains no toxic chemicals subject to the SARA 313 supplier notification requirements.

CERCLA:	No CERCLA chemicals exist in this product.
IDL:	Ingredient Disclosure List (IDL), the following components are on the list: Acrylates and methacrylates.

Section 16 – Other Information

Abbreviations and acronyms:

USDOT:	United States Department of Transportation.
IMDG:	International Maritime Code for Dangerous Goods.
IATA:	International Air Transport Association.
CAS:	Chemical Abstracts Service (Division of the American Chemical Society).
LC50:	Lethal concentration, 50 percent.
LD50:	Lethal dose, 50 percent.

SDS prepared by:

Aquafin product safety department.

DISCLAIMER:

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, expressed or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use. Aquafin shall not be responsible for the use of this product in a manner to infringe on any patent or any other intellectual property rights held by others. User is responsible for determining appropriate safety measures and for applying the legislation covering his own activities. We recommend that user makes tests to determine the suitability of a product for its particular purpose prior to use.

END OF SDS

(December 3, 2024)