SDS No. 4.1.1

Date prepared: JANUARY 2002

Date revised: JANUARY 2019 SDS No.4.1.1

### Section 1 - Product Identification

IDENTITY: Product Name: MORTAR-LN

Chemical Characterization: Cement - Preparation

Product Use Description: Structural waterproof repair mortar

AQUAFIN, INC. Emergency Phone No. (800) 394-1410 505 BLUE BALL RD. #160 Information Phone No. (410) 392-2300

ELKTON, MD 21921 <u>info@aquafin.net</u> <u>www.aquafin.net</u>

Recommended use of the chemical and restriction on use: Refer to the product technical data sheet.

For industrial and professional users.

# Section 2 - Hazards Identification

#### **GHS Classification:**

Skin irritation, Category 2 H315: Causes skin irritation (alkaline when moistened)

Serious eye damage, Category 1 H318: Causes serious eye damage Respiratory system; Category 3 H335: May cause respiratory irritation

Carcinogenity, Category 1A H350: May cause cancer

#### **GHS Label element:**

### **Hazard Pictograms**



**!** 



GHS05 GHS07

GHS08

Signal Word: Danger

Hazard Statements:

H315: Causes skin irritation (alkaline when moistened).

H318: Causes serious eye damage. H335: May cause respiratory irritation.

H350: May cause cancer.

#### **Precautionary Statements:**

Prevention:

P264: Wash skin thoroughly after handling.
P280: Wear eye protection/face protection.
P280: Wear protective gloves.

P281: Use protective equipment as required.

Response:

P302 + P352: IF ON SKIN: Wash with plenty of water.

P304 + P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable

for breathing.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned, get medical advice/attention.
P332 + P313: IF skin irritation occurs, get medical advice/attention.
P362: Take off contaminated clothing and wash before reuse.

SDS No. 4.1.1

Storage:

P403 + P232: Store in a well-ventilated place. Protect from moisture.

Disposal:

P501: Dispose of contents/container to an approved waste disposal site.
P502: Refer to manufacturer/supplier for information on recovery/recycling.

# Section 3 - Composition / Information on Ingredients

Hazardous Components	CAS No.	TLV	PEL	Weight %
Portland Cement	65997-15-1	10 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	25 - 50
Calcium Aluminate Cement	65997-16-2	10 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	2 - 10
Calcium Hydroxide	1305-62-0	10 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	0.5 - 10
Silica Amorphous	7631-86-9	10 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	2.5 - 10
Crystalline Quartz Silica (SiO <sub>2</sub> )	14808-60-7	0.05 mg/m <sup>3</sup>	0.1 mg/m <sup>3</sup>	30 - 70

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence not require reporting in this section.

### Section 4 - First Aid Measures

After Inhalation: Remove subject to fresh air. Administer oxygen if difficulty with breathing. Consult a

physician.

After Ingestion: Immediately seek medical attention. Do not induce vomiting without medical advice. If

conscious, drink plenty of water.

After Skin Contact: Instantly wash skin with plenty of soap and water for at least 15 minutes. Wash clothing

before reuse. Seek medical attention if symptoms persist.

After Eye Contact: Rinse opened eye with plenty of running water for at least 15 minutes, lifting upper and

lower eyelids occasionally. Consult physician.

## Section 5 – Fire Fighting Measures

**Extinguishing Media:** Carbon dioxide (CO<sub>2</sub>), extinguishing powder, water fog, alcohol-resistant

foam.

Special Fire Fighting Procedures: As in any fire, wear full protective gear and NIOSH-approved self-

contained breathing apparatus with full face-piece operated in the

pressure demand or other positive pressure mode.

Unusual Fire and Explosion Hazards: No unusual fire or explosion hazards. Material can splatter above 212°F

(100°C).

#### Section 6 – Accidental Release Measures

Person-related Safety Precautions: Avoid causing dust. Avoid eye and skin contact.

**Environmental precautions:** Prevent material from reaching sewage and drainage systems or bodies

of water.

**Methods for Cleaning up:** Use dry cleanup methods that do not disperse dust into the air. With

SDS No. 4.1.1

water, material hydrates to a solid harmless waste. Wear personal protective equipment. Emergency procedures are not required.

# Section 7 – Handling and Storage

Handling: Avoid causing dust. Avoid eye and skin contact. Keep out of reach of children.

Storage: Store in a cool, dry enclosed area off the ground in tightly closed containers. Protect against

wetness and water. No special measures required against explosion and fires. Store away from

foodstuffs.

# **Section 8 – Exposure Controls / Personal Protection**

**Engineering Controls:** Use with adequate general and local exhaust ventilation.

Washing of the skin in the working area must be possible.

Eye-wash bottle must be available.

**Respiratory Protection:** Wear a properly fitted NIOSH approved respirator in poorly ventilated areas and/or if

high dust concentrations are encountered.

**Skin Protection:** When installing, wear appropriate protective rubber or plastic gloves to prevent

hand-skin exposure. Wear appropriate impervious clothing to prevent skin

exposure (long sleeve shirt and long pants).

**Eye Protection:** Wear tightly sealed safety glasses with side shields or goggles. Face shield as

necessary.

Work/Hygienic Practices: Wash hands before breaks and after work, and before eating, drinking or

smoking.

### Section 9 – Physical and Chemical Properties

Physical State: Powder

Appearance/Color: Cement / gray
Odor: Weak, characteristic

Solubility in water: Fully miscible

Boiling Point: N/A

**Melting Point:** >1,000°C (>1,832°F) **Flash Point:** Not combustible

Auto ignition: N/A

**Bulk Density:** approx. 1.6 kg/dm<sup>3</sup> pH (in water): 11 – 13.5 (Alkaline)

**VOC Concentration:** 0 g/l

# Section 10 - Stability and Reactivity

**Chemical Stability:** Stable under normal temperatures and pressures.

**Conditions to Avoid:** Avoid contact with humidity. Product hydrates (hardens) and becomes

unusable.

**Hazardous Decomposition Products:** No decomposition if used according to specifications.

Hazardous Polymerization: Will not occur.

SDS No. 4.1.1

**Incompatibilities:** None known.

## Section 11 – Toxicological Information

Acute Inhalation Toxicity:

<u>Product</u> <u>Type</u> <u>Value</u>

Silica, crystalline quartz

LC50

no data available

Portland cement

LC50

no data available

**Acute Oral Toxicity:** 

Silica, crystalline quartz LC50 (Oral) 1,300 mg/kg Portland cement LC50 (Oral) 2,000 mg/kg

**Acute Dermal Toxicity** 

Silica, crystalline quartz LC50 (Dermal) no data available Portland cement LC50 (Dermal) no data available

**Primary Irritant Effect:** 

On the skin: Irritant for skin and mucous membranes

• On the eye: Irritant effect

Sensitization: No sensitizing effect known.

## Section 12 – Ecological Information

**Ecological Information:** The unused product is slight water pollutant. Large quantities may be toxic to fish. Do

not allow undiluted product or large quantities to reach into waterways or drains.

## Section 13 - Disposal Considerations

Waste Disposal Method: Dispose of in a manner consistent with federal, state and local regulations. Do

not dispose together with household garbage. Do not allow product to reach

sewage system.

Unused Residue or Dry Spillage: Pick up dry material. Possibly reuse depending on amount of contamination.

Prevent dust exposure. In case of disposal, harden with water and dispose in

accordance to local regulations.

**Slurries:** Allow to harden and dispose of as described above.

**Container disposal:** Completely emptied packaging can be given for recycling.

## Section 14 - Transport Information

RCRA Hazard Class: Non-hazardous

USDOT (Domestic Surface)

IMDG (Ocean) Hazard Class or Division:

IATA/ICAO (Air) Hazard Class or Division:

Not regulated

Not regulated

Not regulated

Not regulated

Not regulated

Not regulated

Not listed

## Section 15 - Regulatory Information

SARA 311/312 (RTK): Hazard Categories: Acute Health: YES

Chronic Health: YES

SDS No. 4.1.1

**SARA Section 313 Notification:** This product does not contain any ingredients regulated under Section

313 of the Emergency Planning and Community Right-to-Know Act of

1986 or CFR 372.

CERCLA: No CERCLA chemicals exist in this product above reportable

concentrations.

**TSCA Section 12(b) Export Notification:** There are no reportable TSCA 12(b) Chemicals in this product.

State Regulations: State RTK CAS Number Chemical name

MA, NJ, PA 65997-15-1 Cement, Portland, chemicals MA, NJ, PA 14808-60-7 Silica, crystalline quartz

California Proposition 65: Warning - This product contains a chemical known to the State of

California to cause cancer, birth defects, or other reproductive harm:

CAS 14808-60-7: Silica, crystalline quartz.

### Section 16 – Other Information

(Hazard Rating: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe; \* = Chronic)

HMIS III rating:

Health: 2\* Flammability: 0 Physical hazard: 0

Abbreviations and acronyms:

USDOT: United States Department of Transportation.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

LC50: Lethal concentration, 50 percent.

LD50: Lethal dose, 50 percent.

**SDS prepared by:** Aquafin product safety department.

#### **DISCLAIMER:**

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, expressed or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use. Aquafin shall not be responsible for the use of this product in a manner to infringe on any patent or any other intellectual property rights held by others. User is responsible for determining appropriate safety measures and for applying the legislation covering his own activities. We recommend that user makes tests to determine the suitability of a product for its particular purpose prior to use.

**END OF SDS** 

(January 22, 2019)