

ARDEX 8+9™

Rapid Waterproofing and Crack Isolation Compound


Two-component, solvent-free, Portland cement and acrylic-based liquid system that produces a flexible waterproof coating to protect substrates from topside side water infiltration. ARDEX 8+9 provides an outstanding bonding layer for ARDEX tile and stone setting materials.

Key Features

- Ideal for commercial or residential showers, bathrooms and kitchens
- Now Available in Gray or White
- Cement on cement for a stronger bond
- Rapid setting- tile in as little as 90 minutes
- Crack isolation up to 1/8" (3 mm)
- 1/3 less cost per sq. ft. than competitors' products
- Easy to mix and apply



WHITE




GRAY

Installation

- **Packaging:**
 - Convenient kit: 1 gallon (3.78 L) ARDEX 8 / 9 lb. (4 kg) ARDEX 9
 - Commercial units: 3 gallons (11.34 L) ARDEX 8 / 27 lb. (12 kg) ARDEX 9
- **Coverage:**
 - Convenient kit: 100 sq. ft. per unit
 - Commercial units: 300 sq. ft. per unit
- **Pot life:** 45 minutes
- **Drying time:**
 - Initial coat: 30 to 45 minutes
 - Final coat: 60 minutes
- **Flood test:** 4 hours after the second coat has been applied



Performance



Visit www.youtube.com/ARDEX101 to watch ARDEX 8+9™ product demonstration video. For easy-to-use ARDEX Product Calculators and Product Information On the Go, download the ARDEX App at the iTunes Store or Google Play.



AF 394 8/16

WATERPROOFING AND CRACK ISOLATION



AMERICAS

888-512-7339

+1-725-203-5000

www.ardexamericas.com